HugAgent: Toward Cognitive-Level Human Alignment and Individual-Level Diversity in LLM Simulation

Anonymous Author(s)

Affiliation Address email

Abstract

Simulating human reasoning in open-ended tasks has long been a central aspiration in AI and cognitive science. While large language models now approximate human responses at scale, they remain tuned to population-level consensus, often erasing the individuality of reasoning styles and belief trajectories. To advance the vision of more human-like reasoning in machines, we introduce **HugAgent** (Human-Grounded AGENT Benchmark), which rethinks human reasoning simulation along three dimensions: (i) from averaged to individualized reasoning, (ii) from behavioral mimicry to cognitive alignment, and (iii) from vignette-based to **open-ended** data. The benchmark evaluates whether a model can predict a *spe*cific person's behavioral responses and the underlying reasoning dynamics in out-of-distribution scenarios, given partial evidence of their prior views. HugAgent adopts a dual-track design: a human track that automates and scales the think-aloud method to collect ecologically valid human reasoning data and a synthetic track for further scalability and systematic stress testing. This architecture enables low-cost, extensible expansion to new tasks and populations. Experiments with state-ofthe-art LLMs reveal persistent adaptation gaps, positioning HugAgent as the first extensible benchmark for aligning machine reasoning with the individuality of human thought. The benchmark, along with its complete data collection pipeline and companion chatbot, is open-sourced as *HugAgent* and *TraceYourThinking*.




Figure 1: Illustration of **HugAgent** operationalizing "average-to-individual" reasoning adaptation: a gray robot repeats population consensus, then observes an individual's nuanced reasoning, gradually aligns with that individual (turning colorful), and finally adapts under counterfactual updates (e.g., with eco-lamps). This illustrates the shift from consensus mimicry to individualized reasoning.

1 Introduction

2

3

8

9

10

12

13

14

15

16 17

18

19

21

22 23

24

25

28

29

Background. Large language models (LLMs) are increasingly used as social simulators—to roleplay individuals, build digital twins, and generate synthetic ('silicon') samples for testing social and policy ideas[1–4]. These systems promise scalability and accessibility: instead of recruiting thousands of people, researchers and practitioners can use LLMs to approximate human perspectives at scale. Yet because LLMs are pretrained on population-level corpora, they tend to collapse into an "average voice," capturing consensus patterns while erasing the individuality of personal histories, beliefs, and reasoning styles[5–7].

This paper asks a core question: can LLMs move from simulating the average to simulating the individual?

Submitted to 39th Conference on Neural Information Processing Systems (NeurIPS 2025). Do not distribute.

In other words, can they predict how a specific person would think, believe, and reason in new scenarios, given evidence of their past views? We formalize this broad challenge as **average-to-individual reasoning adaptation**, a measurable task that targets *intra-individual fidelity* in human simulation(formally defined in Section 2).

Motivation. Current benchmarks fail to capture this ability, across three key dimensions.

Intraagent vs. inter-agent fidelity. Existing pluralistic alignment benchmarks probe group dynamics and social influence[8], but neglect whether models can faithfully reproduce reasoning within a single agent, which is crucial for identity-consistent modeling.

Reasoning traces vs. behavioral outcomes. Large-scale "digital twin" datasets such as Agent Bank [1] and Twin-2K-500 [9] primarily assess static behavioral outcomes, but not the evolving reasoning trajectories of a single individual, which are essential for credible social simulation [10].

Open-ended vs. vignettes. Commonsense and social reasoning benchmarks (e.g., SocialIQA, ATOMIC) often reduce diverse answers to a single ground truth [11, 12]. Opinion-oriented datasets likewise emphasize aggregate patterns over individual variation [2, 6]. Theory-of-Mind style tests typically rely on short vignettes with designer labels [13, 14], which limits ecological validity and overlooks first-person reasoning traces that could serve as a richer gold standard [15].

Methodology. Motivated by these gaps, we introduce HugAgent, a benchmark that targets intra-46 agent fidelity by operationalizing average-to-individual reasoning adaptation as a measurable task. 47 For Dimension 1, HugAgent shifts the granularity from *inter-agent* to *intra-agent* fidelity: given a person's profile and reasoning history, a model must predict both their current belief state and how it would evolve when presented with new counterfactual evidence. In Dimension 2, HugAgent 50 advances beyond static outcomes toward reasoning trajectories. It collects first-person, out-loud self-reports as gold-standard reasoning traces. These traces offer a deeper target for prediction than the choice outcomes or survey responses typically captured in lab experiments. To address Dimension 53 3, instead of relying on vignette-style benchmarks, HugAgent builds evaluation around open-ended contexts. We curated real-world topics, beginning with socially and politically controversial issues 55 that introduce inherent conflicts. Through sustained follow-up questions, the benchmark probes participants' deliberate, System 2 style reasoning[16, 17], transforming the dataset from toy settings 57 into complex, open-ended domains. For a broader discussion of prior work on personalization, social 58 reasoning, and user modeling in LLMs, we refer readers to Appendix A.

To build such a benchmark at *scale* while retaining *ecological validity*(i.e., the extent to which findings reflect reasoning as it occurs in real-world contexts), **HugAgent** combines two complementary tracks. A *synthetic track* provides large, controlled datasets where belief shifts and reasoning paths can be systematically manipulated[18, 19]. A *human-grounded track* applies the same protocol to *real human participants*, yielding data anchored in individual variation[20].

65 **Contributions.** Our contributions are fourfold:

34

35

36

37

38

39

44

45

66

67

68 69

77

78

79

80

81

- What does it mean to adapt from the average to the individual? We formalize average-to-individual reasoning adaptation as a measurable task: predicting an individual's beliefs and reasoning trajectory from partial self-reported data, rather than collapsing variation into an "average" label.
- How well do today's models perform? We introduce HugAgent, a dual-track benchmark
 (synthetic + human) that evaluates both Belief State Inference and Belief Dynamics Update.
 Initial experiments with state-of-the-art LLMs provide baseline results and reveal adaptation gaps.
 https://anonymous.4open.science/r/HugAgent
- Where do they fail, and what can improve? Building on these evaluations, we conduct detailed error analyses across synthetic agents, human participants, and state-of-the-art LLMs. This uncovers recurring failure modes and points to concrete avenues for alignment.
 - How can such evaluation scale and persist? We release the entire pipeline as *open source*, including a semi-structured interview chatbot that elicits fine-grained, "out-loud" reasoning data on arbitrary topics. This provides the community with previously lacking resources for capturing not only static answers but also the reasoning processes behind them, ensuring HugAgent is reproducible, extensible, and sustainable. https://anonymous.4open.science/r/trace-your-thinking

By making "average-to-individual" reasoning adaptation measurable, **HugAgent** takes a first step toward a reproducible framework for studying human simulation at the level of individual reasoning.

85 2 Problem Setup and Theoretical Framing

We operationalize individual reasoning through *belief states* (snapshots) and *belief dynamics* (updates under interventions). This framing allows measurable comparison while respecting the diversity of human reasoning paths.

89 2.1 Formalization

96

107

110

111

114

115

We formalize *average-to-individual reasoning adaptation* by modeling an individual i's belief state as a distribution over d factors

$$b_i \equiv P_{\phi_i}(\mathbf{s} \mid \mathcal{C}_i), \quad \mathbf{s} \in \mathbb{R}^d,$$

with context C_i (e.g., demographics, transcripts). Under an intervention \mathcal{I}_t , beliefs evolve via

$$b_i^{t+1} = \mathcal{U}(b_i^t, \mathcal{I}_t), \quad \Delta b_i^t = \mathbb{E}_{b_i^{t+1}}[\mathbf{s}] - \mathbb{E}_{b_i^t}[\mathbf{s}].$$

Tasks. (i) Belief State Inference: infer stance/factor polarity from C_i . (ii) Belief Dynamics Update: predict stance shifts $\widehat{\Delta s}_i$ given (C_i, \mathcal{I}) . Metrics include accuracy, mean absolute error (MAE), and rank correlation.

2.2 Theoretical Anchors: Probabilistic and Causal Perspectives

We use normative models as anchors rather than assumptions. (1) **Bayesian / PLoT.** Idealized revision 97 follows Bayesian conditioning $b_i'(\mathbf{s}) \propto b_i(\mathbf{s}) p(\mathcal{I} \mid \mathbf{s})$, interpreting language as probabilistic evidence 98 over latent stances. We also draw on the **Probabilistic Language of Thought (PLoT)** framework[21], 99 which extends Bayesian inference to compositional linguistic structures. (2) Structural Causal Mod-100 els (SCM). Interventions act as $do(\mathcal{I})$ on a causal graph of values/reasons, yielding counterfactual 101 belief shifts $\mathbb{E}[\mathbf{s} \mid do(\mathcal{I})]$. We additionally represent a person's value-reason structure as a signed 102 directed graph G_i ; we hypothesize that similarity between such graphs (e.g., via graph edit distance 103 or learned embeddings) may predict cross-domain transfer, motivating our Hypothesis H2 and left as 104 future work. Human reasoning deviates from these ideals; the anchors provide principled baselines 105 for analysis. 106

2.3 Guiding Hypotheses

Grounding HugAgent in theory enables us to frame four *guiding hypotheses* that serve as lenses for interpreting empirical results, rather than assumptions to be fully verified:

- H1 (Intra-individual consistency): With sufficient context (e.g., demographic features or prior transcripts), LLMs can stably capture an individual's belief state.
- **H2** (**Cross-domain transfer bound**): Reasoning patterns transfer partially across domains, and accuracy under domain transfer is significantly lower than in-domain performance.
 - H3 (Population prior reliance): Without individual context, LLMs default to global population priors rather than individual-specific cues.
- **H4 (Context information gain)**: Prediction accuracy increases monotonically with context length, until saturation.

These hypotheses move the benchmark beyond performance reporting: they test structural claims about how LLMs approximate, or fail to approximate the individuality of human reasoning.

Validation roadmap. To substantiate these hypotheses, we highlight four key *control experiments* that serve as evidence of individuality; later sections return to each in detail.

What counts as evidence of individuality? (control experiments)

- **Population Prior Baseline** predict only from aggregate distributions (see Sec. 6.1).
- Identity Shuffle Control shuffle person–context pairs (see Sec. 6.2).
- **Per-Person Leave-One-Out** use partial history to predict held-out responses (see Sec. 4.2).
- Context-Length Ablation vary context size to test information gain (see Sec. 5).

3 **HugAgent Benchmark**

123

Grounded in the theoretical setup in Section 2, we now introduce **HugAgent**, which translates these 124 principles into concrete tasks (Sec. 3.2), a scalable data collection pipeline (Sec. 3.3), and evaluation 125 protocols (Sec. 3.5). 126

Task 1 - Belief State Inference

Context (QA pairs from transcript) Q: Technological reliability? A: If the system can't be trusted, people will oppose it Q: Main cause of support? A: Safety is the priority... people want to feel secure Q: Community trust? A: Depends on past experience... takes time to build confidence O: Equity & bias? A: Important to show fairness... treat all groups the same

Task 2 - Belief Dynamic Update

```
Context (QA pairs from transcript)
Q: Technological reliability?
A: If the system can't be trusted,
people will oppose it
Q: Main cause of support?
A: Safety is the priority... people want
to feel secure
Q: Community trust?
A: Depends on past experience... takes
time to build confidence
O: Equity & bias?
A: Important to show fairness... treat all
groups the same
```

```
Question
Based on this person's responses, what
do they think about the effect of
greater accuracy and reliability in
technology on support for surveillance
cameras?
A. POSITIVE effect
B. NEGSTIVE effect
```

Question If surveillance footage was kept only 2 days and checked only after problems, how would this affect your opinion? Scale [1-10] Answer: 8 How much do these reasons matter for your opinion? Scale [1-5] -Privacy Answer: 4 -Freedom / Autonomy Answer: 1 -Policy Persistence Answer: 1

Figure 2: Two benchmark tasks. Task 1 (Belief State Inference) infers stance and reasons from prior context; Task 2 (Belief Dynamics Update) predicts stance shifts and its reasoning under new evidence.

3.1 Design Principles

127

128

129

130

132

133

134

135

139

- Open-ended but deeper. Emphasize depth over breadth: semi-structured dialogue with targeted follow-ups surfaces individuality while avoiding over-scaffolding; ground truth comes from self-reports [22, 20, 1].
- Two observable proxies. We evaluate (i) belief state inference and (ii) belief dynamics up-131 date—tractable targets that avoid requiring exact trace imitation; cf. proxy-label benchmarks [23-25].
 - Dual track. Human interviews provide ecological realism; synthetic agents provide controlled stress tests via scripted causal belief graphs—preventing circularity and enabling scale.
- Human ceiling. Test-retest reliability defines the upper bound, aligning with psychology standards 136 [26, 27] and recent large-scale simulations [9, 1]. 137
- See Appendix K for extended discussion. 138

3.2 Task Definition

- We formalize reasoning adaptation as predicting how an individual's belief state changes under new 140 141
- **Belief representation.** A belief at time t is $b_t = (s_t, \mathbf{w}_t)$, where $s_t \in \{1, \dots, 10\}$ is a stance score 142 and \mathbf{w}_t is a distribution over K reason weights. 143
- **Belief update.** Given evidence e, an update operator U produces $b_{t+1} = U(b_t, e)$. In humans, b_{t+1} 144 comes from self-reports; in synthetic agents, from scripted rules with known ground truth. 145

Tasks. We instantiate two tasks: (i) **Belief State Inference**: predict (s_t, \mathbf{w}_t) from prior responses. (ii) **Belief Dynamics Update**: predict $(s_{t+1}, \mathbf{w}_{t+1})$ given (b_t, e) . Figure 2 shows concrete examples of both tasks in HugAgent.




Figure 3: **HugAgent** benchmark pipeline. Inputs (demographics, questionnaires, and transcripts) flow through two components: a questionnaire that provides demographic anchors, stance baselines, and counterfactual updates, and a semi-structured chatbot that elicits individualized reasoning. Together these elements define two benchmark tasks: (i) *belief state inference*—recovering stance and factor polarity from context, and (ii) *belief dynamics update*—predicting stance shifts and reweighting under new evidence. (A) The chatbot maintains a causal belief network of factors, used to identify the most critical nodes and edges for follow-up. (B) A question generator derives targeted, context-specific probes from this network to structure the dialogue.

149 3.3 Building HugAgent: Scalable Elicitation of Individual Reasoning

HugAgent is built through a two-stage pipeline (Figure 3).

- 1. The questionnaire stage collects demographics, a baseline stance $(s_t, 1-10)$, reason weights $(\mathbf{w}_t, 1-5)$, and counterfactual interventions with updated stances and reasons. These structured responses provide gold labels for *Belief Dynamics Update* and serve as anchors for aligning free text to factors.
- 2. The *chatbot* stage elicits 8–20 question–answer pairs through semi-strutctured interview, combining open-ended elaborations (*Context QAs*) with concise polarity judgments (*GT QAs*). This setup captures both participants' belief, reasoning styles and explicit preferences on each decision factor. Each transcript thus supports both benchmark tasks: *Belief State Inference* (using Context and GT QAs) and *Belief Dynamics Update* (using Context QAs, questionnaire responses upon interventions). Survey-provided updates are never revealed in dialogue, preventing leakage.
- Finally, we establish a human reliability ceiling through test—retest elicitation of a subset of items, reporting intra-individual consistency with Intraclass Correlation (ICC) and quadratic-weighted kappa (QWK) with 95% confidence intervals. Further design choices, intervention phrasing, prompt templates, and quality-control rules are detailed in Appendix K.

3.4 Dataset Statistics

147

150

151

152

153

164

165

168

Applying this pipeline yields HugAgent, a dataset spanning three socially salient domains: *healthcare*, *surveillance*, and *zoning*. These domains were chosen for their ecological validity, diversity of viewpoints, and internally rich trade-offs (e.g., affordability vs. neighborhood character, privacy vs. safety).

Human track. From over 120 participants, we retained 54 whose survey and interview data met predefined quality-control criteria (see Appendix M). Task 1 (*belief state inference*) contains 356 labeled questions, and Task 2 (*belief dynamics update*) contains 1,386 items, distributed as shown in Table 1.

Synthetic track. We construct a parallel synthetic track by assigning each agent a *scripted causal belief network* (CBN) that defines its reasoning structure and deterministic update rules. All synthetic agents follow the same survey and interview protocol as in the human track, allowing direct comparison under identical tasks. In total, the benchmark includes 500 synthetic agents, from which we use a stratified subset of 50 agents for computation and analysis. Unless otherwise specified, all experiments reported in this paper are conducted on this subset. Both the full and subset data are included in the benchmark release. Detailed construction procedures are provided in Appendix N.

	Н	uman Tr	ack (N=54)	Syı	nthetic T	rack (N=5	00)
Task / Domain	Health	Surv.	Zoning	Total	Health	Surv.	Zoning	Total
Belief State Inf. Belief Dyn. Update	108 472	122 364	126 550	356 1,386	1,303 3,888	1,297 2,610	1,302 3,818	3,902 10,316
Total Items	580	486	676	1,742	5,191	3,907	5,120	14,218

Table 1: Dataset statistics by task and domain. Human track (N=54 participants) provides ecological validity; synthetic track (N=500 scripted agents) scales coverage.

3.5 Evaluation Protocols

Finally, we highlight the evaluation protocols that ensure HugAgent's utility as a scientific benchmark.

Evaluation metrics. We evaluate *belief state inference* using accuracy, the proportion of exact matches with ground-truth labels. For *belief dynamics update*, we report four metrics: (i) accuracy, the proportion of predictions within a tolerance band of the true response (±1 for 5-point, ±2 for 10-point scales); (ii) mean absolute error (MAE), the average magnitude of deviation from the ground truth, with all responses normalized to a 5-point scale for consistency; (iii) directional accuracy measures whether the predicted belief update matches the ground truth in direction(increase, decrease, or no change); and (iv) average to individual (ATI) score, following the GLUE [28] and SuperGLUE [29] scoring paradigm, we derive an overall score via hierarchical aggregation, where normalized task-specific metrics (accuracy, MAE, directional accuracy) are combined into belief dynamics update and averaged with belief state inference, with human and random guess performance used as upper and lower bounds for normalization. Formal definitions and computation details are given in Appendix Q.1.

Leakage control. We masked attribution targets, drew interventions from external surveys, and presented each item independently with minimal-overlap prompts (see Appendix J.1 for templates). **Human baselines.** We re-contacted a subset of participants for a short-interval (14-day) test–retest study. Across all sessions, 54 participants contributed data. Of these, 18 completed the retest, and 13 were retained following a demographic consistency check. *Belief State Inference* yielded an accuracy of **84.84**% (SD = 8.90, 95% CI: [80.00, 89.68]). *Belief Dynamics Update* achieved an accuracy of **85.66**% (SD = 7.66, 95% CI: [80.91, 90.40]) and a mean absolute error of **0.68** (SD = 0.20, 95% CI: [0.55, 0.80]). The directional accuracy was **88.92**% (SD = 9.89, 95% CI: [82.09, 96.24]). These scores establish a human consistency ceiling, as outlined in Section 3.1, against which model performance can be benchmarked.

4 Main Results

4.1 Baselines

We compare models against clear anchors: (i) an **upper bound** defined by **real human performance**, measured through test-retest consistency (see Section 3.1); (ii) a **lower bound** defined by **random guessing**, reflecting chance performance; and (iii) a set of strong **pretrained language models**, including GPT, Gemini, LLaMA, and Qwen, which serve as high-performing but non-agentic baselines without explicit memory, personalization, or retrieval components.

To evaluate the role of agent-like structure in modeling belief reasoning, we further include two **agent-style LLM baselines** that incorporate memory or retrieval. The first is the **Generative Agents** baseline, reproduced following the setup of Park et al. [30], using Qwen2.5-32B-instruct as the base model. The second group includes two variants of **retrieval-augmented generation (RAG)**. The first, **RAG**, follows the standard setup [31], replacing the original full QA context with the top-k retrieved QA pairs (k = 5). The second, **RAG with Full Context**, appends the retrieved QA pairs to the original input, allowing the model to jointly condition on both. This variant evaluates whether retrieval can serve as an auxiliary signal rather than a substitute for agent-specific context. Detailed settings and full results are provided in Appendix C.

4.2 Overall Performance

213 214

215

216

217

218

219

220

221

222

Tables 2 summarize performance. We evaluate using the metrics introduced in Section 3.5. For **belief state inference**, best-performing LLMs approach but do not match human accuracy, trailing by 4–6 points. Open-source LLaMA and Qwen rival GPT-40, while smaller or less aligned models lag significantly. For **belief dynamics update**, gaps are larger: models frequently mispredict the direction of stance change or fail to adjust reason weights, yielding higher error than human baseline.

	Belief Stat	e Inference			Belief Dyna	mics Updat	e		
Model	Acc.	(% ↑)	Acc.	(%↑)	MA	E (\dagger)	Dir. Ac	cc. (% †)	ATI (% ↑)
	Real	Synth.	Real	Synth.	Real	Synth.	Real	Synth.	Real
Human	84.84	_	85.66	_	0.68	_	88.92	_	100.00
OpenAI Models									
GPT-4o	$74.66^{\pm 2.86}$	$67.93^{\pm6.04}$	$63.11^{\pm 1.19}$	$58.61^{\pm 5.22}$	$1.29^{\pm0.04}$	$1.44^{\pm0.23}$	$82.27^{\pm 1.02}$	$76.83^{\pm0.46}$	$68.99^{\pm0.80}$
GPT-5-mini	$75.30^{\pm 2.13}$	$62.78^{\pm 9.63}$	$58.21^{\pm 2.41}$	$57.25^{\pm 5.78}$	$1.43^{\pm0.08}$	$1.47^{\pm0.22}$	$77.02^{\pm 2.02}$	$73.69^{\pm 3.76}$	$63.44^{\pm2.25}$
o3-mini	$75.12^{\pm 4.49}$	$69.67^{\pm 8.87}$	$64.54^{\pm4.91}$	$56.48^{\pm7.42}$	$1.22^{\pm0.12}$	$1.45^{\pm0.26}$	$71.29^{\pm 2.87}$	$64.34^{\pm4.24}$	$62.84^{\pm1.82}$
Other Closed-Source Models									
Gemini 2.0 Flash	$69.95^{\pm6.01}$	$59.66^{\pm 5.73}$	$60.55^{\pm 3.19}$	$54.73^{\pm 7.52}$	$1.35^{\pm0.03}$	$1.48^{\pm0.25}$	$83.31^{\pm0.19}$	$68.58^{\pm0.00}$	$61.73^{\pm0.20}$
DeepSeek-R1	$75.43^{\pm0.94}$	$70.75^{\pm 6.00}$	$64.88^{\pm 2.94}$	$61.16^{\pm 2.82}$	$1.29^{\pm0.03}$	$1.38^{\pm0.19}$	$79.69^{\pm0.91}$	$76.20^{\pm 1.10}$	$68.91^{\pm 1.11}$
Qwen-plus	77.57 $^{\pm 1.27}$	$67.81^{\pm 3.65}$	$58.93^{\pm 2.45}$	$55.29^{\pm 8.40}$	$1.40^{\pm0.05}$	$1.49^{\pm0.26}$	$77.17^{\pm0.61}$	$75.82^{\pm4.48}$	$67.26^{\pm0.94}$
Qwen-max	$77.40^{\pm 1.04}$	$67.74^{\pm4.08}$	$58.86^{\pm2.44}$	$55.20^{\pm 8.21}$	$1.40^{\pm0.05}$	$1.49^{\pm0.26}$	$77.17^{\pm0.48}$	$76.54^{\pm3.28}$	$67.00^{\pm0.54}$
Open-Source Models									
LLaMA 3.3 70B	$76.39^{\pm4.33}$	$71.74^{\pm 7.73}$	$67.57^{\pm4.08}$	$58.35^{\pm6.17}$	$1.24^{\pm0.08}$	$1.49^{\pm0.25}$	$79.56^{\pm0.36}$	$74.93^{\pm 2.48}$	71.47 $^{\pm0.28}$
Qwen2.5-32B-instr.	$77.17^{\pm0.81}$	$68.21^{\pm 3.18}$	$58.96^{\pm2.46}$	$55.37^{\pm 8.37}$	$1.40^{\pm0.05}$	$1.49^{\pm0.26}$	$76.88^{\pm0.29}$	$75.32^{\pm 4.62}$	$66.51^{\pm0.26}$
Qwen2.5-7B-instr.	$77.18^{\pm1.61}$	$67.81^{\pm 3.32}$	$58.82^{\pm2.38}$	$55.33^{\pm 8.35}$	$1.40^{\pm0.04}$	$1.49^{\pm0.26}$	$77.12^{\pm0.80}$	$74.95^{\pm4.38}$	$66.63^{\pm1.31}$
Memory-Augmented Baselines									
RAG^1	$75.46^{\pm3.01}$	$63.06^{\pm 8.68}$	$51.90^{\pm 1.42}$	$51.85^{\pm 7.92}$	$1.57^{\pm0.05}$	$1.56^{\pm0.27}$	$72.25^{\pm0.57}$	$66.70^{\pm 2.71}$	$57.06^{\pm0.94}$
RAG-FC ¹	$77.56^{\pm 1.20}$	$72.82^{\pm 3.74}$	$59.97^{\pm 1.44}$	$59.34^{\pm 4.67}$	$1.39^{\pm0.04}$	$1.45^{\pm0.21}$	$76.80^{\pm0.80}$	$76.81^{\pm 1.53}$	$67.43^{\pm0.65}$
Generative Agents ¹	$76.19^{\pm0.96}$	$73.48^{\pm 3.82}$	$58.22^{\pm 2.51}$	$55.43^{\pm 7.63}$	$1.40^{\pm0.05}$	$1.49^{\pm0.26}$	$76.13^{\pm2.45}$	$82.76^{\pm0.36}$	$64.29^{\pm1.87}$
Non-Learning Baselines									
Global Majority	$65.77^{\pm0.00}$	$64.30^{\pm0.00}$	$58.18^{\pm0.00}$	$54.60^{\pm0.00}$	$2.54^{\pm0.00}$	$2.37^{\pm0.00}$	$17.93^{\pm0.00}$	$21.95^{\pm0.00}$	$4.44^{\pm0.00}$
Random Guess	$51.89^{\pm 5.18}$	$50.62^{\pm 4.47}$	$43.12^{\pm 2.06}$	$50.36^{\pm3.55}$	$1.88^{\pm0.09}$	$1.62^{\pm0.15}$	$46.74^{\pm3.28}$	$29.78^{\pm 13.18}$	$0.00^{\pm 5.80}$

Table 2: Average results for both *Belief State Inference* and *Belief Dynamics Update*. Macro-averages are reported as *mean*±*std* over 5 runs. Best-performing non-human (upper-bound) results in each column are highlighted in **bold**.

227 5 Main Findings

Finding 1: Preserving Identity Across Domains is Harder Than Expected

Task	Model	$Health \rightarrow Surv$	$Surv \rightarrow Zone$	$Zone \rightarrow Health$	Avg
Belief State Inference (Accuracy % ↑)	Qwen2.5-32B-instr. GPT-40	53.52 ^{±1.52} 58.52±0.77	58.69 ^{±1.10} 65.41±1.58	$55.08^{\pm 1.20}$ $51.75_{\pm 1.03}$	$55.76^{\pm 2.54}$ 58.56 ± 5.88
Belief Dynamics Update (Accuracy % ↑)	Qwen2.5-32B-instr. GPT-40	44.41 ± 0.98 49.49 ± 0.87	$\substack{24.84 \pm 0.60 \\ 42.47 \pm 0.50}$	30.15 ± 0.35 41.96 ± 0.30	33.13 ± 8.58 44.64 ± 3.60
Belief Dynamics Update (MAE ↓)	Qwen2.5-32B-instr. GPT-40	$\substack{1.69 \pm 0.01 \\ 1.55 \pm 0.01}$	$^{1.94\pm0.01}_{1.60\pm0.00}$	2.05 ± 0.01 1.71 ± 0.00	$^{1.89\pm0.16}_{1.62\pm0.07}$

Table 3: Cross-domain swap test: models are trained with QA context from one domain and evaluated on another domain for the *same participant*. We report performance for *Healthcare* \rightarrow *Surveillance*, *Surveillance* \rightarrow *Zoning*, *Zoning* \rightarrow *Healthcare*, and their average. Reported as *mean* \pm *std* over 5 runs.

To evaluate whether models can generalize a person's contextual information across domains, we conduct a cross-domain swap test. Each model is given QA context from one domain and evaluated on

¹RAG [31], RAG-FC = RAG with Full Context [31], Generative Agents [30].

another domain for the same participant (for example, using context from *Healthcare* and testing on 231 Surveillance). Based on Table 2, we selected GPT-40 and Qwen2.5-32B-instruct as representative 232 models from two categories: closed-source SOTA and strong open-source baseline. 233 Under cross-domain transfer, model performance degrades substantially compared to within-domain 234 evaluation. GPT-40 achieves an average of 58.56% on belief state inference, compared to its within-235 domain score of 74.66%, while Qwen2.5-32B-instruct drops from 77.17% to 55.76%. In the 236 Belief Dynamics Update task, GPT-40 declines from 63.11% to 44.64%. The degradation is most 237 pronounced in belief dynamics update, where compounding errors accumulate across domains. These 238 findings suggest that current models depend heavily on domain-specific linguistic and contextual cues, 239 240 resulting in limited cross-domain reasoning transfer. This underscores the importance of evaluating within-person, cross-domain consistency as a key indicator of robust generalization, and suggests 241 that improving transferability requires focusing on essential, domain-relevant context rather than 242 surface-level correlations.

4 Finding 2: More Context Doesn't Always Help

Model	Context	Bel	ief State Inferer	ice (Accuracy %	• ↑)	Belie	f Dynamics Up	date (Accuracy	% ↑)	Belief Dynamics Update (MAE ↓)			
		Health	Surv.	Zone	Avg	Health	Surv.	Zone	Avg	Health	Surv.	Zone	Avg
GPT-40	5 QAs	68.89±0.51	73.93±1.07	72.22±0.00	71.68±2.26	61.48±0.35	67.80±0.45	63.27±0.36	64.19±2.78	1.26±0.01	1.19±0.01	1.24±0.00	1.23±0.03
	10 QAs	67.59±1.73	72.30±0.37	72.06±0.66	70.65±2.46	62.29±0.33	64.56±0.39	65.82±0.39	64.22±1.55	1.28±0.00	1.26±0.01	1.21±0.01	1.25±0.03
	20+ QAs	71.11±0.77	75.25±0.90	77.62±0.35	74.66±2.86	61.57±0.19	63.74±0.58	64.04±0.20	63.11±1.19	1.27±0.01	1.35±0.01	1.26±0.01	1.29±0.04
Gemini 2.0 Flash	5 QAs	61.30±0.41	65.25±0.45	65.08±0.00	63.87±1.92	59.70±0.09	65.71±0.30	62.25±0.21	62.56±2.56	1.36±0.00	1.23±0.00	1.34±0.00	1.31±0.06
	10 QAs	60.19±0.65	64.75±0.00	71.27±0.35	65.40±4.72	58.22±0.28	62.58±0.23	65.20±0.16	62.00±2.99	1.37±0.00	1.30±0.01	1.26±0.00	1.31±0.05
	20+ QAs	63.89±0.00	68.20±0.37	77.78±0.00	69.95±6.01	56.23±0.12	62.25±0.37	63.16±0.10	60.55±3.19	1.39±0.00	1.33±0.00	1.33±0.00	1.35±0.03
Qwen2.5-32B-instr.	5 QAs	68.33±1.21	73.11±2.68	65.08±0.56	68.84±3.77	59.45±0.55	62.53±0.57	63.38±0.69	61.79±1.84	1.36±0.00	1.31±0.01	1.27±0.01	1.31±0.04
	10 QAs	75.37±4.47	75.90±1.80	67.78±1.06	73.02±4.66	58.52±0.74	60.66±0.60	63.02±0.47	60.73±1.99	1.41±0.01	1.36±0.01	1.27±0.01	1.35±0.06
	20+ QAs	77.96±0.41	76.56±0.45	76.98±0.79	77.17±0.81	56.82±0.41	57.80±0.25	62.25±0.16	58.96±2.46	1.43±0.00	1.43±0.01	1.33±0.01	1.40±0.05

Table 4: Question masking / length scaling for both *Belief State Inference* and *Belief Dynamics Update*. Reported as $mean \pm std$ over 5 runs. Best results per column are highlighted in **bold**.

To examine how context length influences model performance across tasks, we varied the number 245 of Context QAs (5, 10, 20+). Based on Table 2, we selected GPT-4o, Gemini2.0Flash, and 246 Qwen2.5-32B-instruct as representative models from three categories: closed-source SOTA, 247 lightweight efficient, and strong open-source baseline. 248 The core result is that belief state inference accuracy rises monotonically with additional dialogue and 249 saturates at 20+ questions, whereas belief dynamics update accuracy peaks at 5-10 questions before 250 declining. Longer context provide richer cues for recovering belief states but also introduce noise that 251 impairs belief updating. This asymmetry suggests that context length benefits belief state inference 252 through scale, while belief dynamics update is vulnerable to cognitive overload, likely disrupting 253 System2 reasoning and prompting fallback to heuristic shortcuts[16, 17]. We next investigate whether 254 these context-length effects stem from surface-level pattern matching rather than genuine identity 255 modeling. 256

6 Why It Happens: Diagnostic Ablations

Section 5 revealed a **consistent failure to preserve identity across domains**. Here we ask *why*: is it because models never learned to use personal information, or because they use it in an *associative*, *non-generalizable* way? To answer this, we conduct two diagnostic ablations.

6.1 Population Prior vs. Individual Context

257

258

259

260

261

Task	Method		Accurac	ey (% †)			MAE	(\psi)	
		Healthcare	Surveillance	Zoning	Avg	Healthcare	Surveillance	Zoning	Avg
Belief State Inference	GPT-40 (No-Context) GPT-40 (Full-Context) Qwen2.5-32B-instr. (No-Context) Qwen2.5-32B-instr. (Full-Context)	55.93±1.40 71.11±0.77 45.19±1.66 77.96±0.41	66.07±1.37 75.25±0.90 59.02±1.16 76.56±0.45	53.49±1.99 77.62±0.35 48.57±1.30 76.98±0.79	58.49±5.83 74.66±2.86 50.92±6.23 77.17±0.81	N/A N/A N/A N/A			
Belief Dynamics Update	GPT-40 (No-Context) GPT-40 (Full-Context) Qwen2.5-32B-instr. (No-Context) Qwen2.5-32B-instr. (Full-Context)	34.62±0.68 61.57±0.19 34.58±0.55 56.82±0.41	48.24±0.31 63.74±0.58 33.90±0.60 57.80±0.25	36.62±0.52 64.04±0.20 27.89±0.38 62.25±0.16	39.83±6.24 63.11±1.19 32.12±3.15 58.96±2.46	1.77±0.01 1.27±0.01 1.89±0.01 1.43±0.00	1.51±0.01 1.35±0.01 1.75±0.01 1.43±0.01	1.84±0.01 1.26±0.01 1.99±0.01 1.33±0.01	1.70±0.15 1.29±0.04 1.88±0.10 1.40±0.05

Table 5: Comparison of *No-Context* (population prior) and *Full-Context* (with individual transcripts) settings. Reported as $mean \pm std$ over 5 runs.

We first test whether models improve their predictive performance when given individual context, using a population-level prior as the baseline. The *No-Context* setting provides only demographic background, while the *Full-Context* setting additionally includes transcripts and survey answers. As shown in Table 5, GPT-40 achieves substantially higher performance when provided with individual context: its belief-state inference accuracy increases from **58.49% with demographic priors** to

74.66% with full context, and its belief-dynamics-update accuracy from **39.83%** to **63.11%**. The consistent gains in *Full-Context* indicate that models leverage individual cues rather than population priors, showing that the benchmark captures identity-sensitive reasoning rather than general demographic trends.

6.2 Cross-Person Generalization

Method	Belief State Inference	Belief Dynamics Update						
	Accuracy (% ↑)	Accuracy (% ↑)	$\mathrm{MAE}\left(\downarrow\right)$	Dir. Acc. (% ↑)				
GPT-40 Qwen2.5-32B-instr.	54.44±6.37 60.44±3.22	39.30±2.84 38.16±3.28	1.93±0.10 2.02±0.13	63.56 ± 0.76 69.17 ± 1.06				

Table 6: Cross-person swap test: QA context from one participant is used to predict another participant's responses within the same domain. Belief State Inference reports accuracy; Belief Dynamics Update reports accuracy, MAE, and directional accuracy (Dir. Acc.). Results are reported as $mean \pm std$ over 5 runs, averaged across domains.

We then test whether the observed gains reflect genuine identity modeling or simply the benefit of having richer, more fine-grained context. In this *Cross-Person* setting, QA context from one participant is used to predict another's responses within the same domain. As shown in Table 6, performance drops sharply, e.g., GPT-40 achieves only **39.30**% belief-dynamics-update accuracy with an MAE of **1.93**, showing that models fail to generalize when identity cues are mismatched. These results suggest that improvements in the *Full-Context* setting arise from learning identity-specific patterns rather than simply benefiting from additional contextual detail.

Summary. Together with the findings in Section 5, these ablations reveal that current models' failure to preserve identity across domains is not because they ignore individual context in inference, but rather implies a reliance on associative context matching instead of identity-consistent reasoning.

7 Discussion and Open Challenges

Topic selection is not neutral. What we ask shapes who a model appears to simulate. Highly controversial topics elicit richer value trade-offs and sharper updates; homogeneous topics compress variation and inflate apparent accuracy. We propose treating topic choice as an **explicit experimental variable**: (i) curate pairs of domains with high vs. low opinion dispersion; (ii) report results stratified by a simple *controversy index C* (e.g., stance variance + polarity entropy) so scores are comparable across corpora; (iii) add *dilemma framings* (e.g., fairness vs. safety) to probe value conflicts rather than single-axis opinions. Practically, this turns "topic selection" from a hidden confound into a **controlled factor** that the community can measure and replicate.

Comparative benchmarks, transfer, and ethics-by-design. Personalization that succeeds only within-domain but fails across domains is not robust. We propose a comparative benchmark protocol that (i) pairs controversial vs. homogeneous topics, (ii) contrasts intuition vs. deliberation, and (iii) evaluates within-person, cross-domain transfer as a core metric. Preregistered topic panels and per-item metadata (controversy index C, tension flags, latency) will aid comparability. Ethically, tension induction must be consentful and minimal, with disclosed framings, capped length, and opt-out. The challenge is designing evaluation that respects persons while probing the hard cases where individuality matters most.

8 Limitations and Conclusion

Our study is constrained by a modest human sample due to resource limits, yet this is complemented by a synthetic track that provides controlled variation and an open, end-to-end pipeline for collecting and processing human subject data. This design enables the community to expand the dataset both in domain coverage and scale *at minimal cost*. Even so, **HugAgent** offers a benchmark for *average-to-individual reasoning adaptation*, uniting ecological validity with scalability. Analyses reveal structured failure modes in current LLMs, positioning **HugAgent** as a reproducible testbed for evaluating how well foundation models can represent human diversity at the individual level when acting as human proxies, and for extending the notion of **trustworthiness** from behavioral imitation to cognitive reasoning fidelity.

References

- [1] Joon Sung Park, Carolyn Q Zou, Aaron Shaw, Benjamin Mako Hill, Carrie Cai, Meredith Ringel
 Morris, Robb Willer, Percy Liang, and Michael S Bernstein. Generative agent simulations of
 1,000 people. arXiv preprint arXiv:2411.10109, 2024.
- [2] Lisa P Argyle, Ethan C Busby, Nancy Fulda, Joshua R Gubler, Christopher Rytting, and David Wingate. Out of one, many: Using language models to simulate human samples. *Political Analysis*, 31(3):337–351, 2023.
- 316 [3] Chengxing Xie, Canyu Chen, Feiran Jia, Ziyu Ye, Shiyang Lai, Kai Shu, Jindong Gu, Adel 317 Bibi, Ziniu Hu, David Jurgens, et al. Can large language model agents simulate human trust 318 behavior? *Advances in neural information processing systems*, 37:15674–15729, 2024.
- [4] Hang Jiang, Doug Beeferman, Brandon Roy, and Deb Roy. Communitylm: Probing partisan worldviews from language models, 2022. URL https://arxiv.org/abs/2209.07065.
- [5] Angelina Wang, Jamie Morgenstern, and John P Dickerson. Large language models that replace human participants can harmfully misportray and flatten identity groups. *Nature Machine Intelligence*, pages 1–12, 2025.
- [6] Shibani Santurkar, Esin Durmus, Faisal Ladhak, Cinoo Lee, Percy Liang, and Tatsunori Hashimoto. Whose opinions do language models reflect? In *International Conference on Machine Learning*, pages 29971–30004. PMLR, 2023.
- [7] Esin Durmus, Karina Nguyen, Thomas I Liao, Nicholas Schiefer, Amanda Askell, Anton
 Bakhtin, Carol Chen, Zac Hatfield-Dodds, Danny Hernandez, Nicholas Joseph, et al. Towards
 measuring the representation of subjective global opinions in language models. arXiv preprint
 arXiv:2306.16388, 2023.
- Taylor Sorensen, Jared Moore, Jillian Fisher, Mitchell Gordon, Niloofar Mireshghallah, Christopher Michael Rytting, Andre Ye, Liwei Jiang, Ximing Lu, Nouha Dziri, et al. A roadmap to pluralistic alignment. *arXiv preprint arXiv:2402.05070*, 2024.
- Olivier Toubia, George Z. Gui, Tianyi Peng, Daniel J. Merlau, Ang Li, and Haozhe Chen. Twin-2k-500: A dataset for building digital twins of over 2,000 people based on their answers to over 500 questions, 2025. URL https://arxiv.org/abs/2505.17479.
- 1337 [10] Chance Jiajie Li, Jiayi Wu, Zhenze Mo, Ao Qu, Yuhan Tang, Kaiya Ivy Zhao, Yulu Gan, Jie 1338 Fan, Jiangbo Yu, Jinhua Zhao, Paul Liang, Luis Alonso, and Kent Larson. Position: Simulating 1339 society requires simulating thought, 2025. URL https://arxiv.org/abs/2506.06958.
- [11] Maarten Sap, Ronan LeBras, Emily Allaway, Chandra Bhagavatula, Nicholas Lourie, Hannah Rashkin, Brendan Roof, Noah A. Smith, and Yejin Choi. Atomic: An atlas of machine commonsense for if-then reasoning, 2019. URL https://arxiv.org/abs/1811.00146.
- [12] Maarten Sap, Hannah Rashkin, Derek Chen, Ronan LeBras, and Yejin Choi. Social IQa:
 Commonsense reasoning about social interactions. In *Proceedings of EMNLP*, 2019.
- [13] Heinz Wimmer and Josef Perner. Beliefs about beliefs: Representation and constraining function of wrong beliefs in young children's understanding of deception. Cognition, 13(1): 103-128, 1983. ISSN 0010-0277. doi: https://doi.org/10.1016/0010-0277(83)90004-5. URL https://www.sciencedirect.com/science/article/pii/0010027783900045.
- Zhuang Chen, Jincenzi Wu, Jinfeng Zhou, Bosi Wen, Guanqun Bi, Gongyao Jiang, Yaru Cao,
 Mengting Hu, Yunghwei Lai, Zexuan Xiong, and Minlie Huang. Tombench: Benchmarking the ory of mind in large language models, 2024. URL https://arxiv.org/abs/2402.15052.
- In Itanian Shu, Thomas L. Griffiths, and Joshua B. Tenenbaum. On benchmarking human-like
 intelligence in machines, 2025. URL https://arxiv.org/abs/2502.20502.
- [16] Daniel Kahneman. Thinking, Fast and Slow. Farrar, Straus and Giroux, New York, 2011.
- Jonathan St. B. T. Evans and Keith E. Stanovich. Dual-process theories of higher cognition:
 Advancing the debate. *Perspectives on Psychological Science*, 8(3):223–241, 2013. doi: 10.1177/1745691612460685.

- [18] Hanna Yukhymenko, Robin Staab, Mark Vero, and Martin Vechev. A synthetic dataset for
 personal attribute inference. Advances in Neural Information Processing Systems, 37:120735–
 120779, 2024.
- [19] Qiuejie Xie, Qiming Feng, Tianqi Zhang, Qingqiu Li, Linyi Yang, Yuejie Zhang, Rui Feng,
 Liang He, Shang Gao, and Yue Zhang. Human simulacra: Benchmarking the personification of
 large language models. arXiv preprint arXiv:2402.18180, 2024.
- [20] Aarohi Srivastava, Abhinav Rastogi, Abhishek Rao, Abu Awal Md Shoeb, Abubakar Abid, 365 Adam Fisch, Adam R. Brown, Adam Santoro, Aditya Gupta, Adrià Garriga-Alonso, Ag-366 nieszka Kluska, Aitor Lewkowycz, Akshat Agarwal, Alethea Power, Alex Ray, Alex Warstadt, 367 Alexander W. Kocurek, Ali Safaya, Ali Tazarv, Alice Xiang, Alicia Parrish, Allen Nie, Aman 368 Hussain, Amanda Askell, Amanda Dsouza, Ambrose Slone, Ameet Rahane, Anantharaman S. 369 370 Iyer, Anders Andreassen, Andrea Madotto, Andrea Santilli, Andreas Stuhlmüller, Andrew Dai, Andrew La, Andrew Lampinen, Andy Zou, Angela Jiang, Angelica Chen, Anh Vuong, 371 Animesh Gupta, Anna Gottardi, Antonio Norelli, Anu Venkatesh, Arash Gholamidavoodi, Arfa 372 Tabassum, Arul Menezes, Arun Kirubarajan, Asher Mullokandov, Ashish Sabharwal, Austin 373 Herrick, Avia Efrat, Aykut Erdem, Ayla Karakaş, B. Ryan Roberts, Bao Sheng Loe, Barret Zoph, 374 Bartłomiej Bojanowski, Batuhan Özyurt, Behnam Hedayatnia, Behnam Neyshabur, Benjamin 375 Inden, Benno Stein, Berk Ekmekci, Bill Yuchen Lin, Blake Howald, Bryan Orinion, Cameron 376 Diao, Cameron Dour, Catherine Stinson, Cedrick Argueta, César Ferri Ramírez, Chandan 377 Singh, Charles Rathkopf, Chenlin Meng, Chitta Baral, Chiyu Wu, Chris Callison-Burch, Chris 378 Waites, Christian Voigt, Christopher D. Manning, Christopher Potts, Cindy Ramirez, Clara E. 379 Rivera, Clemencia Siro, Colin Raffel, Courtney Ashcraft, Cristina Garbacea, Damien Sileo, 380 Dan Garrette, Dan Hendrycks, Dan Kilman, Dan Roth, Daniel Freeman, Daniel Khashabi, 381 Daniel Levy, Daniel Moseguí González, Danielle Perszyk, Danny Hernandez, Danqi Chen, 382 Daphne Ippolito, Dar Gilboa, David Dohan, David Drakard, David Jurgens, Debajyoti Datta, 383 Deep Ganguli, Denis Emelin, Denis Kleyko, Deniz Yuret, Derek Chen, Derek Tam, Dieuwke 384 Hupkes, Diganta Misra, Dilyar Buzan, Dimitri Coelho Mollo, Diyi Yang, Dong-Ho Lee, Dylan 385 Schrader, Ekaterina Shutova, Ekin Dogus Cubuk, Elad Segal, Eleanor Hagerman, Elizabeth 386 Barnes, Elizabeth Donoway, Ellie Pavlick, Emanuele Rodola, Emma Lam, Eric Chu, Eric Tang, 387 Erkut Erdem, Ernie Chang, Ethan A. Chi, Ethan Dyer, Ethan Jerzak, Ethan Kim, Eunice En-388 gefu Manyasi, Evgenii Zheltonozhskii, Fanyue Xia, Fatemeh Siar, Fernando Martínez-Plumed, 389 Francesca Happé, Francois Chollet, Frieda Rong, Gaurav Mishra, Genta Indra Winata, Gerard 390 de Melo, Germán Kruszewski, Giambattista Parascandolo, Giorgio Mariani, Gloria Wang, 391 Gonzalo Jaimovitch-López, Gregor Betz, Guy Gur-Ari, Hana Galijasevic, Hannah Kim, Hannah 392 Rashkin, Hannaneh Hajishirzi, Harsh Mehta, Hayden Bogar, Henry Shevlin, Hinrich Schütze, 393 Hiromu Yakura, Hongming Zhang, Hugh Mee Wong, Ian Ng, Isaac Noble, Jaap Jumelet, Jack 394 Geissinger, Jackson Kernion, Jacob Hilton, Jaehoon Lee, Jaime Fernández Fisac, James B. 395 Simon, James Koppel, James Zheng, James Zou, Jan Kocoń, Jana Thompson, Janelle Wingfield, 396 Jared Kaplan, Jarema Radom, Jascha Sohl-Dickstein, Jason Phang, Jason Wei, Jason Yosinski, 397 Jekaterina Novikova, Jelle Bosscher, Jennifer Marsh, Jeremy Kim, Jeroen Taal, Jesse Engel, 398 Jesujoba Alabi, Jiacheng Xu, Jiaming Song, Jillian Tang, Joan Waweru, John Burden, John 399 Miller, John U. Balis, Jonathan Batchelder, Jonathan Berant, Jörg Frohberg, Jos Rozen, Jose 400 Hernandez-Orallo, Joseph Boudeman, Joseph Guerr, Joseph Jones, Joshua B. Tenenbaum, 401 Joshua S. Rule, Joyce Chua, Kamil Kanclerz, Karen Livescu, Karl Krauth, Karthik Gopalakrish-402 nan, Katerina Ignatyeva, Katja Markert, Kaustubh D. Dhole, Kevin Gimpel, Kevin Omondi, 403 Kory Mathewson, Kristen Chiafullo, Ksenia Shkaruta, Kumar Shridhar, Kyle McDonell, Kyle 404 Richardson, Laria Reynolds, Leo Gao, Li Zhang, Liam Dugan, Lianhui Qin, Lidia Contreras-405 406 Ochando, Louis-Philippe Morency, Luca Moschella, Lucas Lam, Lucy Noble, Ludwig Schmidt, Luheng He, Luis Oliveros Colón, Luke Metz, Lütfi Kerem Şenel, Maarten Bosma, Maarten Sap, 407 Maartje ter Hoeve, Maheen Farooqi, Manaal Faruqui, Mantas Mazeika, Marco Baturan, Marco 408 Marelli, Marco Maru, Maria Jose Ramírez Quintana, Marie Tolkiehn, Mario Giulianelli, Martha 409 Lewis, Martin Potthast, Matthew L. Leavitt, Matthias Hagen, Mátyás Schubert, Medina Orduna 410 Baitemirova, Melody Arnaud, Melvin McElrath, Michael A. Yee, Michael Cohen, Michael Gu, 411 Michael Ivanitskiy, Michael Starritt, Michael Strube, Michał Swędrowski, Michael Bevilacqua, 412 Michihiro Yasunaga, Mihir Kale, Mike Cain, Mimee Xu, Mirac Suzgun, Mitch Walker, Mo Ti-413 wari, Mohit Bansal, Moin Aminnaseri, Mor Geva, Mozhdeh Gheini, Mukund Varma T, Nanyun Peng, Nathan A. Chi, Nayeon Lee, Neta Gur-Ari Krakover, Nicholas Cameron, Nicholas Roberts, Nick Doiron, Nicole Martinez, Nikita Nangia, Niklas Deckers, Niklas Muennighoff, 417 Nitish Shirish Keskar, Niveditha S. Iyer, Noah Constant, Noah Fiedel, Nuan Wen, Oliver Zhang, Omar Agha, Omar Elbaghdadi, Omer Levy, Owain Evans, Pablo Antonio Moreno Casares, Parth

Doshi, Pascale Fung, Paul Pu Liang, Paul Vicol, Pegah Alipoormolabashi, Peiyuan Liao, Percy 419 Liang, Peter Chang, Peter Eckersley, Phu Mon Htut, Pinyu Hwang, Piotr Miłkowski, Piyush 420 Patil, Pouya Pezeshkpour, Priti Oli, Qiaozhu Mei, Qing Lyu, Qinlang Chen, Rabin Banjade, 421 Rachel Etta Rudolph, Raefer Gabriel, Rahel Habacker, Ramon Risco, Raphaël Millière, Rhythm 422 Garg, Richard Barnes, Rif A. Saurous, Riku Arakawa, Robbe Raymaekers, Robert Frank, Rohan 423 Sikand, Roman Novak, Roman Sitelew, Ronan LeBras, Rosanne Liu, Rowan Jacobs, Rui Zhang, 424 Ruslan Salakhutdinov, Ryan Chi, Ryan Lee, Ryan Stovall, Ryan Teehan, Rylan Yang, Sahib 425 426 Singh, Saif M. Mohammad, Sajant Anand, Sam Dillavou, Sam Shleifer, Sam Wiseman, Samuel Gruetter, Samuel R. Bowman, Samuel S. Schoenholz, Sanghyun Han, Sanjeev Kwatra, Sarah A. 427 Rous, Sarik Ghazarian, Sayan Ghosh, Sean Casey, Sebastian Bischoff, Sebastian Gehrmann, 428 Sebastian Schuster, Sepideh Sadeghi, Shadi Hamdan, Sharon Zhou, Shashank Srivastava, Sherry 429 Shi, Shikhar Singh, Shima Asaadi, Shixiang Shane Gu, Shubh Pachchigar, Shubham Toshniwal, 430 Shyam Upadhyay, Shyamolima, Debnath, Siamak Shakeri, Simon Thormeyer, Simone Melzi, 431 Siva Reddy, Sneha Priscilla Makini, Soo-Hwan Lee, Spencer Torene, Sriharsha Hatwar, Stanis-432 las Dehaene, Stefan Divic, Stefano Ermon, Stella Biderman, Stephanie Lin, Stephen Prasad, 433 Steven T. Piantadosi, Stuart M. Shieber, Summer Misherghi, Svetlana Kiritchenko, Swaroop 434 Mishra, Tal Linzen, Tal Schuster, Tao Li, Tao Yu, Tariq Ali, Tatsu Hashimoto, Te-Lin Wu, Théo 435 Desbordes, Theodore Rothschild, Thomas Phan, Tianle Wang, Tiberius Nkinyili, Timo Schick, 436 Timofei Korney, Titus Tunduny, Tobias Gerstenberg, Trenton Chang, Trishala Neeraj, Tushar 437 Khot, Tyler Shultz, Uri Shaham, Vedant Misra, Vera Demberg, Victoria Nyamai, Vikas Raunak, 438 Vinay Ramasesh, Vinay Uday Prabhu, Vishakh Padmakumar, Vivek Srikumar, William Fedus, 439 William Saunders, William Zhang, Wout Vossen, Xiang Ren, Xiaoyu Tong, Xinran Zhao, Xinyi 440 Wu, Xudong Shen, Yadollah Yaghoobzadeh, Yair Lakretz, Yangqiu Song, Yasaman Bahri, Yejin 441 Choi, Yichi Yang, Yiding Hao, Yifu Chen, Yonatan Belinkov, Yu Hou, Yufang Hou, Yuntao Bai, 442 Zachary Seid, Zhuoye Zhao, Zijian Wang, Zijie J. Wang, Zirui Wang, and Ziyi Wu. Beyond the 443 imitation game: Quantifying and extrapolating the capabilities of language models, 2023. URL 444 https://arxiv.org/abs/2206.04615. 445

- [21] Noah D. Goodman, Joshua B. Tenenbaum, and Tobias Gerstenberg. Concepts in a probabilistic language of thought. In Eric Margolis and Stephen Laurence, editors, *The Conceptual Mind: New Directions in the Study of Concepts*, pages 623–654. MIT Press, 2015.
- 449 [22] Steinar Kvale. *InterViews: An Introduction to Qualitative Research Interviewing*. Sage Publications, 1996.
- Mor Geva, Daniel Khashabi, Elad Segal, Tushar Khot, Dan Roth, and Jonathan Berant. Did aristotle use a laptop? a question answering benchmark with implicit reasoning strategies, 2021. URL https://arxiv.org/abs/2101.02235.
- [24] Matthew Ho, Aditya Sharma, Justin Chang, Michael Saxon, Sharon Levy, Yujie Lu, and
 William Yang Wang. Wikiwhy: Answering and explaining cause-and-effect questions, 2022.
 URL https://arxiv.org/abs/2210.12152.
- Luke Guerdan, Amanda Coston, Zhiwei Steven Wu, and Kenneth Holstein. Ground(less) truth: A causal framework for proxy labels in human-algorithm decision-making, 2023. URL https://arxiv.org/abs/2302.06503.
- 460 [26] Jum C. Nunnally and Ira H. Bernstein. Psychometric Theory. McGraw-Hill, 3rd edition, 1994.
- ⁴⁶¹ [27] Lee J. Cronbach. Essentials of Psychological Testing. Harper & Row, 3rd edition, 1970.
- 462 [28] Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R. Bowman.
 463 Glue: A multi-task benchmark and analysis platform for natural language understanding. In
 464 Proceedings of the 2019 International Conference on Learning Representations (ICLR), 2018.
- [29] Alex Wang, Yada Pruksachatkun, Nikita Nangia, Amanpreet Singh, Julian Michael, Felix Hill,
 Omer Levy, and Samuel R. Bowman. Superglue: A stickier benchmark for general-purpose
 language understanding systems. In Advances in Neural Information Processing Systems
 (NeurIPS), 2019.
- Joon Sung Park, Carrie J. O'Brien, Carrie J. Cai, Meredith Ringel Morris, Percy Liang, and
 Michael S. Bernstein. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology (UIST)*,
 2023.

- [31] Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman
 Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. Retrieval-augmented
 generation for knowledge-intensive nlp tasks. Advances in neural information processing
 systems, 33:9459–9474, 2020.
- 477 [32] Zhao Kaiya, Michelangelo Naim, Jovana Kondic, Manuel Cortes, Jiaxin Ge, Shuying Luo,
 478 Guangyu Robert Yang, and Andrew Ahn. Lyfe agents: Generative agents for low-cost real-time
 479 social interactions, 2023. URL https://arxiv.org/abs/2310.02172.
- [33] Daniel Wurgaft, Ben Prystawski, Kanishk Gandhi, Cedegao E. Zhang, Joshua B. Tenenbaum,
 and Noah D. Goodman. Scaling up the think-aloud method. *CoRR*, abs/2505.23931, 2025. doi:
 10.48550/ARXIV.2505.23931.
- 483 [34] Simon Baron-Cohen, Alan M. Leslie, and Uta Frith. Does the autistic child have a "the-484 ory of mind"? *Cognition*, 21(1):37–46, 1985. ISSN 0010-0277. doi: https://doi. 485 org/10.1016/0010-0277(85)90022-8. URL https://www.sciencedirect.com/science/ 486 article/pii/0010027785900228.
- Francesca G. E. Happé. An advanced test of theory of mind: Understanding of story characters' thoughts and feelings by able autistic, mentally handicapped, and normal children and adults.
 Journal of Autism and Developmental Disorders, 24(2):129–154, 1994. ISSN 1573-3432. doi: 10.1007/BF02172093. URL https://doi.org/10.1007/BF02172093.
- [36] Aida Nematzadeh, Kaylee Burns, Erin Grant, Alison Gopnik, and Tom Griffiths. Evaluating theory of mind in question answering. In Ellen Riloff, David Chiang, Julia Hockenmaier, and Jun'ichi Tsujii, editors, Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing, pages 2392–2400, Brussels, Belgium, October-November 2018.
 Association for Computational Linguistics. doi: 10.18653/v1/D18-1261. URL https://aclanthology.org/D18-1261/.
- [37] Neil C. Rabinowitz, Frank Perbet, H. Francis Song, Chiyuan Zhang, S. M. Ali Eslami, and
 Matthew Botvinick. Machine theory of mind, 2018. URL https://arxiv.org/abs/1802.
 07740.
- [38] Matthew Le, Y-Lan Boureau, and Maximilian Nickel. Revisiting the evaluation of theory
 of mind through question answering. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 5872–5877, 2019.
- 504 [39] Michael Cohen. Exploring roberta's theory of mind through textual entailment. 2021.
- 505 [40] Kanishk Gandhi, Jan-Philipp Fränken, Tobias Gerstenberg, and Noah D. Goodman. Under-506 standing social reasoning in language models with language models, 2023. URL https: 507 //arxiv.org/abs/2306.15448.
- Yinghui He, Yufan Wu, Yilin Jia, Rada Mihalcea, Yulong Chen, and Naihao Deng. Hi-tom:
 A benchmark for evaluating higher-order theory of mind reasoning in large language models,
 2023. URL https://arxiv.org/abs/2310.16755.
- Hyunwoo Kim, Melanie Sclar, Xuhui Zhou, Ronan Le Bras, Gunhee Kim, Yejin Choi, and Maarten Sap. Fantom: A benchmark for stress-testing machine theory of mind in interactions, 2023. URL https://arxiv.org/abs/2310.15421.
- [43] Chuanyang Jin, Yutong Wu, Jing Cao, Jiannan Xiang, Yen-Ling Kuo, Zhiting Hu, Tomer
 Ullman, Antonio Torralba, Joshua B. Tenenbaum, and Tianmin Shu. Mmtom-qa: Multimodal
 theory of mind question answering, 2024. URL https://arxiv.org/abs/2401.08743.
- [44] Chunkit Chan, Cheng Jiayang, Yauwai Yim, Zheye Deng, Wei Fan, Haoran Li, Xin Liu,
 Hongming Zhang, Weiqi Wang, and Yangqiu Song. Negotiationtom: A benchmark for stress testing machine theory of mind on negotiation surrounding, 2024. URL https://arxiv.org/
 abs/2404.13627.
- James W. A. Strachan, Dalila Albergo, Giulia Borghini, Oriana Pansardi, Eugenio Scaliti,
 Saurabh Gupta, Krati Saxena, Alessandro Rufo, Stefano Panzeri, Guido Manzi, Michael
 S. A. Graziano, and Cristina Becchio. Testing theory of mind in large language models
 and humans. Nature Human Behaviour, 8(7):1285–1295, 2024. ISSN 2397-3374. doi:
 10.1038/s41562-024-01882-z. URL https://doi.org/10.1038/s41562-024-01882-z.

- [46] Lance Ying, Tan Zhi-Xuan, Lionel Wong, Vikash Mansinghka, and Joshua Tenenbaum. Grounding language about belief in a bayesian theory-of-mind. arXiv preprint arXiv:2402.10416, 2024.
- 529 [47] Neil Stewart, Jesse Chandler, and Gabriele Paolacci. Crowdsourcing samples in cognitive science. *Trends in cognitive sciences*, 21(10):736–748, 2017.
- [48] Lionel Wong, Gabriel Grand, Alexander K Lew, Noah D Goodman, Vikash K Mansinghka,
 Jacob Andreas, and Joshua B Tenenbaum. From word models to world models: Translating from
 natural language to the probabilistic language of thought. arXiv preprint arXiv:2306.12672,
 2023.
- [49] Brenden M Lake, Tomer D Ullman, Joshua B Tenenbaum, and Samuel J Gershman. Building
 machines that learn and think like people. *Behavioral and Brain Sciences*, 40, 2017.
- [50] Kevin Ellis, Catherine Wong, Maxwell Nye, Mathias Sable-Meyer, Luc Cary, Lucas Morales,
 Luke Hewitt, Armando Solar-Lezama, and Joshua B. Tenenbaum. Dreamcoder: Growing
 generalizable, interpretable knowledge with wake-sleep bayesian program learning, 2020. URL
 https://arxiv.org/abs/2006.08381.
- [51] Zhiting Hu and Tianmin Shu. Language models, agent models, and world models: The law for
 machine reasoning and planning, 2023. URL https://arxiv.org/abs/2312.05230.
- [52] David Maxwell Chickering. Optimal structure identification with greedy search. *Journal of machine learning research*, 3(Nov):507–554, 2002.
- [53] N Pohontsch and T Meyer. Cognitive interviewing-a tool to develop and validate questionnaires.
 Die Rehabilitation, 54(1):53–59, 2015.
- [54] Tianyi Zhang, Isaac Tham, Zhaoyi Hou, Jiaxuan Ren, Liyang Zhou, Hainiu Xu, Li Zhang,
 Lara J Martin, Rotem Dror, Sha Li, et al. Human-in-the-loop schema induction. arXiv preprint
 arXiv:2302.13048, 2023.
- [55] Roger Tourangeau, Lance J. Rips, and Kenneth Rasinski. *The Psychology of Survey Response*.
 Cambridge University Press, Cambridge, UK, 2000.
- [56] Maarten W Van Someren, Yvonne F Barnard, Jacobijn AC Sandberg, et al. The think aloud
 method: a practical approach to modelling cognitive processes. *London: AcademicPress*, 11(6),
 1994.
- [57] Herbert H. Clark. *Using Language*. Cambridge University Press, 1996.
- [58] Daniel Driess, Fei Xia, Mehdi SM Sajjadi, et al. Palm-e: An embodied multimodal language
 model. In *Proceedings of ICML*, 2023.
- [59] Alison Gopnik and Laura Schulz. Causal learning: Psychology, philosophy, and computation.
 Oxford University Press, 2007.
- 560 [60] Steven Sloman. Causal Models: How People Think About the World and Its Alternatives.
 561 Oxford University Press, 2009.
- Feter W Battaglia, Jessica B Hamrick, Victor Bapst, Alvaro Sanchez-Gonzalez, Vinicius
 Zambaldi, Mateusz Malinowski, Andrea Tacchetti, David Raposo, Adam Santoro, Ryan
 Faulkner, et al. Relational inductive biases, deep learning, and graph networks. arXiv preprint
 arXiv:1806.01261, 2018.

A Related Work

566

Social Simulation, Digital Twins, and Population Panels. A growing line of work simulates 567 societies with LLM agents. Early "silicon samples" use LMs to approximate human samples in 568 stylized tasks [2], while Generative Agents extend to rich daily-life environments with memory and 569 social coordination [30]. This has scaled to population panels—e.g., simulations of 1,000 people [1] 570 and digital-twin datasets such as Twin-2K-500 [9]—as well as community/role-play platforms for 571 real-time social interaction [32] and personification benchmarks [19, 3]. These approaches provide 572 breadth and largely static outcome measures; **HugAgent** adds depth via think-aloud transcripts that 573 trace reasoning trajectories, counterfactual interventions to test belief updates, and a human test-retest 574 reliability ceiling to anchor claims [33, 26, 27]. 575

Social Reasoning and Theory of Mind. Work on Theory of Mind (ToM) in AI draws from 576 developmental psychology tests such as the false-belief task [13], Sally-Anne [34], and Strange 577 Stories [35], later reformulated as computational tasks [36, 37]. Scaled language models brought 578 ToM into broad benchmarks [38, 39, 20, 14] and inspired synthetic testbeds such as BigToM [40], 579 HI-TOM [41], FANTOM [42], and MMTOM-QA [43]. More recent directions ground ToM in 580 dialogues and social contexts [44, 12, 45], or frame it through Bayesian belief attribution [46]. Yet 581 these benchmarks remain synthetic, vignette-based, and decontextualized, missing ecological and 582 demographic variability [5, 47]. 583

Parallel lines in AI reasoning emphasize world and agent models: causal world modeling [48–50] and the LAW framework, which coordinates world, agent, and language models [51]. Within this framing, HugAgent extends ToM evaluation by asking whether models can map natural language into personalized belief states and update them consistently under interventions, bridging synthetic ToM tasks and socially grounded reasoning.

B Auxiliary Dataset

589

Our core benchmark is designed around interview transcripts, where each data point consists of demographic information, a context in the form of question—answer pairs, and ground-truth first-person self-reports. This setup defines a clean belief inference language task: given demographic cues and conversational context, models must infer individual beliefs and predict reactions.

To complement this benchmark, we also release an auxiliary demographics-only dataset (39 users, each with survey responses and demographic attributes). While these records do not support direct belief inference, they enable principled baselines and transfer settings. Concretely, we implemented a demographic–linear regression model based on survey responses, and further tested Qwen-Plus on the main belief dynamics update task with auxiliary supervision from a subset of 15 users. Results from both the demographic-linear baseline and the augmented Qwen-Plus setting are reported in Table 7, illustrating how population-level priors can inform personalized inference.

Table 7: Results on the auxiliary demographics-only setting. Comparison of a demographic-only prior baseline and Qwen-Plus with auxiliary supervision across three domains. Higher accuracy and lower MAE indicate better performance.

Domain	Demographi	c-only prior	Qwen-Plus w	/ auxiliary data
201114111	Accuracy	MAE	Accuracy	MAE
Healthcare Zoning Surveillance	0.130 0.202 0.081	2.954 2.954 2.797	0.524 0.474 0.589	1.792 1.765 1.819

C HugAgent Benchmark Details

601

- We introduce the **HugAgent Benchmark** (*HUman-Grounded Theory of Mind*), a new evaluation suite for reasoning fidelity in generative agents. HugAgent formalizes the task of *causal BN reconstruction* from human interviews, and provides (1) a dataset of annotated causal belief graphs derived from natural language Q&A, and (2) multi-level evaluation metrics (node, edge, motif) to assess structural alignment between human and agent reasoning.
- Unlike prior benchmarks focused on behavioral imitation or chain-of-thought generation, HugAgent directly evaluates whether agents can reconstruct the latent causal structures that underlie human judgments. This benchmark responds to recent concerns that LLM-based agents risk flattening individual identity representations by grounding evaluation in structured, human-annotated causal beliefs.

Data schema and cognitive grounding

- Inspired by cognitive science, we use causal BNs to represent the reasoning structures underlying human decision-making. Rather than modeling surface discourse, our schema captures latent causal dynamics by explicitly linking belief variables, affective states, and behavioral intentions in a directed graph. This design supports psychologically grounded and structurally coherent representations of human reasoning.
- Schema Design Each participant's causal BN is represented as a structured JSON object composed of three main components: nodes, edges, and qa_history. This schema is designed to encode causal beliefs extracted from interviews, with each element indexed by a unique ID to enable motif analysis, simulation, and evidence tracing.
- Nodes Each node represents a belief concept and includes a label, a model-generated confidence score (ranging from 0.0 to 1.0), and a list of source_qa IDs that support the node's existence. Nodes also track their incoming_edges and outgoing_edges for efficient graph traversal.
- Edges Edges capture directed causal links between nodes. Each edge includes a source node ID, a target node ID, and an aggregate_confidence score reflecting the model's overall belief in the causal connection. A modifier (in the range [-1.0, 1.0]) represents the direction and strength of influence: positive values indicate causal support, negative values indicate inhibition. Each edge is backed by a list of individual QA-based evidence entries with associated confidence scores.
- QA History The qa_history component stores raw interview responses, mapping each QA pair to its corresponding extracted causal relations. Each QA entry includes the original question and answer texts, as well as a list of extracted_pairs, where each pair links a source node to a target node with a confidence score.
- This data structure supports fine-grained analysis of belief formation, causal reasoning, and evidence provenance across participants.

636 Dataset Construction

We collected over 100 interviews from participants recruited through the Prolific platform. Topics—such as urban upzoning, surveillance cameras, and universal healthcare—were chosen to elicit reflective, ecologically valid reasoning.

640 Transcript Collection

645

To construct structured causal BNs from qualitative interviews, we developed a **semi-structured**, **cognitively grounded elicitation framework**. This framework guides LLMs in extracting interpretable causal structures from natural language dialogue and generating follow-up questions that balance open-ended exploration with targeted inquiry [52, 53].

Human Annotation Protocol

We asked annotators to label causal BNs using soft labels, capturing graded beliefs and allowing for variation across annotators. Our human-in-the-loop annotation tool supports annotators in assigning confidence scores to each node and edge[54].

- Annotators were also recruited from Prolific [47]. During selection, we followed three principles: (1)
- double-blind annotation, (2) matching annotators with similar backgrounds, and (3) using shared
- guidelines to maintain consistency. Annotation instructions were carefully designed to ensure
- 652 reproducibility and interpretability.

Evaluation Settings

653

- All models are evaluated under a consistent inference setup. We fix the random seed to 42 and set
- the temperature to 0.1 for all experiments. Models from the GPT and Gemini series are executed in
- batch inference mode, while all other models use real-time completion inference. All outputs are
- constrained using function calling to ensure structured and valid responses. Prompts adopt a pure
- 658 in-context learning format without any examples or reasoning demonstrations.
- For the Generative Agents setting, following [30], we employ Qwen2.5-32B-instruct to analyze
- the dialogue transcript and generate three high-level expert reflections that serve as auxiliary reasoning
- cues during inference. For the two retrieval-augmented variants of RAG[31], we adopt a TF-IDF
- retriever to identify the top five most relevant QA pairs.

663 Human Baselines

- We re-contacted a subset of participants for a short-interval (14-day) test-retest study. Across all
- sessions, 54 participants contributed data. Of these, 18 completed the retest, and 13 were retained
- 666 following a demographic consistency check.
- 667 Belief State Inference yielded an accuracy of **84.84**% (SD = 8.90, 95% CI: [80.00, 89.68]). By topic,
- 668 accuracies were **87.50**% for *Surveillance* (SD = 8.29, 95% CI: [82.81, 92.19]), **81.54**% for *Zoning*
- 669 (SD = 15.11, 95% CI: [73.32, 89.75]), and **84.53**% for *Healthcare* (SD = 13.90, 95% CI: [76.97,
- 670 92.09]).
- 671 Belief Dynamics Update achieved an accuracy of **85.66**% (SD = 7.66, 95% CI: [80.91, 90.40]) and a
- mean absolute error of **0.68** (SD = 0.20, 95% CI: [0.55, 0.80]). Across topics, accuracy was **85.75**%
- for Healthcare (SD = 10.68), 85.33% for Surveillance (SD = 12.98), and 85.86% for Zoning (SD)
- = 10.08). Corresponding mean absolute errors were **0.66** (SD = 0.28, 95% CI: [0.49, 0.83]) for
- 675 Healthcare, **0.72** (SD = 0.35, 95% CI: [0.50, 0.93]) for Surveillance, and **0.67** (SD = 0.28, 95% CI:
- 676 [0.49, 0.84]) for Zoning.
- 677 In the Belief Dynamics Update tasks, we decompose directional accuracy into two components:
- 678 (1) **change detection**—the model's ability to detect whether a belief change has occurred, and (2)
- direction adjustment—the model's ability to predict the direction of that change (increase, decrease,
- or no change) (detailed definitions are provided in Appendix Q.1).
- Overall, the directional accuracy was **88.92**% (SD = 9.89, 95% CI: [82.09, 96.24]). The results across topics are summarized as follows:
- **Healthcare:** change detection = 80.00% (SD = 25.82, 95% CI: [61.53, 98.47]); direction adjustment = 96.67% (SD = 10.54, 95% CI: [89.13, 100.00]); directional accuracy = 91.67% (SD = 11.06, 95% CI: [83.76, 99.58]).
- **Surveillance:** change detection = 90.00% (SD = 16.10, 95% CI: [78.48, 100.00]); direction adjustment = 88.33% (SD = 19.33, 95% CI: [74.51, 100.00]); directional accuracy = 88.83% (SD = 15.15, 95% CI: [77.99, 99.67]).
- **Zoning:** change detection = 80.00% (SD = 23.31, 95% CI: [63.33, 96.67]); direction adjustment = 90.00% (SD = 21.08, 95% CI: [74.92, 100.00]); directional accuracy = 87.00% (SD = 18.14, 95% CI: [74.03, 99.97]).

Full Results

		Human Dataset (N=54)											
Model	Belie	f State Infe	rence			elief Dynam	ics Update						
		Acc. (% ↑)			Acc. (% ↑)			MAE (↓)					
	Health	Surveil.	Zoning	Health	Surveil.	Zoning	Health	Surveil.	Zoning				
Human	84.53	87.50	81.54	85.75	85.33	85.86	0.66	0.72	0.67				
OpenAI Models													
GPT-40				$61.57^{\pm0.19}$									
GPT-5-mini				$59.92^{\pm 1.05}$									
o3-mini	$69.26^{\pm 1.21}$	$77.38^{\pm 1.70}$	$78.73^{\pm0.87}$	$60.08^{\pm0.28}$	$62.53^{\pm 1.16}$	$71.02^{\pm0.79}$	$1.31^{\pm0.02}$	$1.29^{\pm0.03}$	$1.07^{\pm0.01}$				
Other Closed-Source Me													
Gemini 2.0 Flash				$56.23^{\pm0.12}$									
DeepSeek-R1-0528				$61.44^{\pm0.58}$									
Qwen-plus_2025-07-28				$56.74^{\pm0.59}$									
Qwen-max_2024-10-15	$78.52^{\pm0.77}$	$76.39^{\pm0.37}$	$77.30^{\pm0.43}$	$56.78^{\pm0.64}$	$57.69^{\pm0.27}$	$62.11^{\pm0.35}$	$1.43^{\pm0.01}$	$1.44^{\pm0.01}$	$1.34^{\pm0.00}$				
Open-Source Models													
LLaMA_3.3_70B				64.28 ^{±0.38}									
Qwen2.5-32B-instr.				$56.82^{\pm0.41}$									
Qwen2.5-7B-instr	$78.33^{\pm0.51}$	$75.74^{\pm 2.06}$	$77.46^{\pm0.43}$	$56.82^{\pm0.41}$	$57.64^{\pm0.45}$	$62.00^{\pm0.34}$	$1.43^{\pm0.01}$	$1.43^{\pm0.01}$	$1.34^{\pm0.01}$				
Memory-Augmented Bas													
RAG^1				$50.64^{\pm0.58}$									
RAG-FC ¹				$58.73^{\pm0.55}$									
Generative Agents ²	$76.11^{\pm0.41}$	$77.21^{\pm0.37}$	$75.24^{\pm0.66}$	$57.67^{\pm0.76}$	55.66 ^{±0.69}	$61.35^{\pm0.38}$	$1.43^{\pm0.01}$	$1.44^{\pm0.01}$	$1.34^{\pm0.00}$				

Table 8: Results on **Human** dataset for *belief state inference* and *belief dynamics update* tasks across three policy topics (Health, Surveillance, Zoning). Values are mean ^{±std} over 5 runs. For *belief dynamics update*, both Accuracy and MAE are reported separately. Best non-human results per column are in **bold**.

	Synthetic Dataset (N=50)											
GPT-40 GPT-5-mini o3-mini Other Closed-Source M Gemini 2.0 Flash DeepSeek-R1-0528 Qwen-plus_2025-07-2 Qwen-max_2024-10-1 Open-Source Models LLaMA_3.3_70B Qwen2.5-32B-instr. Qwen2.5-7B-instr	Beli	ef State Infe Acc. (% ↑)			Be Acc. (% ↑)	elief Dynam	ics Update	MAE (\lambda)				
	Health	Surveil.	Zoning	Health	Surveil.	Zoning	Health	Surveil.	Zoning			
OpenAI Models												
GPT-40	$60.76^{\pm0.00}$	$75.00^{\pm0.77}$	$68.03^{\pm0.58}$	$52.71^{\pm0.29}$	$65.00^{\pm0.35}$	$58.11^{\pm0.48}$	$1.72^{\pm0.00}$	$1.18^{\pm0.01}$	$1.41^{\pm0.01}$			
GPT-5-mini	$50.38^{\pm 1.88}$	$72.39^{\pm 1.24}$	$53.61^{\pm 26.80}$	$51.09^{\pm0.91}$	$64.44^{\pm0.46}$	$56.23^{\pm 1.63}$	$1.74^{\pm0.01}$	$1.21^{\pm0.02}$	$1.46^{\pm0.02}$			
o3-mini	$58.23^{\pm 1.55}$	78.48 $^{\pm 1.19}$	$72.30^{\pm1.47}$	$46.90^{\pm0.81}$	$58.46^{\pm0.28}$	$64.07^{\pm0.37}$	$1.80^{\pm0.02}$	$1.29^{\pm0.00}$	$1.26^{\pm0.01}$			
Other Closed-Source Me	odels											
Gemini 2.0 Flash			$63.61^{\pm0.45}$									
DeepSeek-R1-0528	$62.78^{\pm 1.13}$	$75.87^{\pm 1.42}$	$73.61^{\pm0.69}$	$60.52^{\pm0.18}$	$64.75^{\pm0.40}$	$58.21^{\pm0.45}$	$1.59^{\pm0.01}$	$1.15^{\pm0.01}$	$1.40^{\pm0.01}$			
Qwen-plus_2025-07-28			$71.80^{\pm0.73}$									
Qwen-max_2024-10-15	$62.78^{\pm 2.12}$	$68.48^{\pm0.00}$	$71.97^{\pm0.37}$	$45.20^{\pm0.44}$	$64.57^{\pm0.14}$	$55.83^{\pm0.46}$	$1.80^{\pm0.00}$	$1.18^{\pm0.01}$	$1.50^{\pm0.01}$			
Open-Source Models												
LLaMA_3.3_70B	$61.27^{\pm 1.13}$	$76.09^{\pm0.00}$	77.87 $^{\pm0.00}$	$51.44^{\pm0.65}$	$57.65^{\pm0.34}$	$65.96^{\pm0.21}$	$1.82^{\pm0.01}$	$1.32^{\pm0.00}$	$1.32^{\pm0.00}$			
Qwen2.5-32B-instr.	$64.30^{\pm0.56}$	$68.70^{\pm0.49}$	$71.64^{\pm0.93}$	$45.24^{\pm0.39}$	$65.00^{\pm0.17}$	$55.88^{\pm0.54}$	$1.80^{\pm0.00}$	$1.18^{\pm0.00}$	$1.50^{\pm0.01}$			
Qwen2.5-7B-instr	$63.80^{\pm 1.13}$	$68.48^{\pm1.33}$	$71.15^{\pm0.90}$	$45.11^{\pm0.29}$	$64.81^{\pm0.22}$	$56.08^{\pm0.25}$	$1.80^{\pm0.00}$	$1.18^{\pm0.01}$	$1.50^{\pm0.01}$			
Memory-Augmented Bas	selines											
RAG^1	$51.39^{\pm 1.44}$	$67.61^{\pm0.90}$	$70.16^{\pm 1.37}$	$43.49^{\pm0.28}$	$61.98^{\pm0.40}$	$50.07^{\pm0.32}$	$1.85^{\pm0.00}$	$1.22^{\pm0.01}$	$1.61^{\pm0.00}$			
RAG-FC ¹	$68.10^{\pm 1.65}$	$76.09^{\pm 1.09}$	$74.26^{\pm 1.10}$	$53.41^{\pm0.45}$	$64.26^{\pm0.46}$	$60.35^{\pm0.59}$	$1.70^{\pm0.01}$	$1.20^{\pm0.01}$	$1.44^{\pm0.01}$			
Generative Agents ²	68.61 ^{±0.57}	$77.39^{\pm0.91}$	$74.43^{\pm0.37}$	$46.24^{\pm0.68}$	$64.26^{\pm0.26}$	$55.78^{\pm0.21}$	$1.79^{\pm0.01}$	$1.17^{\pm0.00}$	$1.52^{\pm0.01}$			

Table 9: Results on **Synthetic** dataset for *belief state inference* and *belief dynamics update* tasks across three policy topics (Health, Surveillance, Zoning). Values are mean ^{±std} over 5 runs. For *belief dynamics update*, both Accuracy and MAE are reported separately. Best results per column are in **bold**.

Model	Belief Dynamics Update											
Model	Change	Detection A	cc. (%†)	Direction	Adjustment	Acc. (%↑)	Ι	Dir. Acc. (%	†)			
	Health	Surveil.	Zoning	Health	Surveil.	Zoning	Health	Surveil.	Zoning			
Human	80.00	90.00	80.00	96.67	88.33	90.00	91.67	88.83	87.00			
OpenAI Models												
GPT-40				$88.89^{\pm0.00}$								
GPT-5-mini				$82.95^{\pm 2.56}$								
o3-mini	$50.64^{\pm4.54}$	$55.83^{\pm4.25}$	$59.05^{\pm 5.71}$	$76.43^{\pm4.84}$	$79.58^{\pm 3.64}$	$78.59^{\pm 12.06}$	$68.69^{\pm3.33}$	$72.45^{\pm 3.10}$	$72.72^{\pm 8.67}$			
Other Closed-Source Me	odels											
Gemini 2.0 Flash				$100.00^{\pm0.00}$								
DeepSeek-R1-0528				$83.62^{\pm 2.10}$								
Qwen-plus_2025-07-28	$34.04^{\pm 2.33}$	$63.01^{\pm 1.94}$	66.67 ^{±0.00}	$85.24^{\pm0.95}$	$83.03^{\pm0.61}$	$92.31^{\pm0.00}$	$69.88^{\pm0.97}$	$77.02^{\pm0.89}$	$84.62^{\pm0.00}$			
Qwen-max_2024-10-15	$34.89^{\pm 1.04}$	$63.33^{\pm 1.67}$	66.67 ^{±0.00}	$85.71^{\pm0.00}$	$82.05^{\pm 2.56}$	$92.31^{\pm0.00}$	$70.47^{\pm0.31}$	$76.44^{\pm 1.29}$	$84.62^{\pm0.00}$			
Open-Source Models												
LLaMA_3.3_70B				$80.00^{\pm0.00}$								
Qwen2.5-32B-instr.				$84.29^{\pm 1.17}$								
Qwen2.5-7B-instr	$33.62^{\pm 1.59}$	$62.50^{\pm0.00}$	$65.63^{\pm 1.40}$	$84.29^{\pm 1.17}$	$83.33^{\pm0.00}$	$93.57^{\pm 3.26}$	$69.09^{\pm 1.03}$	$77.08^{\pm0.00}$	$85.19^{\pm 2.30}$			
Memory-Augmented Bas												
RAG^1	$42.55^{\pm 1.90}$	$55.83^{\pm 5.00}$	66.67 $^{\pm0.00}$			$85.71^{\pm0.00}$						
RAG-FC ¹	$45.11^{\pm 2.08}$	$62.43^{\pm6.00}$	$60.95^{\pm 1.90}$			$86.03^{\pm 2.82}$						
Generative Agents ²	$36.17^{\pm 1.90}$	$61.06^{\pm 2.27}$	$60.95^{\pm 1.90}$	$81.00^{\pm 9.70}$	$83.64^{\pm3.64}$	$93.85^{\pm 3.08}$	$67.55^{\pm6.41}$	$76.86^{\pm2.20}$	$83.98^{\pm 1.58}$			

Table 10: Directional accuracy results on **Human** dataset for *belief dynamics update* task across three policy topics (Health, Surveillance, Zoning). Values are mean \pm std over 5 runs. For each topic, we report Change Detection Accuracy, Direction Adjustment Accuracy, and Directional Accuracy (Dir. Acc). Best results per column are in **bold**.

693 Results on Human Dataset

Task	Model	Belief State Inference (Accuracy (% ↑))				Belie	f Dynamics Upd	late (Accuracy ((% ↑))	Belief Dynamics Update (MAE ↓)			
		Health	Surv.	Zone	Avg	Health	Surv.	Zone	Avg	Health	Surv.	Zone	Avg
Swap-cross_person	Gemini 2.0 Flash Owen2.5-32B-instr.	52.78 ^{±0.65} 58.15 ^{±0.77}	52.79 ^{±1.49} 64.75 ^{±0.00}	47.46 ^{±0.66} 58.41 ^{±0.90}	51.01 ^{±2.76} 60.44 ^{±3.22}	34.19 ^{±0.12} 33.77 ^{±0.73}	40.71 ^{±0.36} 40.77 ^{±0.63}	39.35 ^{±0.16} 39.93 ^{±0.46}	38.08 ^{±2.91} 38.16 ^{±3.28}	2.13 ^{±0.01} 2.19 ^{±0.01}	1.85 ^{±0.01} 1.87 ^{±0.01}	2.05 ^{±0.00} 2.01 ^{±0.00}	2.01 ^{±0.12} 2.02 ^{±0.13}
	GPT-40	50.93 ^{±7.29}	61.31 ^{±0.37}	51.11 ^{±0.71}	54.45 ^{±6.37}	37.37 ^{±0.19}	43.13 ^{±0.75}	37.38 ^{±0.28}	39.30 ^{±2.84}	2.02 ^{±0.01}	1.80 ^{±0.01}	1.98 ^{±0.01}	1.93 ^{±0.10}

Table 11: Human **Cross_Person** test: models trained on one participant and evaluated on another. Reported as mean \pm std over 5 runs.

¹RAG [31], RAG-FC = RAG with Full Context [31].

²Generative Agents [30].

¹RAG [31], RAG-FC = RAG with Full Context [31].

²Generative Agents [30].

Results on Synthetic Dataset

Model	Context	Bel	ief State Inferer	ce (Accuracy (% ↑))	Belie	f Dynamics Upd	late (Accuracy (% ↑))	Ве	lief Dynamics	Update (MAE	1)
		Health	Surv.	Zone	Avg	Health	Surv.	Zone	Avg	Health	Surv.	Zone	Avg
GPT-4o	10 QAs	56.96 ^{±1.27} 62.28 ^{±1.06} 60.76 ^{±0.00}	$74.13^{\pm0.49}$	62.30 ^{±1.00} 66.89 ^{±0.45} 68.03 ^{±0.58}		53.23 ^{±0.71} 52.18 ^{±0.44} 52.71 ^{±0.29}		56.28 ^{±0.27} 55.53 ^{±1.78} 58.11 ^{±0.48}	57.90 ^{±4.80} 57.61 ^{±5.76} 58.61 ^{±5.22}		1.18 ^{±0.01} 1.17 ^{±0.01} 1.18 ^{±0.01}	$1.44^{\pm0.00}$	1.43 ^{±0.21} 1.45 ^{±0.24} 1.44 ^{±0.23}
Gemini 2.0 Flash	5 QAs 10 QAs 20+ QAs	37.97 ^{±0.00} 43.04 ^{±0.00} 51.90 ^{±0.00}	63.48 ^{±0.60} 61.74 ^{±0.49} 63.48 ^{±1.24}	57.38 ^{±0.00} 62.13 ^{±0.90} 63.61 ^{±0.45}	52.94 ^{±11.26} 55.64 ^{±9.24} 59.66 ^{±5.73}	42.75 ^{±0.18} 41.79 ^{±0.25} 45.28 ^{±0.20}	63.64 ^{±0.14} 63.02 ^{±0.14} 62.96 ^{±0.00}	54.09 ^{±0.18} 55.73 ^{±0.14} 55.93 ^{±0.22}	53.49 ^{±8.84} 53.51 ^{±9.12} 54.73 ^{±7.52}	1.82 ^{±0.00} 1.83 ^{±0.00} 1.77 ^{±0.00}	1.18 ^{±0.00} 1.19 ^{±0.00} 1.18 ^{±0.00}	1.54 ^{±0.00} 1.52 ^{±0.00} 1.49 ^{±0.00}	
Qwen2.5-32B-instr.	10 QAs	47.34 ^{±2.12} 59.24 ^{±1.39} 64.30 ^{±0.57}	68.70 ^{±0.91}	66.56 ^{±0.37} 70.82 ^{±0.73} 71.64 ^{±0.93}	60.50 ^{±9.73} 66.25 ^{±5.30} 68.21 ^{±3.18}	45.37 ^{±0.57} 44.76 ^{±0.41} 45.24 ^{±0.39}	$64.75^{\pm0.14}$	54.74 ^{±0.62}	54.75 ±8.46	$1.83^{\pm0.01}$	1.18 ^{±0.01} 1.18 ^{±0.01} 1.18 ^{±0.00}	1.56 ^{±0.01} 1.52 ^{±0.01} 1.50 ^{±0.01}	

Table 12: Synthetic *belief state inference* and *belief dynamics update* performance across question lengths (5Q, 10Q, 20Q) for *GPT-4o*, *Gemini 2.0 Flash* and *Qwen2.5-32B-instr.*. Reported as mean \pm std over 5 runs. Best in each **column (across all models)** is bolded.

Task	Model	$Health \rightarrow Surv$	$Surv \rightarrow Zone$	$Zone \rightarrow Health$	Avg.
Belief State Inference (Accuracy (% ↑))	GPT-40 Gemini 2.0 Flash Qwen2.5-32B-instr.	$18.99^{\pm 0.90}$ $17.97^{\pm 2.26}$ $22.78^{\pm 1.55}$	$50.22^{\pm0.49}$ $38.91^{\pm0.91}$ $48.26^{\pm1.97}$	$39.67^{\pm 0.73}$ $20.49^{\pm 1.30}$ $45.57^{\pm 0.73}$	$36.29^{\pm 13.44}$ $25.79^{\pm 9.77}$ $38.87^{\pm 11.91}$
Belief Dynamics Update (Accuracy (% ↑))	GPT-40 Gemini 2.0 Flash Qwen2.5-32B-instr.	$43.62^{\pm0.71}$ $36.03^{\pm0.22}$ $34.28^{\pm0.56}$	$55.43^{\pm0.64}$ $41.73^{\pm0.51}$ $23.40^{\pm0.34}$	$35.58^{\pm0.28}$ $52.06^{\pm0.32}$ $26.65^{\pm0.89}$	$44.88^{\pm 8.45}$ $43.27^{\pm 6.88}$ $28.11^{\pm 4.76}$
Belief Dynamics Update (MAE ↓)	GPT-40 Gemini 2.0 Flash Qwen2.5-32B-instr.	$1.64^{\pm 0.01} 1.97^{\pm 0.00} 2.16^{\pm 0.01}$	$1.45^{\pm 0.01} 1.70^{\pm 0.01} 1.88^{\pm 0.01}$	$1.73^{\pm 0.00} 1.62^{\pm 0.01} 2.12^{\pm 0.01}$	$1.61^{\pm 0.12} 1.76^{\pm 0.15} 2.05^{\pm 0.13}$

Table 13: Synthetic **Cross_Domain** test: models are trained in one topic domain and evaluated on another. Reported as mean \pm std over 5 runs.

Task Model		Belief State Inference (Accuracy (% ↑))			Belief Dynamics Update (Accuracy (% ↑))			Belief Dynamics Update (MAE (↓)					
		Health	Surv.	Zone	Avg	Health	Surv.	Zone	Avg	Health	Surv.	Zone	Avg
Swap-cross_person	GPT-40 Gemini 2.0 Flash Qwen2.5-32B-instr.	41.52 ^{±1.06} 30.89 ^{±0.69} 42.28 ^{±1.13}	54.35 ^{±0.00} 47.83 ^{±0.00} 55.00 ^{±0.60}	33.11 ^{±0.73} 33.93 ^{±0.45} 34.75 ^{±0.45}	42.99 ^{±9.06} 37.55 ^{±7.64} 44.01 ^{±8.68}	$40.17^{\pm0.22}$ $30.13^{\pm0.15}$ $32.10^{\pm0.53}$	52.90 ^{±0.35} 50.93 ^{±0.00} 52.78 ^{±0.22}	36.72 ^{±0.50} 35.53 ^{±0.11} 35.04 ^{±0.32}	43.27 ^{±7.21} 38.86 ^{±9.12} 39.97 ^{±9.46}	$2.04^{\pm0.00}$ $2.16^{\pm0.00}$ $2.14^{\pm0.01}$	1.54 ^{±0.00} 1.52 ^{±0.00} 1.49 ^{±0.00}	$2.00^{\pm 0.00}$ $2.06^{\pm 0.00}$ $2.06^{\pm 0.00}$	1.86 ^{±0.24} 1.91 ^{±0.29} 1.90 ^{±0.30}

Table 14: Synthetic **Cross_Person** test: models trained on one participant and evaluated on another. Reported as mean \pm std over 5 runs.

695 D Chatbot Design




Figure 4: Overview of the QA loop and data structures. The system integrates the Causal Belief Network (CBN), Node Queue, and Question List to guide interaction. Stages regulate question priorities, with an irreversible transition from Stage 1 to Stage 2 once anchor nodes ≥ 3 .

696 Core Data Structures

The system is built on three key data structures: (i) the **Causal Belief Network** (**CBN**), (ii) the **Node Queue**, and (iii) the **Question List**. Together with a staged QA loop, these structures support the
dynamic modeling of user beliefs and the generation of targeted questions.

700 Causal Belief Network (CBN)

The CBN is the central representation of the user's belief system. It organizes concepts as nodes and captures their relations as edges.

- **Nodes.** Nodes represent concepts in the belief system.
 - Candidate Nodes: new concepts detected in user answers, under evaluation.
 - *Belief Nodes*: stable concepts that have been upgraded from candidates (e.g., due to repeated mentions or high user confidence).
 - Anchor Nodes: a subset of belief nodes that play a special role in question generation and stage transition.
- **Edges.** Edges encode causal or influence relations between nodes. They specify direction (source → target), polarity (positive/negative), and optionally strength.

711 Node Queue

704

705

706

707

708

The Node Queue maintains candidate nodes that may become belief nodes.

- Entry Condition: a new concept first appears in user responses.
- **Upgrade Condition:** node is promoted to belief node when thresholds are met (e.g., frequency of mention, confidence expressed by the user).

716 Ouestion List

The Question List stores both guiding questions and follow-up questions. It is dynamically updated based on the current CBN and node queue, and it serves as the buffer for delivering the next question to the user.

720 OA Loop Overview

The overall interaction loop proceeds as follows:

- 1. **Initialization.** The CBN contains only a stance node.
- 2. **User Input.** User provides a new answer.
- 3. **Update.** Update the CBN and node queue based on the answer.
- Question Generation. Generate new questions using the CBN and queues; append them to the question list.
- 5. **Next Question.** Select and ask the next question from the list.

728 Two-Stage Design

- The QA loop has two stages. The transition occurs when the number of anchor nodes ≥ 3 . This transition is one-way; Stage 2 never returns to Stage 1.
- **Stage 1.** Only Priority 2 questions are allowed. Rationale: with too few anchors, meaningful relationship questions are not possible. The system must first accumulate important concepts to avoid premature exploration.
- **Stage 2.** Questions are selected from a candidate list according to priority. Higher-priority items are chosen first.

736 Question Priorities

737

754

• Priority 1 – Stance Connection.

- Purpose: connect essential concepts to the user's stance.
- Condition: isolated anchor (out-degree = 0, not connected to stance).
- Format: "How does {anchor} affect your support for {stance}? Positive or negative? How strong?"
- *Example:* "How does privacy protection affect your support for surveillance?"

• Priority 2 – Node Discovery / Upstream Exploration.

- Purpose: discover new concepts or explore influencing factors of anchors.
- Condition: in Stage 1 or anchor has fewest in-degrees.
- 746 Format (Stage 1): "Tell me more about {concept}."
- Format (Stage 2): "What factors influence {anchor}? Positive or negative?"
- 748 Examples: "Tell me more about public safety."; "What factors influence government oversight?"

• Priority 3 – Relationship Strengthening.

- Purpose: quantify the strength and direction of existing relationships.
- Condition: edge requires parameters or graph pattern needs completion.
- Format: "How strong is the relationship between {A} and {B}? Positive or negative?"
- 753 Example: "How does technological advancement affect privacy protection? Strong or weak?"

• Priority 4 – General Backup.

- Purpose: fill in missing information at the end of the interview.
- Condition: remaining questions ≤ 3 and candidate pool insufficient.
- 757 Format: "Anything else important we have not discussed?"
- 758 Example: "Any clarifications on your previous answers?"

759 E Semi-Structured Interview and Causal Belief Network Formalization



Figure 5: Illustration of the semi-structured interview process and causal belief network construction. The chatbot begins with open-ended questions and extracts candidate concepts from user responses (Anchor Node Discovery). Once three or more anchors are identified, it transitions to targeted follow-ups to expand causal relations (Anchor Expansion). Edges represent directional influences with polarity, forming the evolving CBN.

Semi-Constructed Interview Design. We use GPT-4 (or Qwen for open-source deployments) as the backbone of a semi-structured interviewer. The model follows a two-phase logic:

- 1. **Anchor Node Discovery:** From initial open-ended responses, the system uses noun-phrase mining and causal phrase detection to extract candidate belief variables. Candidates that appear in multiple QA pairs or show causal centrality are promoted to *anchor nodes*, representing key ideas around which reasoning is structured.
- Anchor Expansion: For each anchor node, the system asks targeted follow-ups (e.g., "What causes this?" or "What does this influence?"). These responses are parsed into edges, which represent directional causal relations with confidence scores and modifiers (positive or negative influence).

causal BN Formalization. Each participant's graph is a Directed Acyclic Graph (DAG), with nodes v_i labeled by semantically grounded belief variables, and edges e_{ij} denoting belief in the causal influence from $v_i \rightarrow v_j$. We capture the following metadata for each element:

Node-level: Label, frequency across QAs, semantic role (external_state, internal_affect, behavioral_intention), layer depth (e.g., experience → value → stance).

773

774

789

• **Edge-level:** Confidence (based on question phrasing), polarity (positive or negative), and QA provenance.

Fig. Edge Probability Estimation. Each edge is assigned a probability $P(v_j|v_i)$ based on linguistic indicators in the answer and motif alignment scores:

$$P(v_j|v_i) = \sigma(w_1 \cdot s_{\text{causal}} + w_2 \cdot s_{\text{linguistic}} + w_3 \cdot s_{\text{motif}}) \tag{1}$$

where $s_{\rm causal}$ captures explicit causal phrasing, $s_{\rm linguistic}$ measures structural confidence from the model, and $s_{\rm motif}$ reflects alignment to previously seen cognitive motif patterns. σ is the logistic function.

Demographic Consideration. To support downstream generalization and population modeling (Phase III), each interview is paired with structured demographic data (age, housing status, transportation mode, etc.). These attributes allow later stages to interpolate motif distributions and simulate representative reasoning across diverse population groups.

Stopping Criteria. The system continues alternating between node discovery and causal expansion until one or more termination conditions are met: (1) no new anchor nodes emerge, (2) motif-based reasoning paths reach convergence, or (3) information gain across simulated stances falls below a threshold.

Forward Simulation and Inference. Once an intervention is identified, the causal BN is used to simulate the effects of this intervention. The intervention is applied to the graph as a DO-operation which cuts all incoming edges to the intervened node and updates its distribution. This is followed by a forward simulation to propagate the effects through the network.

Post-processing includes analyzing changes in node probabilities and identifying significant shifts, particularly those related to policy objectives. These results help explain the agent's behavior and evaluate proposed interventions. This structured method empowers stakeholders to make data-driven decisions based on causal dynamics.

F Questionnaire General Design

The questionnaire serves as the foundational layer of HugAgent, designed to capture both baseline beliefs and structured reasoning factors before participants engage in interactive chatbot interviews. The survey was administered through the Prolific platform, ensuring a diverse and demographically balanced pool of respondents. Importantly, not all participants were asked to complete the chatbot phase; instead, all participants began with the questionnaire, and only a subset was later recruited for semi-structured chatbot interviews. This two-stage design allows us to ground conversational transcripts in an already standardized and validated set of structured responses.

The questionnaire is structured into three complementary components. First, participants provide 806 demographic information, including age, gender, education, income, housing status, neighborhood 807 context, and transportation habits. These variables are aligned with U.S. Census and urban planning 808 survey standards, enabling stratified analyses of systematic variability in beliefs across groups 809 (e.g., renters versus homeowners, high-income versus low-income). Second, participants answer 810 stance and intervention items, rating their support on a 1–10 scale and updating their stance under 811 812 hypothetical scenarios (e.g., reduced rent under upzoning, reduced household costs under universal healthcare, reduced crime under surveillance). Third, each topic includes a standardized reason 813 **pool**, a set of common factors such as affordability, fairness, privacy, safety, and neighborhood character. After reporting their stance, participants rate on a 1–5 scale how strongly each reason influences their opinion. This structure provides interpretable ground-truth (GT) data for reasoning dimensions and enables cross-participant comparability, since all individuals evaluate the same set of reasons. By aggregating these structured ratings, we can test whether models not only predict overall support levels but also recover the latent weighting of reasons that drive human decision-making. These structured ratings also serve as a reference for aligning open-ended chatbot responses with quantitative belief factors, creating a consistent bridge between free-text explanations and structured 821 data. 822

Question Types

823

- We define distinct question types to systematically probe both interpretive reasoning (inferring hidden beliefs) and predictive reasoning (anticipating belief change).
- Type 1.1: Stance elicitation (baseline beliefs). Participants report initial support levels on a 1–10 scale (e.g., "How much do you support allowing taller apartment buildings in your neighborhood?").
 This provides the starting point for belief state modeling.
- Type 1.2: Reason evaluation. Participants rate how strongly predefined reasons (e.g., economic benefits, fairness, neighborhood character, privacy, efficiency) influence their stance on a 1–5 scale. The reason pools are shared across all respondents within a topic, allowing structured comparison across individuals and providing ground-truth data on how value dimensions shape beliefs.
- Type 1.3: Contextualized interview beliefs. Through chatbot dialogue, participants explain or justify their stance in natural language. These free-form responses provide latent belief evidence, which models must interpret to infer hidden attitudes. The transcripts can be cross-validated against the structured reason evaluations for consistency.
- Type 2.1: Scenario-based interventions. Participants evaluate counterfactual scenarios (e.g., "If rent prices fall by 15% after upzoning, how would your stance change?"). This probes dynamic updating of beliefs in response to outcomes.
- Type 2.2: Normative fairness interventions. Scenarios manipulate fairness dimensions (e.g., "If upzoning applied equally to wealthy neighborhoods" or "If cameras were controlled by local boards").
 These tasks test whether models capture fairness-based belief shifts.
- Type 2.3: Conditional trade-offs. Participants consider hybrid conditions (e.g., "Universal healthcare exists alongside private insurance" or "Surveillance footage stored for 48 hours only"). These tasks require reasoning under institutional or design constraints.

Task Ty	pe	Upzoning	Surveillance Cameras	Universal Healthcare
Belief ence	Infer-	Q: "On a scale from 1 to 10, how much do you support allowing taller apartment buildings in your neighborhood?" A: "Probably around 3. I worry it changes the character of the area." Target: Low support (3/10); belief: upzoning harms neighborhood character.	Q: "How comfortable do you feel being monitored by public cameras?" A: "Honestly, it makes me uneasy. I don't trust how the footage is used." Target: Low comfort; belief: privacy concerns about surveillance.	Q: "Do you feel your current health insurance provides adequate coverage?" A: "Not really, I often avoid going to specialists due to cost." Target: Insurance inadequate; belief: high costs limit access.
Reaction diction	n Pre-	Scenario: "After the city allows more apartments, rent prices drop 15%. Your monthly rent is noticeably lower." Target: Support increases (e.g., +2 on 1–10 scale).	Scenario: "After installing cameras, neighborhood break-ins fall and robberies drop by 20%." Target: Support increases (stronger acceptance).	Scenario: "After switching to universal healthcare, household out-of-pocket costs fall by \$3,000 annually." Target: Support increases (e.g., from 6/10 to 9/10).

Table 15: Illustrative examples of HugAgent questionnaire and interview tasks. Each domain includes both belief inference and reaction prediction items, enabling evaluation of models on stance attribution and dynamic belief updating.

846 G Zoning Opinion Questionnaire (Human Evaluation)

To rigorously evaluate the fidelity of our generative agents' responses against real human participants, we conducted a structured public opinion survey titled *General Housing & Upzoning Public Opinion Survey*. The survey was carefully designed to facilitate comparison between human-generated responses and those from LLM-based agents, specifically targeting residents of United states.

851 Motivation and Objectives

This survey aimed to assess public opinion on urban upzoning scenarios, capturing nuanced attitudes toward housing policies and their underlying reasoning. Our goal was to determine whether generative agents could reliably replicate human response patterns, especially regarding sensitive issues such as neighborhood change, density increases, and emotional responses like YIMBY (Yes In My Backyard) and NIMBY (Not In My Backyard).

857 Survey Structure and Methodology

858 The survey comprised two primary sections:

Section 1: Demographic and Background Information Participants provided detailed demographic data aligned with U.S. Census Bureau categories:

- 861 Age
- Housing status (owner or renter)
- Income levels
- Occupation
- Marital status
- Presence of children
- Transportation mode
- Monthly rent as a percentage of income
- Residential mobility
- ZIP code or proximity-based location verification

- To ensure data quality, participants were required to explicitly answer an attention check question.
- 872 Section 2: Scenario-Based Opinion Measurement Participants were first asked general zoning
- questions and rated their support for allowing larger, taller apartment buildings in their neighborhood
- on a 1–10 Likert scale (1 = strongly oppose, 10 = strongly support). Each scenario was accompanied
- by a set of related factors, which participants evaluated on a 1-5 scale (1 = no impact, 5 = very large
- impact), regardless of whether the impact was positive or negative. The factors included:
- Housing supply and availability
- Affordability for low- and middle-income residents
- Neighborhood character and visual compatibility
- Traffic and parking availability
- Walkability and access to amenities
- Noise, congestion, or infrastructure strain
- Fairness and distribution of development
- Economic vitality for local businesses
- Building height/scale relative to surroundings
- Property values or homeownership concerns
- 887 Clarifying examples were provided to ensure consistent interpretation of impact ratings.

888 Data Collection and Implementation

- 889 The survey was implemented using Google Forms and distributed via the Prolific platform, with
- compensation set at \$12/hour. Participants were guided through the survey flow with embedded
- instructions and examples to ensure comprehension and engagement.

892 Transparency

- All survey items, design rationales, and filtering criteria are publicly documented to support repro-
- ducibility and public trust. This enables rigorous evaluation of generative agents' ability to simulate
- human attitudes under complex, emotionally and politically sensitive policy conditions.

896 H Universal Healthcare Ouestionnaire

897 Motivation and Objective

- 898 This survey was designed to evaluate whether a structured reasoning system—based on Bayesian
- networks extracted from interviews and conditioned large language models (LLMs)—can simulate or
- 900 recover human judgments on complex policy issues. In this case, we focus on universal healthcare, a
- topic involving tradeoffs across fairness, cost, autonomy, and trust.
- 902 Rather than simply measuring stance, the survey was constructed to expose the participant's reasoning
- pathway, enabling fidelity evaluation at both outcome and process levels.

904 Survey Structure and Methodology

- The survey design draws on the four-stage cognitive model of survey response [55]:
- **Comprehension**: Questions were phrased clearly and definitions were provided (e.g., what universal healthcare entails).
- **Retrieval**: Participants were asked to recall relevant experiences (e.g., delays in care, interactions with public systems).
- **Judgment**: Participants evaluated tradeoffs and reflected on personal values.
- **Response**: Structured Likert scales captured quantified opinions.

912 Survey Components

- 913 The survey includes:
- **Stance Rating**: Support for universal healthcare on a 1–10 scale.
- Personal Experience: Items capturing healthcare access and insurance adequacy.
- **Baseline Reason Evaluation**: Participants rated 13 carefully constructed reasons (e.g., fairness, efficiency, innovation) for their general influence on stance.

918 Counterfactual Scenarios

- To probe reasoning dynamics and test the model's sensitivity to causal perturbations, four counterfac-
- 920 tual scenarios were introduced, each followed by a stance re-rating and a focused subset of reasons.
- 921 Scenarios included:
- 922 1. National cost reduction with increased wait times.
- 923 2. Household savings of \$3,000 annually.
- 3. Retention of private insurance alongside a public system.
- 925 4. Coverage limited to essential services.
- 926 Participants re-evaluated selected reasons in the context of each scenario (e.g., "I worry about tax
- 927 increases" or "Universal healthcare might reduce personal choice in care") on a 1-5 scale, allowing
- 928 analysis of belief shifts.

929 Reason Design

- 930 Reasons were drawn from qualitative policy discourse and refined to:
- Reflect distinct value dimensions (e.g., equality, responsibility, institutional trust).
- Avoid biasing language (neutral framing, no moral triggers).
- Enable both positive and negative stance justifications across political orientations.
- Each reason was independently interpretable and mapped to latent causal factors in the underlying
- Bayesian model. Subsets of reasons were assigned to each counterfactual scenario to ensure relevance
- 936 while reducing redundancy.

937 I Surveillance Camera Questionnaire

938 Motivation and Objective

- 939 This survey is designed to evaluate the reasoning fidelity of structured models such as Bayesian
- Networks (BNs) when paired with large language models (LLMs). Specifically, it tests whether a
- 941 BN+LLM system can simulate human responses to policy questions about public surveillance more
- 942 faithfully than a baseline persona-based LLM. To do this, we use controlled question design inspired
- by cognitive science and causal reasoning frameworks.

944 Survey Structure and Methodology

- The survey design draws on the four-stage cognitive model of survey response [55]:
- 946 1. **Comprehension**: Understand the question and context.
- 947 2. **Retrieval**: Recall relevant experiences and beliefs.
- 948 3. **Judgment**: Synthesize and evaluate relevant considerations.
- 949 4. **Response**: Map judgment to a scale-based response.
- This model guides both our baseline attitude elicitation and our counterfactual design. The survey consists of:
- 952 Section 1: Baseline Stance and Experience Participants rate their general support for public
- 953 surveillance (1–10), followed by personal experiences such as feelings of safety, comfort, and negative
- 954 interactions with surveillance technology.
- 955 Section 2: General Reason Evaluation Participants evaluate the importance of twelve potential
- reasons (1–5 Likert scale) influencing their baseline stance, including factors like privacy, crime
- prevention, power misuse, and behavioral impacts.
- Section 3: Counterfactual Scenarios and Dynamic Reasoning Participants are then presented
- 959 with three hypothetical surveillance policy changes:
- Crime Reduction vs. False Arrest Tradeoff
- Limited Data Retention (48h)
- Community-Controlled Surveillance
- 963 For each scenario:
- Participants rate how the new information affects their stance (1–10 scale).
- Then, they re-evaluate a scenario-specific subset of 3–5 reasons (1–5 scale) that are most relevant under the new condition.
- 967 This design allows us to evaluate whether the model (and human) responses adjust not only the final
- stance, but also the internal reasoning paths—a critical distinction for validating structural cognitive
- 969 models.

970 **Design Highlights**

- Cognitive fidelity: Question wording avoids surface cues and forces reasoning across multiple values (e.g., privacy vs. safety, trust vs. control).
- Counterfactual sensitivity: Each scenario targets a specific edge in the causal BN, enabling us to observe how reason weights shift under perturbation.
- **Explanation delta**: By comparing reason weights before and after each scenario, we quantify whether the model exhibits structural adaptation or static stance mimicry.

977 Data Collection and Implementation

- The survey was implemented using Google Forms and distributed via the Prolific platform, with
- ompensation set at \$12/hour. Participants were guided through the survey flow with embedded
- instructions and examples to ensure comprehension and engagement.

Transparency

- All survey items, design rationales, and filtering criteria are publicly documented to support reproducibility and public trust. This enables rigorous evaluation of generative agents' ability to simulate human attitudes under complex, emotionally and politically sensitive policy conditions.

J Prompt

J.1 Task formatting prompt 986

System Prompt

zoning: "You are an expert at analyzing conversations about urban policy to extract causal

surveillance": "You are an expert at analyzing conversations about surveillance and public safety to extract causal beliefs.

healthcare": "You are an expert at analyzing conversations about healthcare policy to extract causal beliefs.

987

User Prompt

Based on the following conversation about {conversation_topic}, identify ALL questionanswer pairs that reveal the person's beliefs about causal relationships between different

Conversation: {context_text} Your task: 1. Find ALL Q&A pairs that show how the person believes one factor affects another (up to 10 pairs) 2. For each pair, create a direct question asking about the influence level using everyday language 3. Based on the person's answer, determine their belief about the effect.

Selection rule: - PRIORITIZE items with dependency level >= 1 (needs-context). If fewer than 10 such items exist, then fill the remainder with the best dependency level = 0 items. Prefer diverse factor pairs; avoid near-duplicates.

Return JSON format as an array.

{answer_options_text}

Use simple, everyday language for the factors. Examples by topic:

Zoning: "building more housing" instead of "upzoning policies", "traffic congestion", "neighborhood character".

Surveillance: "installing cameras" instead of "surveillance systems", "crime rates", "privacy concerns".

Healthcare: "universal coverage" instead of "healthcare policy", "wait times", "healthcare costs".

Return up to 10 belief inference questions maximum.

988 989

J.2 Evaluation prompt

System Prompt

You are an expert psychologist specializing in Theory of Mind and belief inference.

Your task: analyze conversation transcripts to infer what the participant believes about causal relationships. Focus on understanding their mental model - what they think causes what, not what is objectively true.

Consider their background, conversation patterns, and implicit beliefs expressed through their responses. Base your inference strictly on evidence from their statements, not general assumptions.

990

User Prompt

{Context QA + Demographic information}

Based on the evidence above (including Conversation History and Person's Background), respond with ONLY the single letter (options_str) that best represents this person's belief.)

991

K Extended Design Principles

Open-ended reasoning as principle Our benchmark targets *reasoning as a dynamic and individualized process*, rather than static prediction. We therefore adopt an **open-ended elicitation principle**: instead of pre-defining fixed question banks, HugAgent uses a single *guiding question* to initiate a semi-structured conversation. All follow-up questions are generated adaptively within the same dialogue, grounded in the participant's own responses. This design enables *deep*, *conversational reasoning* to unfold while minimizing artificial scaffolding from the chatbot itself. We do not claim fully open-world coverage; rather, we emphasize *open-domain extensibility*: by simply swapping the guiding question, the benchmark can be ported to new domains while maintaining consistency in evaluation. Such minimal-interaction protocols align with prior work showing that lightweight conversational scaffolds preserve ecological validity in human reasoning studies [56, 57, 12, 58]. **This principle directly motivates the guiding-question chatbot protocol we describe in Appendix D.**

Proxy tasks of reasoning To evaluate whether models capture not only what individuals believe but also how their beliefs evolve, we operationalize reasoning through two proxy tasks: *belief state inference* (recovering stance and factor polarity from context) and *belief dynamics update* (predicting stance shifts and reweighting under new evidence). These tasks follow the tradition of modeling belief revision as a tractable proxy for underlying cognitive processes [59, 60]. While other proxies could be envisioned, these two are the most direct operationalizations of *individual reasoning trajectories*, balancing interpretability and task difficulty. **This motivates our benchmark's two-task structure, detailed in Appendix D.**

Dual-track design: human and synthetic agents Human data provide ecological validity: rich, idiosyncratic reasoning paths embedded in natural language. Synthetic agents, by contrast, provide controllability and scale: fully specified stance profiles and deterministic update rules allow stress-testing model adaptation under known ground truth. Together, the two tracks are complementary: humans as ecological baselines, synthetics as controlled stress tests. This mirrors dual-track designs in cognitive science and simulation benchmarks, where naturalistic and synthetic data jointly enhance validity and reproducibility [49, 61]. Synthetic agents are not intended to replace human data but to serve as a complementary axis of evaluation. **This dual-track design is what anchors HugAgent between ecological realism and controlled generalization tests.**

Extended Rationale: Synthetic Stage Justification Synthetic data in HugAgent follows the same legitimacy principles as established ToM and social reasoning benchmarks. Rather than letting LLMs freely invent beliefs, we first define a formal structure—a causal belief graph specifying nodes (beliefs), edges (causal relations), and interventions (external stimuli). Synthetic agents then evolve along this graph to generate new belief states and reasoning trajectories. The graph itself provides the ground truth for evaluation (e.g., stance updates, trajectory alignment), while LLMs merely render these states into natural language explanations. This ensures that labels are independently controlled and falsifiable, avoiding the risk of self-validation. As in prior benchmarks, sampled human verification is performed for quality assurance.

Upper bound via test–retest reliability A natural question is whether human annotators could serve as the benchmark baseline. While this is common in many benchmarks, HugAgent tasks present unique challenges: they involve *long*, *naturalistic transcripts* and fine-grained belief trajectories. In principle, annotators could be asked to re-read transcripts and label stance updates, but such procedures are slow, error-prone, and risk conflating annotators' own heuristics with the original participant's reasoning. This creates a fidelity–feasibility tradeoff: while feasible, the outcome would be a proxy of *third-party interpretation*, rather than a faithful measure of the individual's reasoning process.

Instead, we adopt *test–retest reliability* as the human ceiling. Here, the same participant is re-sampled or re-interviewed, and the consistency of their own responses provides a direct measure of reliability. This practice is well established in psychology and survey research, and has been adopted in recent large-scale reasoning datasets facing similar challenges [30, 9]. Compared to annotator baselines, test–retest reliability offers a more precise and ecologically valid upper bound for model performance, aligned with the benchmark's goal of capturing intra-individual reasoning fidelity. **This principle defines how we report the human ceiling in HugAgent.**

Data Full Example L

User's Demographic:

Attribute	Example (Anonymized Participant)
Housing Experience	Has lived in the same residence for several years
Age	30
Moved Last Year	Same house 1 year ago
Housing Status	Owner-occupied
Transportation	Car / Truck / Van
Household Income	\$75,000–\$99,999
Occupation	Sales and office occupations
Marital Status	Not married
Children	Has children
Neighborhood Safety	Very safe. I rarely worry about crime
Health Insurance	Private insurance, no disability
Education	High school graduate or equivalent
Citizenship	Native-born U.S. citizen
Financial Situation	Gets by, but money is tight

Table 16: Example anonymized participant profile used in analysis (for illustration only). Personally identifiable details have been generalized or omitted.

Interview QA

1047

1048

1054 1055

1056 1057

1060

1061

1062

1063

1064

1068

1069

1070

1071

1072

1073

1074

1075

1078

1079

1081

Note: The following excerpt reflects a simulated or anonymized participant's responses. It may 1049 contain biased or stereotypical opinions that do not represent the authors' or dataset creators' views. 1050 It is included purely for analysis of belief attribution and reasoning behavior. 1051

- 1. Q: To what extent do you support or oppose upzoning policies that allow for higher density 1052 housing in traditionally single-family neighborhoods? Please explain your reasoning. 1053
 - A: I don't support it at all. I'm worried that it'll cause overcrowding if cheaper apartments or housing were made. Aside from that, we know that statistically, lower income people tend to have more of the criminal population in them, isn't that right? So this might cause the crime rates to go
- 2. Q: What do you think are the most significant impacts, positive or negative, of increasing housing 1058 density in residential neighborhoods? 1059
 - A: I've mentioned the potential for crime rates to go up, that's the real worry here. Lots of new lower income people, lots of potential criminals.
 - 3. **Q:** How do you think upzoning policies might affect housing affordability in urban areas?
 - A: They'd most likely lower the price of rent because of "competition". But at what cost? The safety of the people!
- 4. Q: What impact do you believe increased housing density might have on neighborhood character 1065 and quality of life? 1066 1067
 - A: Safety for sure. Low income places simply have more potential for crimes due to people being tempted to commit criminal acts for survival.
 - 5. Q: How do you think upzoning might affect transportation systems and traffic congestion in cities? A: It's going to worsen! Look, there was a time when I used to take the bus to get to work every day when I still didn't have a car. I live in a big city and sometimes, the bus couldn't take all of us! That caused me to get late a couple of times since there wasn't even any standing room. So imagine, a rush of new low income people to this area, probably they don't have cars so they'll rely on buses, it'll just be extra strain on the buses and not everyone would be able to get on the bus at all.
- Q: What role do you believe local government should play in regulating housing development 1076 and density? 1077
 - A: The government really shouldn't be too involved with many things. Just minimally involved. Less government involvement, the better.
- **Q:** How might environmental concerns factor into decisions about urban density and zoning? 1080 A: I don't personally care about these so-called "environmental concerns". I'm not some kind of 1082 environmental activist or terrified climate change believer. As long as something doesn't dump toxic waste or all sorts of hazardous material in my area, then it's good. 1083

- 8. **Q:** What economic effects, both positive and negative, might result from changing zoning laws to allow more multi-family housing?
- A: More new people, more potential customers for businesses in the area obviously. BUT we also have to think that these are low income people if we're talking about low income housing. So businesses targeting low income people would most likely benefit, but the more upscale ones wouldn't.
- 9. **Q:** How do you think the interests of current residents versus future residents should be balanced when making zoning decisions?
- A: The current residents should ALWAYS be prioritized, they were there first. New people should always be considerate of the people living wherever they're planning to move to. It's just basic human decency.
- 10. **Q:** What role do you think social equity and access to opportunity play in discussions about zoning and housing policy?
- A: I am totally against EQUITY. Equity means taking opportunities away from someone in order to give it to somebody else who probably didn't earn it. I don't like the idea of redistributing what a successful person has.
- 110 11. **Q:** How confident are you that changes in Higher density housing lead to changes in Support for Upzoning? Does it have a positive effect (increasing it) or a negative effect (decreasing it)? How strong is this effect?
- A: It's going to be NEGATIVE. If we're talking about people, it's not just quantity that we're supposed to worry about, but also the quality. So we can say "Don't judge a book by their cover", but we also must think that people are in the situation they are for a reason. So if we're going to get flooded by low income people, we have to ask, "Why are they low income?" Of course not all low income people are bad, but majority of criminals are low income people.
- 1108 12. **Q:** What factors do you think influence Support for Upzoning, and how strong is their impact? Please also indicate if these influences are positive (increasing) or negative (decreasing).
- A: Definitely the idea of SAFETY is a huge factor. Just imagine you live in a peaceful neighbor-hood where crime isn't really a problem, then suddenly a huge number of new low income people flood in to your community and suddenly kids start getting bullied at the playground, people start getting mugged left and right. Safety is really a big concern!
- 1114 13. **Q:** Does Crime rates have a positive or negative effect on Support for Upzoning, and how signifi-1115 cant is this effect? Does it have a positive effect (increasing it) or a negative effect (decreasing it)? 1116 How strong is this effect?
- A: That's what I've been talking about this entire conversation, the potential for CRIME! As I've already stated numerous times, it's a MAJOR concern and an influx of low income people would definitely affect the crime rate!
- 14. **Q:** Would small changes in Housing affordability lead to noticeable changes in Support for Upzoning, or would it take larger shifts? Does it have a positive effect (increasing it) or a negative effect (decreasing it)? How strong is this effect?
- A: At first people would probably think things will be better because rent might go down a bit, BUT that's not guaranteed. Second, SAFETY is really something that people are probably not willing to compromise.
- 1126 15. **Q:** Would small changes in Safety lead to noticeable changes in Support for Upzoning, or would it take larger shifts? Does it have a positive effect (increasing it) or a negative effect (decreasing it)? How strong is this effect?
- A: If there's really no way about avoiding the creation of some kind of tall low income apartment building for the sake of "equity", then the next best thing would be to thoroughly do background checks on all the renters. For example, there should be strictly nobody in there with a criminal record.
- 1133 16. **Q:** How would you describe the relationship between Low Income People and Support for Upzoning? Is it a strong or weak connection? Does it have a positive effect (increasing it) or a negative effect (decreasing it)? How strong is this effect?
- A: Well of course low income people would support the creation of low income rental building.

 But the problem is that people already living in the community, like me, wouldn't support it at all for fears of safety worsening.
- 1139 17. **Q:** Is the effect of Minimal Regulation on Support for Upzoning immediate, or does it take time to develop? Does it have a positive effect (increasing it) or a negative effect (decreasing it)? How strong is this effect?
- A: Any policy takes TIME to develop. Rushed policies just end up in disaster because it won't be well thought out.

- 1144 18. **Q:** Would small changes in Impact on businesses lead to noticeable changes in Support for Upzoning, or would it take larger shifts? Does it have a positive effect (increasing it) or a negative effect (decreasing it)? How strong is this effect?
- A: No. As I've said, low income people will only provide benefit to businesses targeting low income customers. Mid to upscale businesses wouldn't benefit from them because they won't be able to afford their products and services. In short, not all businesses would be in support of having some kind of low income housing in the area if all they're going to be able to afford are low income stuff.
- 1152 **Q:** How would you describe the relationship between Basic human decency and Support for Upzoning? Is it a strong or weak connection? Does it have a positive effect (increasing it) or a negative effect (decreasing it)? How strong is this effect?
- A: There are people who make decisions based on feelings alone. Yes, they'll think it's "decent" to allow low income people to have low income housing in their community, BUT often, these people don't think about the consequences that would affect the people already living in the community. They are too focused on helping others that they don't realize they are causing harm to themselves.
- 1160 20. **Q:** Is the effect of Redistribution on Support for Upzoning immediate, or does it take time to develop? Does it have a positive effect (increasing it) or a negative effect (decreasing it)? How strong is this effect?
- A: That's definitely going to be a huge NEGATIVE right away. Nobody in their right mind would want themselves to be compromised for others. So let's think about what happens if in a moderately wealthy area, they allowed low income housing in the name of "equity". For actual home owners (not renters), the value of their properties would go down. These are properties that they've worked for years to maintain, and suddenly, in the name of "equity", is it alright to allow the values to go down? No of course not! So we have to always think about how low income housing would affect the people already living in the community.
- 1170 21. **Q:** Would small changes in Negative Effect lead to noticeable changes in Support for Upzoning, or would it take larger shifts? Does it have a positive effect (increasing it) or a negative effect (decreasing it)? How strong is this effect?
- A: No, it's called "Negative Effect" because it affects people in a bad way. Nobody would support anything like that knowingly.
- 1175 22. **Q:** What factors affect Upzoning policies, and which ones have the strongest influence? Please also indicate if these influences are positive (increasing) or negative (decreasing).
- A: As I've been saying this entire conversation, the major facor that affects people's support for low income housing is the SAFETY, the potential for crime rates to go up, and these things will definitely always affect support for low income housing negatively.
- 1180 23. **Q:** Does Community Resistance to Upzoning have a positive or negative effect on Support for Upzoning, and how significant is this effect? Does it have a positive effect (increasing it) or a negative effect (decreasing it)? How strong is this effect?
- A: Of course community resistance won't support low income housing, that's the point. People would resist these places from being built in order to protect the community from potential safety concerns.
- 1186 24. **Q:** How would you describe the relationship between Time for policy development and Support for Upzoning? Is it a strong or weak connection? Does it have a positive effect (increasing it) or a negative effect (decreasing it)? How strong is this effect?
- A: Of course "Time" will always have something to do with whether low income housing would be allowed or not. For example, maybe a politician would take his time forming some kind of bill concerning low income housing and he'll wait for enough public support before officially launching it in order to increase its chances of succeeding.
- 1193 25. **Q:** Would small changes in Low Income Housing lead to noticeable changes in Support for Upzoning, or would it take larger shifts? Does it have a positive effect (increasing it) or a negative effect (decreasing it)? How strong is this effect?
- A: No, even small changes in low income housing won't change people's support for it because it will negatively affect the community. People already know it's most likely going to be the cause of many safety concerns aside from property devaluation.
- 1199 26. **Q:** Does Equity have a positive or negative effect on Support for Upzoning, and how significant is this effect? Does it have a positive effect (increasing it) or a negative effect (decreasing it)? How strong is this effect?
- A: Equity has NEGATIVE effects on people already living in the community, because the point of equity is to take from those people (land space) and to redistribute it to other people (the low

- income people). People might try to frame it as "helping the poor", but you can help poor people in other ways without harming the community.
- 1206 27. **Q:** How would you describe the relationship between Support for low income housing and Support for Upzoning? Is it a strong or weak connection? Does it have a positive effect (increasing it) or a negative effect (decreasing it)? How strong is this effect?
- A: People are directly against low income housing because it's more likely to bring bad stuff with it that good ones. The consequences outweigh the positives.

1211 Sample Survey: Housing / Upzoning

1212 Baseline Stance

1213

1214 1215

1218

1223

122

• Q1. On a scale from 1 to 10, how much do you support or oppose allowing bigger, taller apartment buildings in your neighborhood?

1	2	3	4	5	6	7	8	9	10
Strongly Oppose				Neutral					Strongly Support

1216 Reason Evaluation (Baseline)

1217 Q1r. How much do the following reasons influence your general opinion on upzoning?

Reason Scale (1–5)

Building more homes helps with the housing crisis. (A)
This gives more housing choices for middle- and lowerincome people. (B)
Taller buildings might change the look and feel of the neighborhood. (C)
More traffic and parking is a real concern. (D)
I'm worried about my property value or investment. (I)

1219 Scenario 1: Rent Drop

• Q2. After the city allows more apartments in low-density areas, rent prices drop 10–15%. Your monthly rent is noticeably lower. It's easier to find a decent place. How would this affect your stance?

1	2	3	4	5	6	7	8	9	10
Much Less Supportive				Neutral					Much More Supportive

1224 Reason Evaluation (Scenario 1)

1225 Q2r. To what extent do the following reasons influence your stance?

	Reason	Scale (1–5)
26	Building more homes helps with the housing crisis. (A) More traffic and parking is a real concern. (D) Everyone should help handle the growth. (N) More people means more business for local shops. (O) I'd worry about noise and crowding on my block. (P)	

1227 M Quality-Control Protocol

- We applied a standardized protocol to ensure that only participants with reliable and reproducible data were retained. The following criteria were applied sequentially:
- 1230 1. **Redundant responses**: cases where the participant repeatedly produced near-identical statements without substantive variation.
- 2. **Meta-level questioning**: transcripts dominated by repeated challenges to the validity of the task itself rather than substantive reasoning about the topic.
- 1234 3. **Insufficient length**: responses falling below a minimum threshold of tokens or turns, preventing meaningful inference of reasoning structure.
- 4. **Sparse causal belief networks**: chatbot elicitation yielding fewer than five unique nodes, limiting the interpretability of downstream causal graph construction.
- This filtering ensured that the retained dataset reflects consistent engagement with the task, while minimizing artifacts that could compromise the validity of subsequent analyses.

Synthetic Agent Construction (Algorithmic) 1240

Problem Setting and Notation 1241

- We population construct a synthetic agent \mathcal{A} for topics 1242
- {ZONING, HEALTHCARE, SURVEILLANCE}. Each agent $a \in \mathcal{A}$ for topic $t \in \mathcal{T}$ has (i) a 1243
- Causal Belief Network (CBN) G = (V, E), (ii) a demographic profile d, (iii) an initial belief 1244
- state $b_0=(s_0,\mathbf{w}_0)$ with stance $s_0\in\{1,\ldots,10\}$ and reason weights $\mathbf{w}_0\in\Delta^{K-1}$, and (iv) a deterministic update operator U that maps $(b_t,e)\mapsto b_{t+1}$ given an intervention e. 1245
- 1246
- Topic-level statistics. From human CBN corpora we estimate topic-specific sufficient statistics 1247
- $\Theta_t = \{\mu_n, \sigma_n, \mu_e, \sigma_e, \alpha_{\text{imp}}, \beta_{\text{imp}}, \alpha_{\text{conf}}, \beta_{\text{conf}}, \mathcal{V}\}$: node/edge count moments (μ_n, σ_n) and (μ_e, σ_e) , Beta parameters for node importance and edge confidence, and a topic vocabulary \mathcal{V} for label 1248
- 1249
- generation. A content hash over source JSON files ensures cache validity. 1250

N.2 CBN Sampling Model 1251

- **Graph size.** We draw $|V| \sim$ TruncNorm $(\mu_n, \sigma_n, [n_{\min}, n_{\max}])$ and |E|1252
- $\min\{\text{LogNormal}(\mu'_e, \sigma'_e), |V|(|V|-1)/2\}$ with log-space moments chosen to match (μ_e, σ_e) . 1253
- **Node attributes.** For each $v \in V$: 1254

importance
$$(v) \sim \text{Beta}(\alpha_{\text{imp}}, \beta_{\text{imp}}), \text{ evidence}(v) \sim \text{Poisson}(\lambda_t).$$

- Text label $\ell(v)$ is generated by sampling $m \in \{2, 3, 4\}$ tokens from \mathcal{V} (frequency-weighted) and 1255
- filling a topic template. 1256
- **Edge attributes and topology.** We form a hub-spoke backbone plus random residual edges. 1257
- For each selected hub h (top-q by importance), connect $h \to u$ for $u \in V \setminus \{h\}$ with probability 1258
- proportional to $0.7 \cdot \text{importance}(u) + 0.3 \text{ until a target degree.}$ Each edge $e = (u \rightarrow v)$ gets: 1259

$$\operatorname{conf}(e) \sim \operatorname{Beta}(\alpha_{\operatorname{conf}}, \beta_{\operatorname{conf}}), \quad \operatorname{sign}(e) \in \{-1, 0, +1\} \text{ with } p_+, p_0, p_-, \quad \operatorname{weight}(e) \sim \operatorname{Beta}(\alpha_w, \beta_w).$$

- We then add random non-duplicate edges until |E| is reached. 1260
- **Stance node selection.** Let deg(v) be (undirected) degree. Define score $\sigma(v) = 0.7$. 1261
- importance $(v) + 0.3 \cdot \deg(v) / \max_u \deg(u)$. Sample stance node v^* from top-3 nodes according to 1262
- $\sigma(v)$ (softmax). Ensure weak connectivity from v^* to all nodes (add minimal edges if needed). 1263

N.3 Deterministic Update Operator 1264

- Let reasons be a fixed topic-specific set $\{r_1, \dots, r_K\}$ aligned to V. Given intervention e encoded as 1265
- factor deltas $\Delta \mathbf{f} \in \mathbb{R}^{|V|}$, we update stance and reason weights: 1266

$$s_{t+1} = \operatorname{clip}\left(s_t + \eta_s \sum_{(u \to \operatorname{stance}) \in E} \operatorname{sign}_u w_u \, \Delta f_u, \, 1, \, 10\right),\tag{2}$$

$$\mathbf{w}_{t+1} = \text{Normalize}(\mathbf{w}_t + \eta_w \,\mathbf{M} \,\Delta \mathbf{f}), \quad \mathbf{M}_{k,u} = g(r_k, u),$$
 (3)

- where w_u is the edge weight into stance, η_s, η_w are step sizes, and $g(\cdot, \cdot)$ aligns reasons to graph 1267
- nodes (one-hot or soft map). This yields reproducible ground truth for stance shifts and reweighting. 1268

N.4 Demographic Generator and Coupling 1269

- We sample a demographic profile d with correlated marginals: age bands, gender, education, income, 1270
- housing status, employment, location, children, and rent-burden. Simple rules induce a small stance 1271
- prior $\delta(d)$ (e.g., renter $\Rightarrow +\delta$ on pro-development; older age $\Rightarrow -\delta$ on rapid change). We set
- $s_0 \leftarrow \text{clip}(s_0 + \delta(d), 1, 10).$

1274

N.5 Natural Language Realization

- A realization module renders (G, e, b_t, b_{t+1}) to text: (i) paraphrase e with templates; (ii) describe 1275
- reasons using top-m nodes connected to v^* by high-confidence edges; (iii) optionally ask/answer
- interview-style QAs. LLMs are used strictly as a renderer; labels remain from the scripted dynamics
- in §N.3 to avoid circularity.

Algorithm 1: GenerateAgent $(t, \Theta_t, \text{seeds})$

```
Input: topic t, stats \Theta_t, RNG seeds
Output: agent (G, d, b_0, \{(e_j, b_j)\}_{j=1}^m, text)

1 Sample |V|, |E|; create V with importance, evidence, label from \mathcal{V};

2 Build E via hubs + random; assign conf, sign, weight;

3 Select stance node v^*; ensure connectivity;

4 Sample demographics d; set b_0 = (s_0, \mathbf{w}_0) and apply prior \delta(d);

5 for j = 1 to m do

6 Sample intervention e_j (topic-specific deltas \Delta \mathbf{f});

7 b_j \leftarrow U(b_{j-1}, e_j) using Eqns. (1)–(2);

8 Realize (e_j, b_{j-1}, b_j) to text; append to transcript;

9 return packaged JSON: graph G, demographics d, \{(e_j, b_{j-1}, b_j)\}, transcript;
```

1279 N.6 End-to-End Generation

1280 N.7 Complexity and Scaling

Graph sampling is O(|V| + |E|); hub wiring adds $O(|V| \log |V|)$ for sorting. Per-agent conversation of m turns is O(m) render calls. The pipeline trivially parallelizes across agents and topics.

1283 N.8 Quality Control and Determinism

Graph validity: degree bounds, stance reachability, parameter ranges. Topic relevance: label vocabulary coverage threshold. **Determinism:** all stochastic steps are seeded; topic stats are cached with file hashes. **Leakage control:** interventions and post-update labels never appear in the dialogue context used for model evaluation.

1288 N.9 Release Schema

1289 Records are released as JSON:

- belief_graph: nodes with label, importance; edges with source, target, sign, weight, confidence; stance node id.
- demographic: age, gender, education, income, housing, employment, location, children, burden.
- state_before/state_after: stance (1-10), reason weights (1-5 or normalized).
- intervention: structured deltas and a natural-language paraphrase.
- transcript: ordered QA pairs (renderer output).

1296 N.10 Human-Synthetic Similarity

To assess whether synthetic agents provide a faithful approximation of human reasoning structures, 1297 we compare structural statistics of belief graphs across the two tracks. As shown in Figure 6, the 1298 distributions of key properties—including graph size (nodes, edges), sparsity (edge density, average 1299 degree), and semantic alignment (importance, confidence, anchor-node ratio)—exhibit strong overlap 1300 between real and synthetic agents. Notably, synthetic graphs reproduce the long-tailed variation 1301 in node and edge counts observed in human data, while maintaining comparable distributions of 1302 stance-related weights. This alignment suggests that the synthetic track can serve as a scalable proxy 1303 for human reasoning traces, capturing core structural regularities even as it abstracts away from 1304 1305 individual variability.

N.11 Limitations

1306

Synthetic agents offer coverage and ablation control but abstract from human variability (noise, inconsistency, framing sensitivity). Thus, results on this track are *stress tests* and should be interpreted alongside the human-grounded track, which provides the ecological ceiling.




Figure 6: Distributional comparison of structural statistics between human-grounded (blue) and synthetic (red) belief graphs. Synthetic graphs replicate key patterns such as node/edge counts, confidence levels, and anchor-node ratios, supporting their use as controlled stress-test agents.

O Benchmark Task Structure

To clarify how HugAgent maps input materials to evaluation tasks, we provide here a consolidated overview of the benchmark structure. As shown in Figure 7, raw inputs include (i) demographic profiles, (ii) structured questionnaires, and (iii) open-ended chatbot transcripts. These inputs are transformed into two core task families:

- Task 1: Belief State Inference. Given a participant's responses and contextual cues, models must infer the person's stance and factor-level attribution. Example questions include: "Does the respondent view low-income housing as a positive or negative effect on property values?"
- Task 2: Belief Dynamics Update. After an intervention (e.g., rent decrease, policy change, technological improvement), models must predict both the stance shift (1–10 scale) and the reweighting of reasons (1–5 scale). Example questions include: "How would a 10% reduction in rents affect the respondent's stance on upzoning?"

Each topic domain—zoning, healthcare, and surveillance—is instantiated with multiple scenarios and corresponding reason mappings. This ensures comparability across domains while preserving topic-specific ecological validity.




Figure 7: Overview of the HugAgent benchmark structure. Inputs (demographics, questionnaires, and transcripts) are mapped to outputs, including **belief state inference** (Task 1) and **belief dynamics update** (Task 2).

P User Journey and Use Cases of TRACE-YOUR-THINKING (A Semi-structured Chatbot Eliciting Human Reasoning)

This appendix provides a detailed user guide and representative use cases for TRACE-YOUR-THINKING, our semi-structured chatbot system designed to elicit human reasoning at scale. We describe both participant-facing (user) and researcher-facing (admin) views, followed by system outputs and illustrative use cases. We use open science practices as an example here. Our design emphasizes three goals: (i) lowering barriers for participants, (ii) giving researchers flexible and reliable control, and (iii) producing structured outputs that make reasoning analyzable at scale.

1333 Participant Journey (User View)

Participants experience a streamlined workflow that reduces friction while maximizing the richness of collected reasoning.

Step 1: Consent and ID submission. Recruitment begins on the Prolific platform, where participants are shown eligibility criteria and compensation details. Upon accepting the study, they are redirected to a Google Form where they confirm basic requirements (age \geq 18, residence within a specified region, consent for anonymous data usage). Entering their Prolific ID links the responses to the recruitment system, enabling follow-ups without storing personal identifiers, as is shown in Figure 8.




Figure 8: Participant view of the onboarding and interview flow (Consent)



Figure 9: Participant view of the welcome page

Step 2: Login and onboarding. Participants are then redirected to the TRACE-YOUR-THINKING website. After inputting their Prolific ID, they are guided through a short tutorial. This tutorial introduces input modalities (typed text vs. voice-to-text) and explicitly informs users that all answers can be revised either immediately or retrospectively. A persistent progress bar at the top of the interface communicates task completion, reducing dropout risk by making expectations transparent. This part is shown in Figure 9.

Step 3: Semi-structured interview. The core of the participant journey is the semi-structured interview, which unfolds in a guided yet flexible flow: introduction \rightarrow guiding questions \rightarrow follow-up probes \rightarrow final review. This design balances standardization with open-ended flexibility, allowing for wide variation in content, style, and depth of responses.

wide variation in content, style, and depth of responses.

Participants can choose between typed responses and spoken input, enabling a think-aloud protocol that captures more spontaneous reasoning processes. Figure 10 illustrates the onboarding screen where both input modes are explained, while Figure 11 shows a participant actively using voice input to answer a question. Once the interview begins, participants can monitor their progress via a




Figure 10: Participant view of the onboarding of the chatbot, including audio and text input

persistent progress bar (Figure 12), which reduces fatigue by making task completion transparent.
During processing, the interface will show the processing status while still generating new questions

and allow users to answer (Figure 13).

Participants can not only edit their responses immediately but also review the entire transcript at the end of the interview. As shown in Figures 14 and 15, the system presents an overview of all questions and answers, enabling users to backtrack, refine, and self-correct their reasoning. This mirrors how real-world reasoning often evolves over multiple passes rather than being fixed in a single draft.

Step 4: Submission and compensation. Once satisfied, participants submit their responses. Figures 16 and 17 demonstrate the submission stage, where participants re-enter their Prolific ID to confirm completion and finalize their session. The system redirects them back to Prolific, which automatically verifies completion and issues compensation. This tight integration ensures high-quality participation while minimizing administrative overhead.



Figure 11: Participant view of using audio to give the answer

P.1 Researcher Journey (Admin View)

1368

1393

- The system provides a dedicated control panel that makes data collection transparent, configurable, and scalable. Unlike static survey platforms, admins can adapt the study design on the fly and extract structured reasoning outputs.
- Recruitment integration. Admins can publish tasks directly on Prolific, embedding the study link into recruitment posts. Prolific's filters (approval rate, demographics, geography) allow targeted participant pools, while stored Prolific IDs support longitudinal follow-ups. This design enables researchers to re-engage the same individuals across time or across topics, making it uniquely suitable for longitudinal reasoning studies.
- Session management. The Session Management dashboard (Fig. 18) displays all ongoing and completed interviews with metadata including status, progress, and timestamps. From this panel, admins can (i) reorder questions, (ii) export raw QA data, or (iii) export causal graphs for downstream analysis. This unified view makes it easy to monitor study progress at scale and to recover high-fidelity reasoning traces.
- Configurable guiding questions. Admins can design and adjust the interview protocol using a guiding question editor (Fig. 19). Each question has metadata (short text, full text, category), can be toggled on/off, and can be reordered dynamically. This flexibility makes it possible to test multiple hypotheses without rewriting the underlying system. In practice, this feature has been used to swap tutorial vs. research questions and to experiment with different probing strategies, making the platform versatile for diverse research programs.
- Global settings. Admins can set a global interview topic (e.g., policy, healthcare, surveillance) with a single configuration (Fig. 20). This allows open-ended reasoning tasks to be deployed across arbitrary domains, ensuring that the platform is not tied to a fixed task. In effect, the system generalizes beyond a dataset-collection tool to become a reusable infrastructure for eliciting reasoning in any domain.

P.2 Research Outputs (System Features)

- The system is designed to produce outputs that go beyond raw transcripts, giving researchers structured and analyzable data.
- Raw QA transcripts. All participant responses are preserved verbatim (Fig. 21). This ensures that qualitative nuances (hesitations, personal anecdotes, colloquial phrasing) are not lost. At the same time, transcripts provide the raw material for quantitative benchmarking, enabling evaluations of stance classification, belief calibration, and reasoning depth. The ability to capture both structured and noisy responses is a feature, not a limitation: it reflects the diversity of real-world human reasoning.
- **Dynamic causal graphs.** The distinctive feature of TRACE-YOUR-THINKING is the automatic 1401 1402 construction of causal graphs in real time (Fig. 22). As participants answer questions, the system incrementally extracts stance nodes (opinions), belief nodes (anchors), and candidate nodes (sup-1403 porting reasons). The graph expands as reasoning unfolds, producing a structured representation of 1404 how beliefs and justifications interconnect. This design is important for two reasons: (i) it transforms 1405 unstructured reasoning into analyzable graph data, and (ii) it enables researchers to trace belief 1407 updates step by step, rather than relying only on final outcomes. These graphs can be exported for 1408 downstream tasks such as reasoning alignment, structural consistency evaluation, or cross-domain transfer prediction. 1409




Figure 12: Participant view of answering questions and the interview progress

1410 P.3 Use Cases

1412

1413

1414

1415

1416

1417

1411 The flexibility of the system enables multiple research paradigms:

- Baseline data collection: Build large-scale corpora of reasoning traces in a controlled domain (e.g., housing policy), establishing benchmarks for human reasoning diversity.
- Cross-domain transfer: Instantly switch topics (e.g., from zoning to healthcare) by editing global settings, to study how reasoning patterns generalize across domains.
- Longitudinal studies: Re-engage the same participants over weeks or months via Prolific IDs, enabling the study of belief updates and reasoning drift.
- **Human–model benchmarking:** Compare LLM predictions against human causal graphs to quantify intra-agent fidelity, context sensitivity, and adaptation gaps.




Figure 13: Participant view while AI is processing questions, but the participant can still answer the following questions without waiting




Figure 14: Participant view of the overview of the questions and answers. One can edit and go back to any of their answer.




Figure 15: Participant view of the end of the overview of the questions and answers




Figure 16: Participant view of reentering prolific id for submission




Figure 17: Participant view of the end of the test




Figure 18: Admin session management panel with status tracking, progress monitoring, and export functionality. Researchers can monitor studies in real time and batch export reasoning data.




Figure 19: Guiding question editor. Researchers can toggle tutorial vs. research questions, reorder them dynamically, and experiment with alternative protocols. They can also choose to skip some questions by changing the status.




Figure 20: Global interview settings. With one change, the system can adapt to entirely new domains, enabling domain-agnostic deployment.




Figure 21: Sample QA transcripts highlighting variation in response depth and style. The system captures both structured argumentation and spontaneous informal commentary.




Figure 22: Dynamic causal graph visualization. Nodes capture beliefs, stances, and supporting reasons, updated continuously as the participant responds.

1420 **O** Evaluation

Q.1 Evaluation Metrics

Let y_i denote the ground-truth response for instance i, \hat{y}_i the model prediction, and N the total number of instances. For belief dynamics update tasks, let y_i^{prev} denote the participant's pre-intervention score.

Accuracy.

1421

$$Acc = \frac{1}{N} \sum_{i=1}^{N} \mathbf{1} [|\hat{y}_i - y_i| \le \tau],$$

where au is the tolerance band (au=1 for 5-point scales, au=2 for 10-point scales).

Mean Absolute Error (MAE).

MAE =
$$\frac{1}{N} \sum_{i=1}^{N} |\hat{y}_i - y_i|$$
.

Directional Accuracy. We define directional accuracy as a two-stage weighted metric: (1) detecting whether a belief change occurred, and (2) if so, correctly predicting the direction of change (*increase*, decrease, or no change). To better reflect the importance of directional reasoning, a higher weight is assigned to the second stage.

DirAcc =
$$\lambda \cdot \frac{1}{N} \sum_{i=1}^{N} \mathbf{1}[(\Delta y_i = 0 \wedge \Delta \hat{y}_i = 0) \vee (\Delta y_i \neq 0 \wedge \Delta \hat{y}_i \neq 0)]$$

 $+ (1 - \lambda) \cdot \frac{1}{|\mathcal{C}|} \sum_{i \in \mathcal{C}} \mathbf{1}[\operatorname{sgn}(\Delta y_i) = \operatorname{sgn}(\Delta \hat{y}_i)],$ (4)

where $\Delta \hat{y}_i = \hat{y}_i - \hat{y}_i^{\text{prev}}$ and $\Delta y_i = y_i - y_i^{\text{prev}}$ denote predicted and true belief changes, respectively.

C = $\{i \mid \Delta \hat{y}_i \neq 0 \land \Delta y_i \neq 0\}$ is the set of samples where both predicted and true beliefs changed.

We set $\lambda = 0.3$ by default, placing greater emphasis on directional correctness.

This weighting reflects the intuition that correctly inferring the direction of belief change is more informative than merely detecting whether a change occurred. While the first stage (change detection) captures a coarse perceptual judgment that can often be guessed in noisy or stable settings, the second stage(directional correctness)reveals whether the model truly understands and reasons about belief dynamics. Hence, emphasizing the latter better reflects a model's fidelity to human-like reasoning processes and its capacity to simulate belief evolution.

Average-to-Individual (ATI) Score. To provide a single comprehensive measure of model performance across both static and dynamic belief tasks, we define a unified score, *Average-to-Individual* (ATI) score, that integrates the *Belief State Inference* (BSI) and *Belief Dynamics Update* (BDU) components into a normalized value within [0,1]. Specifically, $S_{\rm BSI}$ denotes the normalized accuracy score for static belief state inference, while $S_{\rm BDU}$ aggregates multiple metrics from the belief dynamics update task, including tolerance accuracy, normalized MAE, and directional reasoning accuracy. The unscaled ATI score is computed as:

$$ATI_{unscaled} = \frac{1}{2}S_{BSI} + \frac{1}{2} \left[\frac{1}{2} \left(\frac{1}{2} S_{BDU-mae-norm} + \frac{1}{2} S_{BDU-acc} \right) + \frac{1}{2} S_{Directional-acc} \right]. \tag{5}$$

where each subscore $S \in [0, 1]$ represents a normalized evaluation metric. For MAE-based components, normalization is defined as:

$$S_{\text{BDU-mae-norm}} = \max(0, \min(1, 1 - \frac{\text{MAE}}{\text{MAE}_{\text{max}}})), \tag{6}$$

where MAE_{max} denotes the task-specific upper bound of allowable error. The unified score assigns equal weights to the state component ($S_{\rm BSI}$) and the update component ($S_{\rm BDU}$). Within the update branch, tolerance accuracy and MAE are equally weighted (0.5 each) to ensure a balanced consideration of robustness and precision. The directional reasoning component ($S_{\rm Directional-acc}$) is assigned

an equal weight (0.5) relative to the combined MAE and accuracy branch, reflecting its comparable importance in capturing belief-updating dynamics.

To facilitate interpretation relative to human performance and baseline behavior, we linearly rescale ATI_{unscaled} to a 0–100 scale:

$$ATI = \frac{ATI_{unscaled} - ATI_{random}}{ATI_{human} - ATI_{random}} \times 100, \tag{7}$$

where ATI_{random} and ATI_{human} denote the unscaled ATI scores of the random guess baseline and human upper bound, respectively. Under this rescaling, a score of 0 indicates random-level performance, while 100 represents human-level performance.

1459 Q.2 Computation Details and Track Usage

Unless otherwise specified, all quantitative analyses and unified average to individual (ATI) score computations are performed on the **human track**, which serves as the primary evaluation benchmark due to its ecological validity and authentic reasoning diversity.

The **synthetic track** follows the same survey and interview protocol but is designed for *auxiliary and*extensibility testing. It provides a controlled setting for examining model sensitivity, scaling behavior,
and cross-domain generalization under scripted causal belief networks (CBNs). While the human
track grounds evaluation in real participant reasoning, the synthetic track extends the benchmark
toward scalable stress testing and potential future applications in simulated social environments.

In practice, model predictions for both tasks—belief state inference (BSI) and belief dynamics update (BDU)—are first computed independently. All metrics (accuracy, MAE, and directional accuracy) are averaged across the three domains (healthcare, surveillance, zoning) before aggregation into the unified score defined in Equation 5. Reported results in Section 4 and subsequent findings are therefore based on the human track unless explicitly noted otherwise.

1473 R Use of LLM Usage

- 1474 Large Language Models (LLMs) were used to aid in the writing and polishing of the manuscript.
- 1475 It is important to note that the LLM was not involved in the ideation, research methodology, or
- experimental design. All research concepts, ideas, and analyses were developed and conducted by
- the authors. The contributions of the LLM were solely focused on improving the linguistic quality of
- the paper, with no involvement in the scientific content or data analysis.
- 1479 The authors take full responsibility for the content of the manuscript, including any text generated or
- polished by the LLM. We have ensured that the LLM-generated text adheres to ethical guidelines and
- does not contribute to plagiarism or scientific misconduct.