

JUDGE_{LM}: FINE-TUNED LARGE LANGUAGE MODELS ARE SCALABLE JUDGES

Anonymous authors

Paper under double-blind review

ABSTRACT

Evaluating Large Language Models (LLMs) in open-ended scenarios is challenging because existing benchmarks and metrics can not measure them comprehensively. To address this problem, we propose to fine-tune LLMs as scalable **judges** (Judge_{LM}) to evaluate LLMs efficiently and effectively in open-ended benchmarks. We first propose a comprehensive, large-scale, high-quality dataset containing task seeds, LLMs-generated answers, and GPT-4-generated judgments for fine-tuning high-performance judges, as well as a new benchmark for evaluating the judges. We train Judge_{LM} at different scales from 7B, 13B, to 33B parameters, and conduct a systematic analysis of its capabilities and behaviors. We then analyze the key biases in fine-tuning LLM as a judge and consider them as position bias, knowledge bias, and format bias. To address these issues, Judge_{LM} introduces a bag of techniques including swap augmentation, reference support, and reference drop, which clearly enhance the judge’s performance. Judge_{LM} obtains the state-of-the-art judge performance on both the existing Panda_{LM} benchmark and our proposed new benchmark. Our Judge_{LM} is efficient and the Judge_{LM}-7B only needs 3 minutes to judge 5K samples with 8 A100 GPUs. Judge_{LM} obtains high agreement with the teacher judge, achieving an agreement exceeding 90% that even surpasses human-to-human agreement¹. Judge_{LM} also demonstrates extended capabilities in being judges of the single answer, multimodal models, multiple answers, multi-turn chat, etc.

1 INTRODUCTION

Recent advancements in large language models (LLMs) have fostered significant interest due to their remarkable performance in following instructions and their broad capabilities in dealing with open-ended scenarios. Based on the open-source LLMs, including OPT (Zhang et al., 2022), Flan-T5 (Chung et al., 2022), LLaMA (Touvron et al., 2023a), and Pythia (Biderman et al., 2023), researchers propose numerous methods to align these models with human preferences through instruction fine-tuning. These aligned LLMs demonstrate enhanced abilities in comprehending human instructions and generating more coherent responses. Nonetheless, existing benchmarks (Hendrycks et al., 2020; Liang et al., 2022) and traditional metrics (Lin, 2004; Papineni et al., 2002; Zhang et al., 2019; Sellam et al., 2020; Yuan et al., 2021) do not adequately estimate the capabilities of LLMs in open-ended scenarios. Therefore, a new benchmark method that could evaluate LLMs comprehensively in open-ended tasks is needed.

Concurrent works are making efforts to explore various methods for evaluating the performance of LLM. The arena-format (Zheng et al., 2023) methods leverage crowdsourced platforms to extract anonymous LLM competition results. While evaluations by humans are trustworthy, they are also time-consuming and financially demanding. Some approaches (Chiang et al., 2023) utilize GPT-4 as a judge. Nevertheless, these methods grapple with challenges of potential data exposure and volatile API model transitions, potentially compromising the judge’s reproducibility. Panda_{LM} (Wang et al., 2023) attempts to fine-tune open-source LLMs for evaluating answers. However, limitations stemming from the training data quality, and inherent LLM biases, undermine the effectiveness of such fine-tuned models in the role of a judge.

¹As a reference, the max agreement among humans in MT-bench (Zheng et al., 2023) is 82%.




Figure 1: An overview of our scalable JudgeLM including data generation, fine-tuning, and various functions.

In this paper, we propose to evaluate LLMs through fine-tuned open-source LLMs, which serve as scalable **judges** (JudgeLM) achieving satisfactory agreement with the teacher judge. Our methodology incorporates scalable judges as evaluators in open-ended tasks, coupled with a high-quality dataset conducive to both training and evaluating the judge models. Within our framework, we adapt open-source LLMs to serve as judges and analyze their scaling ability in relation to model size (ranging from 7B to 33B) and volume of training data (extending from 3.5K to 100K). Our curated dataset comprises 105K seed questions, LLM answer pairs, and judgments from the teacher judge, GPT-4, as shown in Fig. 1a. Note that we generated two judgments for each seed task with and without reference answers. This dataset is partitioned, with 100K seed questions allocated for training ($2 \times$ larger than PandaLM) and the remainder for validation ($29 \times$ larger than PandaLM).

Utilizing LLMs as judges inevitably introduces biases such as position bias (favoring answers in specific positions), knowledge bias (over-reliance on pre-trained knowledge), and format bias (optimal performance only under specific prompt formats) as shown in Fig. 8, 10, 12, 13. When fine-tuning is not possible, GPT-4-API-based judge (Zheng et al., 2023) tries to alleviate this by well-designed prompt methods, i.e., Chain-of-thought, few-shot judge, and judging multiple times with different positions. JudgeLM presents a new way that can address these biases in the fine-tuning stage, skipping the complicated prompt methods and multi-turn API calling. Moreover, our JudgeLM system presents extended capabilities as shown in Fig. 1b, including grading single answers, judging multiple answers, judging multimodal models, multi-turn chat, etc.

In contrast to arena-format methods, our approach is rapid and has a low cost. For instance, JudgeLM-7B requires only 8 A100 GPUs and can evaluate 5000 response pairs in just 3 minutes. In comparison to closed-source LLM judges, JudgeLM ensures reproducibility and protects user privacy. When compared to concurrent open-source LLM judges, our system explores both the scaling ability and biases in LLM fine-tuning. Furthermore, JudgeLM dataset stands as the most diverse and high-quality one, significantly benefitting subsequent research in judge model investigations.

Our main contributions can be summarized as follows:

- We introduce a high-quality, large-scale dataset for judge models, enriched with diverse seed tasks, LLMs-generated answers, and detailed judgments from GPT-4, laying the foundation for future LLMs evaluating research.

- We propose JudgeLM, a scalable language model judge, designed for evaluating LLMs in open-ended scenarios. It achieves an agreement exceeding 90% that surpasses the human-to-human agreement. Our JudgeLM can also generalize to many extended tasks.
- We analyze the biases inherent to **LLM judge fine-tuning** and introduce a series of methods to address them. Our methods significantly improve the consistency of the model in different cases, making the JudgeLM more reliable and flexible.

2 RELATED WORK

2.1 INSTRUCTION FINE-TUNING OF LARGE LANGUAGE MODELS

With the development of large language models (LLMs), researchers find that fine-tuning pre-trained LLMs such as GPT-3 (Brown et al., 2020), T5 (Raffel et al., 2020), OPT (Zhang et al., 2022), and PaLM (Chowdhery et al., 2022) enable LLMs to follow human instructions and help with open-ended tasks. The instruction fine-tuned LLMs such as InstructGPT (Ouyang et al., 2022), ChatGPT (OpenAI, 2022), FLAN-T5 (Chung et al., 2022), FLAN-PaLM (Chung et al., 2022), OPT-IML (Iyer et al., 2022), and GPT-4 (OpenAI, 2023) exhibit stronger ability in zero-shot or few-shot tasks than their base models. After Meta released the powerful open-source LLM LLaMA (Touvron et al., 2023a) and LLaMA2 (Touvron et al., 2023b), lots of instruction fine-tuning works based on LLaMA or LLaMA2 were proposed in the natural language generation or multimodal generation domain, such as Alpaca, Vicuna (Chiang et al., 2023), OpenFlamingo (Awadalla et al., 2023), LLaMA-Adapter (Zhang et al., 2023), and Emu (Sun et al., 2023). Our JudgeLM also belongs to the LLaMA family and takes the Vicuna series as base models. Our JudgeLM follows the instruction fine-tuning manner to create LLM judges and proposes to model the judgment-generation task as “grading, judging, and reasoning”. We further collect a high-quality, large-scale dataset for research in judging the performance of LLMs.

2.2 EVALUATION OF LARGE LANGUAGE MODELS

As many open-source large language models (LLMs) and their fine-tuned variants are proposed and present remarkable performance on various tasks, evaluating the capabilities of LLMs becomes a popular and challenging task. To address this problem, Chatbot Arena (Zheng et al., 2023) aims to build a crowdsourced platform that ranks the LLMs through pairwise comparison and Elo rating. The crowdsourced way to evaluate LLMs has more reliable results but faces high costs and low efficiency. Vicuna (Chiang et al., 2023) uses GPT-4 as a judge to select the better answer. Although the GPT-4-based method can judge LLMs like a human expert, the API-based methods have potential risks of data leakage and unstable performance. Zeno Build (Alex & Graham, 2023) proposes to evaluate LLMs at a customer service dataset, but using traditional metrics such as ChrF (Popović, 2015) and BERTScore (Zhang et al., 2019) can not fully evaluate the answers of LLMs in open-ended tasks. Besides, PandaLM (Wang et al., 2023) and Auto-J Li et al. (2023a) developed judge models based on LLaMA (Touvron et al., 2023a) or LLaMA2 (Touvron et al., 2023b) to compare answers produced by LLMs. When serving as judges, PandaLM achieves an accuracy close to ChatGPT but [ignoring the inherent LLM biases](#) limits its performance further. Our JudgeLM contains scalable judges from 7B-parameter to 33B-parameter and achieves state-of-the-art performance in both PandaLM and our benchmarks. Furthermore, researchers can use the proposed JudgeLM locally which ensures reproducibility and data security.

3 DATASET

High-quality, large-scale datasets are crucial for effectively fine-tuning large language models (LLMs) to act as evaluative judges. However, the concurrent datasets, such as the one by PandaLM (Wang et al., 2023), present limitations in terms of diversity and the granularity of judgment criteria. To address this, we introduce a novel dataset replete with a rich variety of seed tasks, comprehensive answers from modern LLMs, answers’ grades from the teacher judge, and detailed reasons for judgments. Section 3.1 elucidates the data generation process, while Section 3.2 delineates the methods adopted for training and evaluation using our dataset.

162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187

Input							
Question							
If Rosslyn Mountain Boys had produced two more albums, how many albums would they have produced? Rosslyn Mountain Boys was a band that backed up a number of nationally known singers, and released two albums of their own.							
Answer 1				Ground Truth			
4				Rosslyn Mountain Boys produced two albums on their own, so if they produced two more albums then they would have produced four albums.			
Answer 2							
Rosslyn Mountain Boys produced							
Traditional Metrics							
Answer	Rouge-1↑	Rouge-2↑	Rouge-L↑	BLEU↑	BERTScore↑	BLEURT↑	BARTScore↑
1	0.00	0.00	0.00	0.00	0.62	-1.39	-5.33
2	0.30	0.24	0.30	0.52	0.76	-0.78	-3.76
Our Judgment Output							
Answer 1's Score: 10				Answer 2's Score: 1			
Assistant 2's response is incomplete and does not provide any information or answer to the question, hence the low score. On the other hand, Assistant 1's response is accurate and directly answers the question. The Rosslyn Mountain Boys produced two albums, and if they had produced two more, they would have produced a total of four albums. Therefore, Assistant 1 receives a perfect score.							

188 Figure 2: The input and output of our JudgeLM data sample. In open-ended scenarios, traditional
189 metrics can not judge answers accurately by comparing the answers with ground truth. However,
190 the LLM judges can understand the questions and answers and give accurate scores and reasons.

191 3.1 DATA GENERATION

192
193 The primary objective of our data generation is to create a large-scale and diversified dataset that
194 maximizes the evaluative capabilities of judge models. We sample 105K instruction seed tasks from
195 a large-scale set that contains Alpaca-GPT4 (Peng et al., 2023), Dolly-15K (Conover et al., 2023),
196 GPT4All-LAION (Anand et al., 2023), and ShareGPT. To enhance the heterogeneity of the dataset,
197 answers are collated from 11 leading open-source LLMs including, but not limited to, LLaMA (Tou-
198 vron et al., 2023a), Alpaca, and Vicuna (Chiang et al., 2023). Following this, we amalgamate LLM-
199 generated answers with the reference answer to create answer sets. Pairs are randomly selected
200 from the sets, upon which, fine-grained scores and detailed reasons are assigned by the advanced
201 teacher model, GPT-4. To ensure robust and comprehensive judgments, we utilize detailed tem-
202 plates as demonstrated in Fig. 3. Additionally, to allow the model to judge with reference answers,
203 the reference-inclusive template is employed as Fig. 4. This encourages the model to integrate ex-
204 ternal knowledge during the evaluative process. Please note that all samples in the JudgeLM *val* set
205 are further checked and re-annotated by authors to ensure alignment with human preference.

206 3.2 TRAINING AND EVALUATING

207
208 To better utilize our dataset to train and evaluate the judge models, we partition it into a training split
209 and a validation split. The training set contains 100K judge samples, while the validation set has
210 5K. We then introduce the way we use this dataset to train and evaluate, respectively.

211 **Training.** The training process of JudgeLM adheres to the instruction fine-tuning paradigm. As il-
212 lustrated in Fig. 2, the model is fed a question alongside a pair of answers, and an optional reference
213 answer, yielding outputs comprising scores and detailed reasons. It is imperative to note the signif-
214 icance of a detailed crafted prompt template to harness the full potential of JudgeLM’s instruc-
215 tion-following ability. Distinct input templates cater to scenarios with and without references, as depicted
in Fig. 3 and Fig. 4 respectively.

To further analyze the scaling ability of JudgeLM, we fine-tune JudgeLM with sizes of 7B, 13B, and 33B parameters. The specific hyperparameters are enumerated in Table 11. As for the scaling analysis for dataset size, we also fine-tune JudgeLM on varying data scales from 3.5K to 100K samples. JudgeLM demonstrates scaling ability both in terms of model size and data volume.

Evaluating. For the judge’s result, we model it as “grading, judging, and reasoning”. The judge model first generates scores for answer pairs. Subsequently, we can get the judge result from three situations: “Answer 1 wins” if the answer 1’s score is higher than the answer 2’s, “Answer 2 wins” if the answer 2’s score is higher, or “Tie” if the scores of two answers are the same. Last, the model generates detailed reasons if needed. The advantage of this modeling is that the judge model just needs little time to grade and judge, and generates time-consuming reasoning optionally.

For the metrics, we employ the objective metrics and reliability metrics to evaluate the judge models comprehensively. For the objective metrics, we compute the agreement, precision, recall, and F1-score between the model’s judge results and those of the teacher. This provides insights into the alignment of judge models with established benchmarks, such as GPT-4 or human experts. As for reliability metrics, we first compare the results before and after swapping LLM answers. Then we calculate the self-consistency to measure the judge model’s reliability. Last, we further calculate the metrics like “bias toward 1st”, “bias toward 2nd”, and “delta bias” to get insights from specific position biases and their variance.

4 INHERENT BIAS

In this paper, we also study the inherent biases that influence the reliability of fine-tuned LLM judges through reliability metrics and visualizations.

Position Bias. Position bias means that the LLM judges prefer answers in a certain position and it widely exists in natural language processing tasks (Ko et al., 2020; Wang et al., 2018) and decision-making of humans (Blunch, 1984; Raghubir & Valenzuela, 2006). The powerful LLMs, ChatGPT and GPT-4, also face this challenge when working as judges (Wang et al., 2023; Zheng et al., 2023; Li et al., 2023b). As the qualitative and quantitative results shown in Fig. 8 and Table 5, JudgeLM also faces the position bias and prefers the first answer when swapping the positions of answers.

Knowledge Bias. Knowledge bias arises when the pre-trained data lacks the knowledge of some seed tasks or induces possibly undesirable knowledge (Ko et al., 2020; Zheng et al., 2023) that could degenerate the generative capabilities of LLMs. Fig. 10 provides an example that LLM judges can not give correct judgments to open-ended tasks if they lack related truth.

Format Bias. Researchers expect that the judge model can make judgments based on pre-trained knowledge when the reference is not available and can make judgments following the reference when it is available. However, our experiments revealed that judge models fine-tuned without reference perform poorly in judging with reference, and vice versa, as shown in Fig. 12, Fig. 13, and Table 6. We hypothesize fine-tuning with references encourages the judge model to make judgments based on external knowledge and fine-tuning without references pushes the judge model to make judgments through its pre-trained knowledge. We name the situation that a judge fine-tuned without reference but validated with reference as a mismatched format, and vice versa. Such a format bias limits the further generalization of the judge model in other domains.

5 METHOD

In evaluating LLM-generated answers for a seed question, the LLM judge aims to determine the superior answer from a pair of candidates. Motivated by recent methods (Touvron et al., 2023a; Chiang et al., 2023; Ouyang et al., 2022), we present JudgeLM, a scalable judge model, and address inherent biases in such models. Our methodology is depicted in Fig. 1b. The subsequent sections provide a detailed breakdown of our approach.

5.1 SWAP AUGMENTATION

MT-bench (Zheng et al., 2023) and PandaLM (Wang et al., 2023) alleviate the position bias by judging twice with original and reverse order. These methods regard the result as a tie if the judgments

270 are not the same. This kind of method ignoring the inherent position bias and casting double time to
 271 evaluate, can be regarded as a compromise and does not improve the reliability of LLM judges.

272 Intuitively, swapping the positions at the fine-tuning stage could push the judge model to pay more
 273 attention to the contents of answers rather than positions. Leveraging our structured judge data,
 274 we can easily swap the positions of answers to generate a new input sample. Correspondingly, we
 275 also swap the scores and question indexes of the judgment from the teacher (i.e., GPT4) to get the
 276 new ground truth. As shown in Fig. 15, the augmented judge sample keeps the same results but
 277 exchanges the positions of answers. Overall, it is simple but effective to augment the training data
 278 and address position bias. The JudgeLM-with-swap-augmentation can give good judgment to the
 279 same judge sample as shown in Fig. 9.

281 5.2 REFERENCE SUPPORT

282 Introducing external knowledge in the fine-tuning stage is an intuitive way to make up for the lack
 283 of related pre-trained knowledge. To do so, we propose the reference support method to teach the
 284 model to judge with the help of reference answers. Following Zheng et al. (2023), we collect refer-
 285 ence answers for all judge samples and re-generate reference-guided judgments by GPT-4. Please
 286 note that GPT-4 also gives different scores and judgments for most judge samples with or without
 287 references. This proves that the differences between pre-trained knowledge and reference answers
 288 greatly impact judgments. As shown in Fig. 11, the JudgeLM with reference support can avoid fac-
 289 tual errors and give reliable judgments. Furthermore, introducing reference support to LLM judges
 290 can simply insert judge preferences. JudgeLM with reference support training can flexibly set refer-
 291 ence answers with different preferences for different scenarios and needs. As shown in Fig. 16,
 292 changing reference answers does not need extra training and makes JudgeLM more flexible to dif-
 293 ferent preferences.

295 5.3 REFERENCE DROP

296 To address the format bias, we introduce a method, named reference drop, in which we randomly
 297 drop the training sample with reference and use the corresponding sample without reference. As
 298 shown in Fig. 14, judge models with reference drop can alleviate the overfitting for fine-tuning
 299 formats and make judgments based on external reference or pre-trained knowledge when given
 300 reference or not, respectively. Furthermore, the reference drop method also makes the judge model
 301 easy to use and decreases the cost of fitting into different formats.

304 6 EXPERIMENT

305 We study the performance of JudgeLM as follows: Section 6.1 presents the main results of JudgeLM
 306 comparing with concurrent methods, Section 6.2 analyzes the scaling ability of JudgeLM from both
 307 model sizes and data scales, and Section 6.3 shows ablation studies of proposed methods in detail.
 308 Detailed settings are shown in Section A.2.

311 6.1 MAIN RESULTS

312 **Comparison on JudgeLM Benchmark.** We first evaluate the proposed JudgeLM on our *val* set.
 313 Note that JudgeLM *val* set is further checked and re-annotated by authors to ensure alignment with
 314 human preference. As shown in Table 1, we give the quantitative results of GPT-3.5, Vicuna-13B,
 315 PandaLM-7B, Auto-J-13B (Li et al., 2023a), InstructScore-7B (Xu et al., 2023), and our JudgeLM
 316 with three model sizes. Among them, GPT-3.5 is used in the form of APIs with the help of templates
 317 in Fig. 3 and Fig. 4. PandaLM-7B and Auto-J-13B are deployed with the released checkpoints and
 318 templates. These methods could be regarded as zero-shot methods because they are not fine-tuned
 319 by the JudgeLM dataset. On JudgeLM *val* set, the vanilla Vicuna-13B fails 77% of questions.
 320 Specifically, the vanilla Vicuna-13B can not even output a pair of scores in judgments in the failed
 321 cases. But the finetuned version, i.e., JudgeLM, would not fail any questions in the JudgeLM *val* set.
 322 Our JudgeLMs are fine-tuned with proposed methods, i.e., swap augmentation, reference support,
 323 and reference drop. So, they can handle situations with or without references simultaneously. It
 can be observed that our JudgeLM-7B outperforms PandaLM-7B, Auto-J, and InstructScore in all

Table 1: Main results for our JudgeLM and concurrent methods on our *val* set, which uses GPT-4 annotation results as ground truth.

Methods	Agreement \uparrow (w/ GPT-4)	Precision \uparrow (w/ GPT-4)	Recall \uparrow (w/ GPT-4)	F1 \uparrow (w/ GPT-4)	Consistency \uparrow (w/ swap.)
<i>Judge w/o reference.</i>					
GPT-3.5	73.83	70.70	52.80	52.85	68.89
Vicuna-13B	-	-	-	-	-
PandaLM-7B	68.61	40.75	38.82	39.41	74.78
Auto-J-13B	74.86	61.65	57.53	58.14	84.34
<i>Judge w/o reference (Ours).</i>					
JudgeLM-7B	81.11	69.67	78.39	72.21	83.57
JudgeLM-13B	84.33	73.69	80.51	76.17	85.01
JudgeLM-33B	89.03	80.97	84.76	82.64	91.36
<i>Judge w/ reference.</i>					
GPT-3.5	71.46	56.86	51.12	51.14	62.94
Vicuna-13B	-	-	-	-	-
PandaLM-7B	63.77	39.79	34.82	35.18	55.39
Auto-J-13B	72.90	58.80	56.12	56.59	82.84
InstructScore-7B	55.80	58.74	56.84	53.72	-
<i>Judge w/ reference (Ours).</i>					
JudgeLM-7B	84.08	75.92	82.55	78.28	84.46
JudgeLM-13B	85.47	77.71	82.90	79.77	87.23
JudgeLM-33B	89.32	84.00	86.21	84.98	92.37

Table 2: JudgeLM zero-shot evaluation results on PandaLM *test* set, which uses human annotation results as ground truth. “*” means the results are reported in PandaLM (Wang et al., 2023)

Methods	Agreement \uparrow (w/ Human)	Precision \uparrow (w/ Human)	Recall \uparrow (w/ Human)	F1 \uparrow (w/ Human)
<i>zero-shot methods.</i>				
GPT-3.5*	62.96	61.95	63.59	58.20
GPT-4*	66.47	66.20	68.15	61.80
<i>Fine-tuned on PandaLM train set.</i>				
PandaLM-7B*	59.26	57.28	59.23	54.56
<i>Ours (zero-shot).</i>				
JudgeLM-7B	65.07	66.89	71.95	61.92
JudgeLM-13B	68.97	68.21	74.15	65.12
JudgeLM-33B	75.18	69.30	74.93	69.73

metrics, and even surpasses GPT-3.5. Furthermore, the proposed JudgeLM-33B exhibits the most powerful judge ability.

Comparison on Other Human Evaluation Benchmarks. We further evaluate our JudgeLM on other Human evaluation benchmarks, i.e., PandaLM *test* set and human-annotated MM-Vet. PandaLM’s *train* and *val* sets are annotated by GPT-3.5 and humans, respectively. Following the manner of the PandaLM *val* set, we present the zero-shot results of JudgeLM in Table 2. It can be observed that the JudgeLM-7B outperforms GPT-3.5 and PandaLM-7B. When compared with GPT-4, JudgeLM-7B has lower accuracy and higher Precision, Recall, and F1-score than GPT-4. Furthermore, JudgeLM-33B achieves higher results than GPT-4, which demonstrates that fine-tuned JudgeLM can outperform its teacher in this specific task. Besides, we also propose a human-annotated multimodal judging benchmark to evaluate our JudgeLM as shown in Table 13.

Efficiency comparison. To further compare the efficiency between our JudgeLM and PandaLM, we conduct experiments on our *val* set to display the time cost using the same machine with 8 NVIDIA-A100 (40G) GPUs. As shown in Table 3, we display the methods and model sizes in the

Table 3: Efficiency comparison for our JudgeLM and PandaLM on our *val* set. We use a machine with 8 Nvidia-A100 GPUs with 40G memory to evaluate their efficiency.

Methods	model size	GPUs per model	parallel judge?	generate reason?	total time
PandaLM	7B	1	✗	✓	6 hrs 40 mins
<i>Ours.</i>					
JudgeLM	7B	1	✗	✓	6 hrs 40 mins
JudgeLM	7B	1	✗	✗	24 mins
JudgeLM	7B	1	✓	✓	50 mins
JudgeLM	7B	1	✓	✗	3 mins
JudgeLM	13B	1	✓	✗	5 mins
JudgeLM	33B	2	✓	✗	15 mins

Table 4: Performance analysis for the scaling JudgeLM on our *val* set.

Judge Size	Data Scale	Agreement \uparrow (w/ GPT-4)	Consistency \uparrow (w/ swap.)	Bias \downarrow toward 1st	Bias \downarrow toward 2nd	Delta bias \downarrow
7B	3.5k	75.87	73.45	19.83	6.72	13.11
7B	10k	78.89	78.25	17.30	4.45	12.85
7B	30k	81.43	80.89	14.54	4.57	9.97
7B	100k	83.71	82.62	12.31	5.07	7.24
13B	3.5k	80.61	78.91	14.68	6.41	8.27
13B	10k	83.19	81.90	13.42	4.68	8.74
13B	30k	84.39	82.99	11.96	5.05	6.91
13B	100k	85.87	83.01	11.53	5.46	6.07
33B	3.5k	85.38	85.16	9.34	5.50	3.84
33B	10k	87.49	86.40	8.32	5.28	3.04
33B	30k	88.84	87.34	7.57	5.09	2.48
33B	100k	90.06	87.93	6.85	5.22	1.63

first and second columns. The third column shows the needed GPUs for each judge model. The models with 7B or 13B parameters run on 1 A100 GPU with 40G memory while the 33B-parameter needs 2 GPUs. The fourth column shows whether the methods can judge answers in parallel. The fifth column indicates whether judge reasons are generated at runtime. The sixth column presents the total time cost. We use PandaLM-7B and JudgeLM-7B as efficiency baselines, which do not use parallel judging and generate detailed reasons for all questions. Thanks to the modeling of JudgeLM, i.e., “grading, judging, and reasoning”, JudgeLM can skip the reasoning phase and only requires 24 minutes, which is $16.65 \times$ faster than baselines. When we enable the engineering optimization of parallel judging, the JudgeLM can make full use of the 8 GPUs and cost only 50 minutes, which is $8 \times$ faster than the baseline running on a single GPU. When we enable parallel judging and skip the reasoning phase for JudgeLM, the JudgeLM-7B only consumes 3 minutes to judge 5000 response pairs, which is $133.3 \times$ faster than baselines. The largest judge model, JudgeLM-33B, can also complete the validation within 15 minutes. JudgeLM’s high efficiency can significantly reduce the time spent on evaluating LLMs, allowing researchers and developers to boost the pace of advancements.

6.2 SCALING ANALYSIS OF JUDGE LM

In this section, we analyze the scaling ability of the plain JudgeLM (without the proposed methods) on our *val* set without reference as illustrated in Table 4. As we increase the model size and data scale, we can observe the metrics increase. It demonstrates that the proposed JudgeLM is scalable and can reach up to 90.06% agreement and 87.93% consistency with 33B-parameter and 100K fine-tuning data.

Table 5: Ablation study for the swap augmentation on our *val* set.

Methods	Agreement \uparrow (w/ GPT-4)	Consistency \uparrow (w/ swap.)	Bias \downarrow toward 1st	Bias \downarrow toward 2nd	Delta Bias \downarrow
baseline	75.87	73.45	19.83	6.72	13.11
+ swap aug.	76.51	78.89	15.34	5.77	9.57

Table 6: Ablation study for the reference support and reference drop on our *val* set.

Methods	<i>ft</i> w/ ref?	<i>val</i> w/ ref?	Agreement \uparrow (w/ GPT-4)	Consistency \uparrow (w/ swap.)	Bias \downarrow toward 1st	Bias \downarrow toward 2nd	Delta Bias \downarrow
<i>matching format.</i>							
baseline	\times	\times	75.87	73.45	19.83	6.72	13.11
baseline	\checkmark	\checkmark	80.15	81.23	11.55	7.22	4.33
<i>mismatched format.</i>							
baseline	\times	\checkmark	73.09	67.75	29.44	2.81	26.63
baseline	\checkmark	\times	75.69	73.40	20.89	5.71	15.18
<i>w/ ref. drop.</i>							
baseline	ref. drop	\times	76.86	77.13	17.30	5.57	11.73
baseline	ref. drop	\checkmark	80.35	81.24	11.48	7.28	4.20

Table 7: Performance of JudgeLM-7B with explanation-first (CoT) or score-first (Ours) on JudgeLM *val* set.

Methods	Agreement \uparrow (w/ GPT-4)	Consistency \uparrow (w/ swap.)	Bias \downarrow toward 1st	Bias \downarrow toward 2nd	Delta Bias \downarrow
score-first (Ours)	75.87	73.45	19.83	6.72	13.11
explanation-first (CoT)	75.54	74.39	15.05	10.56	4.50

6.3 ABLATION STUDY

In this section, we present the ablation studies of the proposed methods. For all ablation studies, we use JudgeLM-7B as the base model and 3.5K data for fine-tuning. Based on this baseline, we analyze the improvements brought by swap augmentation, reference support, and reference drop.

Improvements of Swap Augmentation. As shown in Table 5, swap augmentation can improve the baseline model comprehensively. It improves consistency by 5.44%, which demonstrates that swap augmentation can reduce the influence of position bias and push the judge to pay more attention to the contents of answers.

Improvements of Reference Support. As shown in the rows with the matching format of Table 6, JudgeLM fine-tuned with reference support exhibits superior performance on every metric. It demonstrates that the introduction of reference answers induces the judge to rely on external knowledge and addresses the limitation of pre-trained knowledge.

Improvements of Reference Drop. As shown in Table 6, baselines can not reach satisfactory performance when facing mismatched formats. With the help of the reference drop, the JudgeLM can handle both the format with or without reference and achieve higher agreement and consistency. It demonstrates that reference drop can address the format bias and avoid the JudgeLM overfitting to a single format.

Ablation of Judging Form We further evaluate the performance of JudgeLM-7B with explanation-first (Chain of Thought, CoT (Wei et al., 2022)) or score-first (Ours) in Table 7. JudgeLM with CoT performs similar agreement with our score-first baseline but with higher consistency, which means that explanation-first form, i.e., CoT, can alleviate the position bias of fine-tuned judges, but not bring significant agreement improvement. As a result, we choose the score-first method for JudgeLM, which has slightly less consistency but more flexible usage.

Table 8: Comparison between GPT-4 teacher and JudgeLM-33B on JudgeLM *val* set.

Methods	Agreement \uparrow (w/ GPT-4)	Consistency \uparrow (w/ swap.)	Bias \downarrow toward 1st	Bias \downarrow toward 2nd	Delta Bias \downarrow
GPT-4	–	85.82	6.10	8.10	2.00
JudgeLM-33B	89.03	91.36	5.55	3.09	2.46

6.4 ADDITIONAL EXPERIMENT

Comparison with GPT-4 Teacher As shown in Table 8, we further list the metrics except for the agreement with GPT-4 itself. JudgeLM-33B achieves higher consistency than GPT-4, which demonstrates that fine-tuning judges like JudgeLM-33B can achieve higher consistency through the proposed techniques.

The learning paradigm of JudgeLM is similar to knowledge distillation, as JudgeLM learns from the expert judgments provided by GPT-4. In the knowledge distillation domain (Gou et al., 2021), the student model (JudgeLM) mimics the teacher model (GPT-4) to achieve competitive or even superior performance. Additionally, our JudgeLM employs three key methods and utilizes large-scale training data specifically for the judging task to enhance its agreement and consistency. As mentioned in “Comparison on Other Human Evaluation Benchmarks” under Section 6.1, our experiments demonstrate that a fine-tuned specialist judge model can surpass its generalist teacher on some judging benchmarks, i.e., JudgeLM *val* set and PandaLM *test* set.

6.5 DETAILS OF DATASET

For the proposed dataset and benchmark, we also provide the explanation of usage scope, details of metric calculations, dataset quality, question category & distribution (among 19 categories), and comparison with UltraFeedback (Cui et al., 2023) in Sec. A.1. We hope the dataset can help researchers build more robust evaluation tools in the future.

6.6 GENERALIZATION ABILITY OF JUDGE LM

Not only judging answer pairs, but our JudgeLM can also generalize to various judging tasks (including math problems and code generation), unseen judging benchmarks (human-annotated benchmark, multimodal judging benchmark, retrieval-format benchmark, multiple-format benchmark, toxic chat benchmark, reward model benchmark), and other various judging extensions (grading single answer, multi-turn chat). We leave the detailed analysis in Sec. A.3 of the appendix.

6.7 MORE DISCUSSION

Due to the limitation of pages, we leave more discussion in Sec. A.4 of the appendix.

7 CONCLUSION

In this paper, we first introduce a high-quality, large-scale dataset for LLM evaluation, that provides a robust foundation for future research. Next, the proposed JudgeLM as scalable judges for evaluating LLMs in open-ended tasks efficiently, achieving state-of-the-art judge performance on two benchmarks. Then, we [analyze two key biases](#) and [introduce a new format bias](#) in fine-tuning LLMs as judges, and address them with the proposed techniques. We hope our work can motivate more studies to explore the judge models for LLMs in open-ended tasks and build more powerful LLMs with guidance from judge models.

Limitations. Although the proposed JudgeLM achieves encouraging performance and efficiency, the cost of the judge dataset limits further scaling up in the judge dataset. Currently, we spend about 4000 dollars to provide 100K high-quality GPT-4-generated judge data to the public. We expect to further improve the performance of judge models with the help of synthetic judge data.

REFERENCES

- 540
541
542 Cabrera Alex and Neubig Graham. Zeno chatbot report, 2023. URL [https://github.com/zeno-ml/zeno-build/tree/main/examples/chatbot/](https://github.com/zeno-ml/zeno-build/tree/main/examples/chatbot/report#zeno-chatbot-report)
543 [report#zeno-chatbot-report](https://github.com/zeno-ml/zeno-build/tree/main/examples/chatbot/report#zeno-chatbot-report).
544
- 545 Yuvanesh Anand, Zach Nussbaum, Brandon Duderstadt, Benjamin Schmidt, and Andriy Mulyar.
546 Gpt4all: Training an assistant-style chatbot with large scale data distillation from gpt-3.5-turbo.
547 <https://github.com/nomic-ai/gpt4all>, 2023.
- 548 Anas Awadalla, Irena Gao, Josh Gardner, Jack Hessel, Yusuf Hanafy, Wanrong Zhu, Kalyani
549 Marathe, Yonatan Bitton, Samir Gadre, Shiori Sagawa, et al. Openflamingo: An open-
550 source framework for training large autoregressive vision-language models. *arXiv preprint*
551 *arXiv:2308.01390*, 2023.
- 552 Jinze Bai, Shuai Bai, Yunfei Chu, Zeyu Cui, Kai Dang, Xiaodong Deng, Yang Fan, Wenbin Ge,
553 Yu Han, Fei Huang, et al. Qwen technical report. *arXiv preprint arXiv:2309.16609*, 2023.
- 554 Stella Biderman, Hailey Schoelkopf, Quentin Gregory Anthony, Herbie Bradley, Kyle O’Brien, Eric
555 Hallahan, Mohammad Aflah Khan, Shivanshu Purohit, USVSN Sai Prashanth, Edward Raff, et al.
556 Pythia: A suite for analyzing large language models across training and scaling. In *International*
557 *Conference on Machine Learning*, pp. 2397–2430. PMLR, 2023.
- 558 Niels J Blunch. Position bias in multiple-choice questions. *Journal of Marketing Research*, 21(2):
559 216–220, 1984.
- 560 Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal,
561 Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are
562 few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.
- 563 Wei-Lin Chiang, Zhuohan Li, Zi Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng,
564 Siyuan Zhuang, Yonghao Zhuang, Joseph E Gonzalez, et al. Vicuna: An open-source chatbot
565 impressing gpt-4 with 90%* chatgpt quality. See <https://vicuna.lmsys.org> (accessed 14 April
566 2023), 2023.
- 567 Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam
568 Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. Palm:
569 Scaling language modeling with pathways. *arXiv preprint arXiv:2204.02311*, 2022.
- 570 Hyung Won Chung, Le Hou, Shayne Longpre, Barret Zoph, Yi Tay, William Fedus, Eric Li, Xuezhi
571 Wang, Mostafa Dehghani, Siddhartha Brahma, et al. Scaling instruction-finetuned language mod-
572 els. *arXiv preprint arXiv:2210.11416*, 2022.
- 573 Mike Conover, Matt Hayes, Ankit Mathur, Jianwei Xie, Jun Wan, Sam Shah, Ali Ghodsi, Patrick
574 Wendell, Matei Zaharia, and Reynold Xin. Free dolly: Introducing the world’s first truly open
575 instruction-tuned llm, 2023. URL [https://www.databricks.com/blog/2023/04/](https://www.databricks.com/blog/2023/04/12/dolly-first-open-commercially-viable-instruction-tuned-llm)
576 [12/dolly-first-open-commercially-viable-instruction-tuned-llm](https://www.databricks.com/blog/2023/04/12/dolly-first-open-commercially-viable-instruction-tuned-llm).
- 577 Ganqu Cui, Lifan Yuan, Ning Ding, Guanming Yao, Wei Zhu, Yuan Ni, Guotong Xie, Zhiyuan Liu,
578 and Maosong Sun. Ultrafeedback: Boosting language models with high-quality feedback. *arXiv*
579 *preprint arXiv:2310.01377*, 2023.
- 580 Jianping Gou, Baosheng Yu, Stephen J Maybank, and Dacheng Tao. Knowledge distillation: A
581 survey. *International Journal of Computer Vision*, 129(6):1789–1819, 2021.
- 582 Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and
583 Jacob Steinhardt. Measuring massive multitask language understanding. *arXiv preprint*
584 *arXiv:2009.03300*, 2020.
- 585 Shima Imani, Liang Du, and Harsh Shrivastava. Mathprompter: Mathematical reasoning using large
586 language models. *arXiv preprint arXiv:2303.05398*, 2023.
- 587 Hamish Ivison, Yizhong Wang, Valentina Pyatkin, Nathan Lambert, Matthew Peters, Pradeep
588 Dasigi, Joel Jang, David Wadden, Noah A Smith, Iz Beltagy, et al. Camels in a changing cli-
589 mate: Enhancing lm adaptation with tulu 2. *arXiv preprint arXiv:2311.10702*, 2023.
- 590
591
592
593

- 594 Srinivasan Iyer, Xi Victoria Lin, Ramakanth Pasunuru, Todor Mihaylov, Daniel Simig, Ping Yu,
595 Kurt Shuster, Tianlu Wang, Qing Liu, Punit Singh Koura, et al. Opt-impl: Scaling language model
596 instruction meta learning through the lens of generalization. *arXiv preprint arXiv:2212.12017*,
597 2022.
- 598
599 Dongfu Jiang, Yishan Li, Ge Zhang, Wenhao Huang, Bill Yuchen Lin, and Wenhui Chen. Tiger-
600 score: Towards building explainable metric for all text generation tasks. *Transactions on Machine*
601 *Learning Research*, 2023.
- 602
603 Seungone Kim, Jamin Shin, Yejin Cho, Joel Jang, Shayne Longpre, Hwaran Lee, Sangdoon Yun,
604 Seongjin Shin, Sungdong Kim, James Thorne, et al. Prometheus: Inducing fine-grained evalua-
605 tion capability in language models. In *The Twelfth International Conference on Learning Repre-*
606 *sentations*, 2023.
- 607
608 Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint*
609 *arXiv:1412.6980*, 2014.
- 610
611 Miyoung Ko, Jinhyuk Lee, Hyunjae Kim, Gangwoo Kim, and Jaewoo Kang. Look at the first
612 sentence: Position bias in question answering. In *2020 Conference on Empirical Methods in*
613 *Natural Language Processing, EMNLP 2020*, pp. 1109–1121. Association for Computational
614 Linguistics (ACL), 2020.
- 615
616 Nathan Lambert, Valentina Pyatkin, Jacob Morrison, LJ Miranda, Bill Yuchen Lin, Khyathi Chandu,
617 Nouha Dziri, Sachin Kumar, Tom Zick, Yejin Choi, et al. Rewardbench: Evaluating reward
618 models for language modeling. *arXiv preprint arXiv:2403.13787*, 2024.
- 619
620 Seongyun Lee, Seungone Kim, Sue Hyun Park, Geewook Kim, and Minjoon Seo. Prometheusvi-
621 sion: Vision-language model as a judge for fine-grained evaluation. *arXiv preprint*
622 *arXiv:2401.06591*, 2024.
- 623
624 Junlong Li, Shichao Sun, Weizhe Yuan, Run-Ze Fan, Hai Zhao, and Pengfei Liu. Generative
625 judge for evaluating alignment. *CoRR*, abs/2310.05470, 2023a. URL [https://doi.org/](https://doi.org/10.48550/arXiv.2310.05470)
626 [10.48550/arXiv.2310.05470](https://doi.org/10.48550/arXiv.2310.05470).
- 627
628 Zongjie Li, Chaozheng Wang, Pingchuan Ma, Daoyuan Wu, Shuai Wang, Cuiyun Gao, and Yang
629 Liu. Split and merge: Aligning position biases in large language model based evaluators. *arXiv*
630 *preprint arXiv:2310.01432*, 2023b.
- 631
632 Percy Liang, Rishi Bommasani, Tony Lee, Dimitris Tsipras, Dilara Soylu, Michihiro Yasunaga, Yian
633 Zhang, Deepak Narayanan, Yuhuai Wu, Ananya Kumar, et al. Holistic evaluation of language
634 models. *arXiv preprint arXiv:2211.09110*, 2022.
- 635
636 Chin-Yew Lin. Rouge: A package for automatic evaluation of summaries. In *Text summarization*
637 *branches out*, pp. 74–81, 2004.
- 638
639 Zi Lin, Zihan Wang, Yongqi Tong, Yangkun Wang, Yuxin Guo, Yujia Wang, and Jingbo Shang.
640 Toxicchat: Unveiling hidden challenges of toxicity detection in real-world user-ai conversation.
641 *arXiv preprint arXiv:2310.17389*, 2023.
- 642
643 Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. *arXiv*
644 *preprint arXiv:2304.08485*, 2023.
- 645
646 Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *ICLR*, 2019.
- 647
648 Haipeng Luo, Qingfeng Sun, Can Xu, Pu Zhao, Jianguang Lou, Chongyang Tao, Xiubo Geng, Qing-
649 wei Lin, Shifeng Chen, and Dongmei Zhang. Wizardmath: Empowering mathematical reasoning
650 for large language models via reinforced evol-instruct. *arXiv preprint arXiv:2308.09583*, 2023.
- 651
652 Jinjie Ni, Yifan Song, Deepanway Ghosal, Bo Li, David Junhao Zhang, Xiang Yue, Fuzhao Xue,
653 Zian Zheng, Kaichen Zhang, Mahir Shah, et al. Mixeval-x: Any-to-any evaluations from real-
654 world data mixtures. *arXiv preprint arXiv:2410.13754*, 2024a.

- 648 Jinjie Ni, Fuzhao Xue, Xiang Yue, Yuntian Deng, Mahir Shah, Kabir Jain, Graham Neubig, and
649 Yang You. Mixeval: Deriving wisdom of the crowd from llm benchmark mixtures. *arXiv preprint*
650 *arXiv:2406.06565*, 2024b.
- 651
652 OpenAI. Chatgpt, 2022. URL <https://openai.com/blog/chatgpt/>.
- 653
654 OpenAI. Gpt-4 technical report, 2023.
- 655 Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong
656 Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow
657 instructions with human feedback. *Advances in Neural Information Processing Systems*, 35:
658 27730–27744, 2022.
- 659 Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic
660 evaluation of machine translation. In *Proceedings of the 40th annual meeting of the Association*
661 *for Computational Linguistics*, pp. 311–318, 2002.
- 662
663 Baolin Peng, Chunyuan Li, Pengcheng He, Michel Galley, and Jianfeng Gao. Instruction tuning
664 with gpt-4. *arXiv preprint arXiv:2304.03277*, 2023.
- 665
666 Maja Popović. chrF: character n-gram F-score for automatic MT evaluation. In *Proceedings of the*
667 *Tenth Workshop on Statistical Machine Translation*, pp. 392–395, Lisbon, Portugal, September
668 2015. Association for Computational Linguistics. doi: 10.18653/v1/W15-3049. URL [https://](https://aclanthology.org/W15-3049)
669 aclanthology.org/W15-3049.
- 670 Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi
671 Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text
672 transformer. *The Journal of Machine Learning Research*, 21(1):5485–5551, 2020.
- 673
674 Priya Raghurir and Ana Valenzuela. Center-of-inattention: Position biases in decision-making.
675 *Organizational Behavior and Human Decision Processes*, 99(1):66–80, 2006.
- 676
677 Aditya Ramesh, Mikhail Pavlov, Gabriel Goh, Scott Gray, Chelsea Voss, Alec Radford, Mark Chen,
678 and Ilya Sutskever. Zero-shot text-to-image generation. *arXiv preprint arXiv:2102.12092*, 2021.
- 679
680 Thibault Sellam, Dipanjan Das, and Ankur Parikh. Bleurt: Learning robust metrics for text genera-
681 tion. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*,
682 pp. 7881–7892, 2020.
- 683
684 Quan Sun, Qiyang Yu, Yufeng Cui, Fan Zhang, Xiaosong Zhang, Yuezhe Wang, Hongcheng Gao,
685 Jingjing Liu, Tiejun Huang, and Xinlong Wang. Generative pretraining in multimodality. *arXiv*
686 *preprint arXiv:2307.05222*, 2023.
- 687
688 Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée
689 Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and
690 efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023a.
- 691
692 Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Niko-
693 lay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open founda-
694 tion and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023b.
- 695
696 Xuanhui Wang, Nadav Golbandi, Michael Bendersky, Donald Metzler, and Marc Najork. Position
697 bias estimation for unbiased learning to rank in personal search. In *Proceedings of the eleventh*
698 *ACM international conference on web search and data mining*, pp. 610–618, 2018.
- 699
700 Yidong Wang, Zhuohao Yu, Zhengran Zeng, Linyi Yang, Cunxiang Wang, Hao Chen, Chaoya Jiang,
701 Rui Xie, Jindong Wang, Xing Xie, Wei Ye, Shikun Zhang, and Yue Zhang. Pandalm: An auto-
matic evaluation benchmark for llm instruction tuning optimization. *CoRR*, abs/2306.05087,
2023. URL <https://doi.org/10.48550/arXiv.2306.05087>.
- Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny
Zhou, et al. Chain-of-thought prompting elicits reasoning in large language models. *Advances in*
Neural Information Processing Systems, 35:24824–24837, 2022.

- 702 Wenda Xu, Danqing Wang, Liangming Pan, Zhenqiao Song, Markus Freitag, William Yang Wang,
703 and Lei Li. Instructscore: Explainable text generation evaluation with finegrained feedback. *arXiv*
704 *preprint arXiv:2305.14282*, 2023.
- 705
- 706 Longhui Yu, Weisen Jiang, Han Shi, Jincheng Yu, Zhengying Liu, Yu Zhang, James T Kwok, Zhen-
707 guo Li, Adrian Weller, and Weiyang Liu. Metamath: Bootstrap your own mathematical questions
708 for large language models. *arXiv preprint arXiv:2309.12284*, 2023a.
- 709
- 710 Weihao Yu, Zhengyuan Yang, Linjie Li, Jianfeng Wang, Kevin Lin, Zicheng Liu, Xinchao Wang,
711 and Lijuan Wang. Mm-vet: Evaluating large multimodal models for integrated capabilities,
712 2023b.
- 713
- 714 Weizhe Yuan, Graham Neubig, and Pengfei Liu. Bartscore: Evaluating generated text as text gener-
715 ation. *Advances in Neural Information Processing Systems*, 34:27263–27277, 2021.
- 716
- 717 Renrui Zhang, Jiaming Han, Aojun Zhou, Xiangfei Hu, Shilin Yan, Pan Lu, Hongsheng Li, Peng
718 Gao, and Yu Qiao. Llama-adapter: Efficient fine-tuning of language models with zero-init atten-
719 tion. *arXiv preprint arXiv:2303.16199*, 2023.
- 720
- 721 Susan Zhang, Stephen Roller, Naman Goyal, Mikel Artetxe, Moya Chen, Shuohui Chen, Christo-
722 pher Dewan, Mona Diab, Xian Li, Xi Victoria Lin, et al. Opt: Open pre-trained transformer
723 language models. *arXiv preprint arXiv:2205.01068*, 2022.
- 724
- 725 Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q Weinberger, and Yoav Artzi. Bertscore: Evaluat-
726 ing text generation with bert. *arXiv preprint arXiv:1904.09675*, 2019.
- 727
- 728 Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang,
729 Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, et al. Judging llm-as-a-judge with mt-bench and
730 chatbot arena. *arXiv preprint arXiv:2306.05685*, 2023.

730 A APPENDIX / SUPPLEMENTAL MATERIAL

731 A.1 MORE ABOUT DATASET

732 **Dataset Usage Scope** We emphasize that the JudgeLM dataset is intended only for academic re-
733 search and any commercial use is prohibited. Because the OpenAI’s terms prohibit developing
734 models that compete with OpenAI, the instruction-tuning datasets generated by the OpenAI’s API,
735 i.e., Alpaca, PandaLM, etc., all follow this rule.

736 **Details of Metric Calculations** For objective metrics, we use the judgments annotated by humans
737 or GPT-4 as ground truth labels, and the judgments generated by judge models as predicted labels.
738 We use TP , FP , TN , and FN to represent the true positive, false positive, true negative, and false
739 negative, respectively. The calculation of agreement, precision, recall, and F1-score are as follows:
740

$$741 \text{Agreement} = (TP + TN)/(TP + FP + TN + FN), \quad (1)$$

$$742 \text{Precision} = TP/(TP + FP), \quad (2)$$

$$743 \text{Recall} = TP/(TP + FN), \quad (3)$$

$$744 \text{F1-score} = (2 * TP)/(2 * TP + FP + FN). \quad (4)$$

745 For reliability metrics, we compare the results before and after swapping the order of the two answers
746 (A and B), i.e., from “the first answer is A, the second answer is B” to “the first answer is B, the
747 second answer is A”. When the judging results change, we mark it as a biased sample. Samples
748 with a bias toward the first position consist of three situations, “from Answer A wins to tie”, “from
749 Answer A wins to Answer B wins”, and “from tie to Answer B wins”. Similarly, samples with a
750 bias toward the second position also consist of three situations, “from Answer B wins to tie”, “from
751 Answer B wins to Answer A wins”, and “from tie to Answer A wins”. The calculation of metrics of
752 “bias toward 1st”, “bias toward 2nd”, “delta bias” are defined as follows:

756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809

$$\text{bias toward 1st} = \frac{\text{Number of samples with a bias toward the first position}}{\text{Numbers of total samples}}, \quad (5)$$

$$\text{bias toward 2nd} = \frac{\text{Number of samples with a bias toward the second position}}{\text{Numbers of total samples}}, \quad (6)$$

$$\text{delta bias} = |\text{bias toward 1st} - \text{bias toward 2nd}|. \quad (7)$$

Dataset Quality To ensure the high quality of the proposed dataset, we filter the low-quality data samples in each step. For data samples (including seed tasks and references) in four public datasets, i.e., Alpaca-GPT4 (Peng et al., 2023), Dolly-15K (Conover et al., 2023), GPT4All-LAION (Anand et al., 2023), and ShareGPT, we first remove data samples containing obviously incorrect, irrelevant, or harmful reference answers through automated filtering scripts. Next, we randomly sample 105K samples from the filtered set and extract answers from 11 LLMs. Then, we input the tasks, randomly sampled answer pairs, and optionally reference answers to the GPT-4 teacher for judgment. Finally, the authors of this work are involved in a multi-step validation process to ensure the quality, accuracy, and reliability of the judge samples. This process includes an initial annotation step where GPT-4 provides preliminary judgments, followed by independent human re-annotation where authors provide simple judgments (“Answer 1 wins,” “Answer 2 wins”, or “Tie”) without exposure to GPT-4’s annotations. The final step involves cross-validation and refinement, where human judgments are compared with GPT-4 annotations to thoroughly verify the judge results, scores, and reasoning quality. Please note that incorporating high-quality answers from closed-sourced models e.g., Qwen (Bai et al., 2023) and Claude, could enhance the diversity of the dataset. We leave it as a future work.

Question Category & Distribution of Validation Set We count the distribution of questions in the JudgeLM *val* set as shown in Table 9. Please note that the question categories included in the JudgeLM *val* set and *train* set are the same, but none of the data samples are identical.

Comparison with UltraFeedback Furthermore, we compare the JudgeLM dataset with UltraFeedback (Cui et al., 2023), which is an excellent dataset serving as a solid foundation for feedback-learning research. JudgeLM has nearly half more seeds than UltraFeedback, and an additional validation set containing 5K seeds. JudgeLM and UltraFeedback both provide scalar and text feedback, GPT-4 annotation, and fine-grained consideration. However, the JudgeLM dataset is further checked and re-annotated by humans, which provides double-checking on the quality of feedback. Moreover, JudgeLM supports judging with references, which can make up for the lack of pre-trained knowledge or insert specific judge preferences. Finally, JudgeLM clearly splits the seeds into 19 categories providing intuitive ability estimation for judges.

Dataset	<i>train</i> Seeds	<i>val</i> Seeds	Feedback Format	Annotator	fine grained?	with Ref.?	Seeds Categories
UltraFeedback	64K	0	Scalar & Text	GPT-4	Y	N	-
JudgeLM	100K	5K	Scalar & Text	GPT-4 & Human	Y	Y	19

Comparison with PandaLM Test Set Furthermore, we compare the JudgeLM dataset with the PandaLM test set. An analysis of task distributions in Table 10 shows significant differences between the PandaLM test set and the JudgeLM benchmark. For example, business, fact-QA, summarizing, linguistics, emotion, entity-processing, explain, retrieval, document, and chat are well-represented in PandaLM but absent in JudgeLM, while writing and roleplay show a significant delta percentage (over 4%). This confirms that the PandaLM test set includes 49% unseen task samples that are out of distribution for JudgeLM.

A.2 FINE-TUNING SETTING

We list the hyper-parameters we used, as shown in Table 11.

Table 9: Distribution of question categories in JudgeLM *val* set

	count	percentage		count	percentage
culture	233	4.66%	planning	309	6.18%
recommendation	482	9.64%	roleplay	77	1.54%
finance	142	2.84%	coding	201	4.02%
science	393	7.86%	health	278	5.56%
technique	42	0.84%	writing	625	12.50%
common-sense	373	7.46%	hardware	130	2.60%
art	335	6.70%	history	243	4.86%
math	250	5.00%	geography	199	3.98%
private-matter	421	8.42%	others	63	1.26%
law	204	4.08%	total	5000	100.00%

Table 10: Distribution of question categories in PandaLM test set. The Δ represents the percentage difference compared to the JudgeLM benchmark. We **bolded** categories that appear in the PandaLM test set but don't exist in the JudgeLM benchmark.

	count	percentage	Δ		count	percentage	Δ
business	87	8.71%	8.71%	writing	81	8.11%	-4.39%
fact-QA	70	7.01%	7.01%	planning	57	5.71%	-0.47%
summarizing	64	6.41%	6.41%	roleplay	57	5.71%	4.17%
linguistics	45	4.50%	4.50%	coding	54	5.41%	1.39%
emotion	45	4.50%	4.50%	art	44	4.40%	-2.30%
entity-processing	42	4.20%	4.20%	finance	40	4.00%	1.16%
explain	41	4.10%	4.10%	culture	38	3.80%	-0.86%
retrieval	40	4.00%	4.00%	math	37	3.70%	-1.30%
document	30	3.00%	3.00%	geography	12	1.20%	-2.78%
chat	26	2.60%	2.60%	others	5	0.50%	-0.76%
recommendation	84	8.41%	-1.23%	total	999	100.00%	

Table 11: JudgeLM fine-tuning setting.

config	JudgeLM / -7B / -13B / -33B
base model	Vicuna / -7B / -13B / -33B
model max length	2048
fine-tuning data source	JudgeLM-100K
learning rate	2e-5
learning rate schedule	cosine decay
optimizer	AdamW (Kingma & Ba, 2014; Loshchilov & Hutter, 2019)
optimizer hyper-parameters	$\beta_1, \beta_2, \epsilon = 0.9, 0.999, 1e-8$
weight decay	0.0
GPU nums	8 / 8 / 16
batch size	128
training epochs	3
warmup ratio	0.003
numerical precision	bf16, tf32
ZeRO optimizer (Ramesh et al., 2021)	stage 3
gradient checkpointing	True
GPT-3.5 and GPT-4 version	2023-03-15-preview

A.3 GENERALIZATION ABILITY OF JUDGE LM

To validate the generalization ability of JudgeLM, we test JudgeLM on various judging tasks (including math problems and code generation), unseen judging benchmarks (human-annotated benchmark, multimodal judging benchmark, retrieval-format benchmark, multiple-format benchmark), and other various judging extensions (grading single answer, multi-turn chat).

Generalize to Various Judging Tasks. To further validate the judging performance on questions with specific categories, we present the judging results of JudgeLM-33B on these questions, i.e., coding, common-sense, math, roleplay, and writing. Table 12 shows that JudgeLM can handle the judging tasks of various categories. We also find that the judging performance of math questions is slightly lower than coding and common-sense questions. However we think it is a common problem of large language models (Imani et al., 2023), and future advancement on base models (Yu et al., 2023a; Luo et al., 2023) would alleviate this problem.

Table 12: Performance of JudgeLM-33B with specific categories on JudgeLM *val* set.

	Agreement \uparrow (w/ GPT-4)	Consistency \uparrow (w/ swap.)	Bias \downarrow toward 1st	Bias \downarrow toward 2nd	Delta Bias \downarrow
<i>coding</i>					
val w/o ref	88.08	88.60	6.22	5.18	1.04
val w/ ref	88.83	91.37	3.55	5.08	1.53
<i>common-sense</i>					
val w/o ref	88.41	90.43	7.25	2.32	4.93
val w/ ref	90.37	92.35	4.53	3.12	1.41
<i>math</i>					
val w/o ref	86.45	84.08	7.76	8.16	0.40
val w/ ref	86.81	87.85	4.45	7.69	3.24
<i>croleplay</i>					
val w/o ref	88.00	88.00	6.67	5.33	1.34
val w/ ref	88.72	89.12	5.01	5.87	0.86
<i>writing</i>					
val w/o ref	87.33	92.36	3.25	4.39	1.14
val w/ ref	89.11	92.83	3.67	3.50	0.17

Generalize to Multimodal Judging Benchmark. Traditional multimodal evaluation needs prediction to match the ground truth exactly. For some open-ended questions, a human-like evaluator is needed to determine whether the prediction is close to the ground truth range. Modern multimodal, such as MM-Vet (Yu et al., 2023b) and Prometheus-Vision (Lee et al., 2024), which use GPT-4V, GPT-4 or GPT-3.5 as judges. The API-based judge takes the question text, ground-truth text, the model’s prediction, and optional input image as input, and makes judgments based on them. Our JudgeLM also provides good practice for such a multimodal evaluation by a slightly modified template as shown in Fig. 7. Thanks to its capacity to judge open-ended answers, our JudgeLM can also perform well in judging multimodal models, as shown in Fig. 21.

We further conduct experiments to evaluate JudgeLM’s ability to judge multimodal models when compared with close-sourced LLM, i.e., GPT-3.5 and GPT-4. We first use GPT-4, GPT-3.5, and JudgeLM to judge the LLaVA’s output (Liu et al., 2023), respectively. Then, we collect judgments from human annotators, whose judgments include three situations: completely correct, semi-correct, and completely wrong. Last, we compute the metrics between the LLM judges’ judgments and human judgments, as shown in Table 13. It can be observed that JudgeLM outperforms GPT-4 (0-shot) and GPT-3.5 (7-shot). Besides, JudgeLM achieves 2.5% higher precision than GPT-4 (7-shot). The encouraging results demonstrate the generalization ability of JudgeLM in dealing with multimodal judging. Furthermore, JudgeLM can use large multimodal models, e.g., LLaVA (Liu et al., 2023), as the backbone for better processing the multimodal judging. We leave it as a future work.

Table 13: JudgeLM zero-shot evaluation results on human-annotated MM-Vet benchmark.

Methods	Agreement \uparrow (w/ Human)	Precision \uparrow (w/ Human)	Recall \uparrow (w/ Human)	F1 \uparrow (w/ Human)
GPT-4 (7-shot)	95.58	88.63	87.79	88.04
GPT-4 (0-shot)	86.70	79.75	86.41	81.81
GPT-3.5 (7-shot)	83.03	76.14	74.84	73.62
JudgeLM-33B (0-shot)	91.74	91.08	85.58	87.26

Generalize to Out-of-distribution ToxicChat Benchmark. To further evaluate the generalization ability of the proposed JudgeLM, we selected an out-of-distribution benchmark, i.e., ToxicChat (Lin et al., 2023), for evaluation. Following the guidelines provided in the ToxicChat dataset, we conducted experiments on the latest test set (0124) of ToxicChat, comparing OpenAI Moderation, the GPT-4 teacher, and our proposed JudgeLM. OpenAI Moderation is an API trained on publicly available toxicity datasets, primarily sourced from social media. For both the GPT-4 teacher and JudgeLM, we used the same templates and thresholds. As shown in Table 14, our proposed JudgeLM achieves superior precision and comparable accuracy to the specialist model, i.e., OpenAI Moderation. These results demonstrate that JudgeLM can further generalize to out-of-distribution datasets such as ToxicChat.

Table 14: JudgeLM zero-shot evaluation results on toxic-chat test set.

Methods	Accuracy \uparrow	Precision \uparrow	Recall \uparrow	F1 \uparrow
<i>Specialist API-based Method</i>				
OpenAI Moderation	89.70	54.76	69.89	61.41
<i>Generalist API-based Method</i>				
GPT-4	88.08	52.17	73.20	60.92
<i>Open-sourced Method</i>				
JudgeLM-33B	89.66	58.79	61.88	60.30

Generalize to Retrieval-format Benchmark. In real-world applications, we do not always have well-organized reference answers for judging. To evaluate the capability of JudgeLM in dealing with this situation, we inject the original reference answers into a randomly selected paragraph. As shown in Table 15, we select paragraphs with different words, and evaluate JudgeLM-33B with the injected paragraphs as references in a zero-shot setting. The results show that JudgeLM can retrieve the correct answers from the paragraphs and make judgments based on them. When the words of paragraphs increase to 400, JudgeLM faces a maximum drop of 3.73% agreement and 3.37% consistency. The results demonstrate that JudgeLM is promising for utilizing JudgeLM to deal with unstructured references or judge in the retrieved form.

Table 15: Performance of JudgeLM-33B with injected paragraphs as references on JudgeLM *val* set.

Reference Paragraph	Agreement \uparrow (w/ GPT-4)	Consistency \uparrow (w/ swap.)	Bias \downarrow toward 1st	Bias \downarrow toward 2nd	Delta Bias \downarrow
No	89.32	92.37	3.62	4.01	0.39
50 words	87.78	92.35	3.00	4.65	1.65
100 words	87.69	91.84	2.62	5.54	2.92
200 words	86.77	90.48	2.70	6.82	4.12
300 words	86.25	89.26	3.13	7.61	4.48
400 words	85.59	89.00	2.98	8.02	5.04

Generalize to Multiple-format benchmark. To get the optimal ranking for N answers from different LLMs, other judge models need to call the model $O(n^2)$ times to get the full matrix, which is a much less efficient solution. We attempt to resolve this limitation by extending our JudgeLM to

process multiple answers at the same time. We first need to modify the template as shown in Fig. 5. As shown in Fig. 18, JudgeLM can judge and rank the multiple answers within the context limit of LLM.

We further conduct experiments to evaluate the consistency in the judging form of answer pairs and multiple answers. We first generate answers on JudgeLM *val* set through 3 LLMs, i.e., Vicuna-13B, LLaMA-7B, and alpaca-7B, for evaluation. Then we use pairwise judging and multiple judging to grade answers and rank them, respectively. Last, we compute the consistency between the two ranking results. Please note that ‘Error Rate@2’ indicates the position orderings of two answers are different between the result of paired judgment and the result of multiple judgment, and ‘Error Rate@3’ means the position orderings of three answers are different. Table 16 shows that consistency between judging pairwise and judging multiple can reach 93.48%, and only 0.14% results are totally wrong. The results are impressive but the 6.38% of ‘Error Rate@2’ also shows room for improvement as well, which could be addressed by the further improvement of JudgeLM’s self-consistency.

Table 16: Performance of JudgeLM-33B in judging multiple answers on JudgeLM *val* set. We calculate the consistency between the pairwise judging results and multiple judging ones.

	Consistency \uparrow (w/ pairwise)	Error Rate@2 \downarrow (w/ pairwise)	Error Rate@3 \downarrow (w/ pairwise)
JudgeLM-33B multipile	93.48	6.38	0.14

Table 17: Comparison with advanced reward models on RewardBench.

Model	Score	Chat	Hard	Safety	Reason
Closed-source Models					
GPT-3.5-turbo-0125	64.5	92.2	44.5	62.3	59.1
Powerful Reward Models.					
Prometheus-8 \times 7B-v2.0	75.3	93	47.1	83.5	77.4
Prometheus-7B-v2.0	72.5	85.5	49.1	78.7	76.5
UltraRM-13B	67.6	96.4	55.5	56.0	62.4
TIGERScore-13B	35.6	35.2	32.9	41.5	32.7
Llama-2-based Models.					
Tulu-2-dpo-70B	79.0	97.5	60.5	83.9	74.1
Tulu-2-dpo-13B	76.4	95.8	58.3	78.2	73.2
Tulu-2-dpo-7B	74.7	97.5	56.1	73.3	71.8
Qwen1.5-based Models.					
Qwen1.5-72B-Chat	71.5	62.3	66.0	72.0	85.5
Qwen1.5-14B-Chat	73.4	57.3	70.2	76.3	89.6
Qwen1.5-7B-Chat	72.0	53.6	69.1	74.8	90.4
Ours.					
JudgeLM-7B	78.5	92.2	56.1	83.2	82.3

Generalize to Single Answer Grading. The Concurrent judge method (Wang et al., 2023) usually judges a pair of answers to decide which one is better or tie but they lack the ability to evaluate a single answer. Thanks to our judging mode of scoring first and then calculating the judging results, our JudgeLM provides an alternative practice to grade a single answer by slightly modifying the template as shown in Fig. 5. Putting the reference answer in the first position and giving it a full grade as a prior, JudgeLM can give quantitative fine-grained evaluations as shown in Fig. 17.

The capability of grading a single answer is an important extension, which only relies the text-form prediction and ground truth to make judgments. For example, the following extension “Judging multimodal models” is also based on this capability.

Generalize to Reward Model. We further compare the proposed JudgeLM with closed-source methods, powerful reward models, Llama-2-based reward methods (Touvron et al., 2023b; Iverson

et al., 2023), and Qwen-1.5-based reward methods (Bai et al., 2023) on the requested reward model benchmark as shown in Table 17. Following the evaluation manner of GPT-3.5-turbo-0125 and Prometheus series (Kim et al., 2023) in RewardBench (Lambert et al., 2024), we evaluate the models among 4 subsets, i.e., Chat, (Chat) Hard, Safety, and Reasoning, and present averaged score in the Score column. The proposed JudgeLM-7B outperforms the GPT-3.5-turbo-0125, the Prometheus series reward models (Kim et al., 2023), UltraRM-13B (Cui et al., 2023), TIGERScore-13B (Jiang et al., 2023), Tulu-2-dpo-13B (Iverson et al., 2023), Tulu-2-dpo-7B (Iverson et al., 2023), and Qwen1.5-based reward models (Bai et al., 2023). Besides, JudgeLM-7B even achieves similar performance to Tulu-2-dpo-70B (Iverson et al., 2023). Noting the RewardBench paper mentions that involving Llama-3 as the base model can significantly improve the metrics on Hard and Reasoning, we leave it as future work.

Multi-turn Chat about Judgments. It is worth noting that fine-tuning with judge samples does not compromise the multi-turn chat ability extended from base models. As illustrated in Fig. 19 and Fig. 20, our JudgeLM retains the capability to engage in meaningful dialogues with users, providing them with a richer context, detailed information, additional examples, and specific details.

A.4 MORE DISCUSSION

Table 18: Comparison of different base models for JudgeLM-7B on JudgeLM *val* set.

Base Models (for JudgeLM-7B)	Agreement \uparrow (w/ GPT-4)	Precision \uparrow (w/ GPT-4)	Recall \uparrow (w/ GPT-4)	F1 \uparrow (w/ GPT-4)	Consistency \uparrow (w/ swap.)
<i>Judge w/o reference.</i>					
Vicuna	81.11	69.67	78.39	72.21	83.57
LLaMA2-chat	83.87	73.43	80.06	75.91	85.17
<i>Judge w/ reference.</i>					
Vicuna	84.08	75.92	82.55	78.28	84.46
LLaMA2-chat	86.60	79.47	83.11	81.02	87.74

Format Bias As shown in Table 16, it can be seen that the judging of multiple answers does not receive a significant performance drop. We hold the viewpoint that judging multiple answers is an easy extension for JudgeLM, which does not change the basis for judging. As mentioned in ‘4 Inherent Biases - Format Bias’, format bias means the model judging basis changes from pre-trained knowledge to reference, or vice versa. So, judging in mismatched situations faces format bias but judging multiple answers does not.

Other Human-annotated benchmarks For a fair comparison, we also evaluate JudgeLM on the PandaLM *test* set in a zero-shot setting. The PandaLM *train* and *test* sets are annotated by GPT3.5 and humans, respectively. As shown in Table 2, the zero-shot results of JudgeLM also outperform other judging methods, i.e., PandaLM, GPT-3.5, and GPT-4. Furthermore, JudgeLM also achieves a superior 0-shot judging performance on the multimodal benchmark with human annotation, i.e., MM-Vet, as shown in Table 13.

Reasoning Ability of LLM Judges Nowadays, NLP researchers are still struggling with proposing LLMs with superior reasoning abilities. JudgeLM also needs the proposed reference sup method to enhance the judging ability for out-of-domain or counterfactual tasks, as shown in Fig. 11 and Fig. 16. Notably, the proposed JudgeLM can benefit from stronger foundation LLMs, e.g., the LLaMA2-7B-Chat-based (Touvron et al., 2023b) JudgeLM outperforms the original JudgeLM-7B on all metrics, as shown in Table 18. The research of judge models is critical for the development of LLMs and can benefit from advanced LLMs, establishing a positive cycle.

Critiques for Judgements Beyond using LLMs to compare answer pairs and generate reasons, the critique and correction of these reasons have become increasingly important topics. This approach allows LLMs to reassess their generated reasons in multiple rounds, thereby enhancing judging accuracy. Works like UltraCM, Auto-J, and Shepherd have reliably evaluated the quality of textual reasons. Recently, CriticBench has also provided a reliable benchmark to evaluate the reasons and evaluation abilities of LLMs.

For JudgeLM, its ability to generalize to multi-turn chat enables us to construct multi-turn judgement critique data by combining data samples without references and those with references. Through two rounds of judge Q&A, i.e., without reference and with reference, JudgeLM can acquire the capability to critique its own judgments. We leave these experiments for future work.

Reference Drop as an Independent Method We think the reference drop is an independent and significant method. At first, we argue that judging with or without references are two sub-benchmarks, which require judges to make judgments with internal knowledge or by comparing LLM-generated answers with a reference answer, respectively. The reference drop is not only a simple but effective hyper-parameter, but also an important method that bridges the two sub-benchmarks, which enables the JudgeLM to make judgments in different situations.

Table 19: Comparison between PandaLM and JudgeLM components in terms of datasets and methods.

Base Model	Data	Method	val w/ ref?	Agreement \uparrow	Consistency \uparrow
<i>PandaLM baseline.</i>					
LLaMA	+ 300K PandaLM data		N	68.61	74.78
<i>change to JudgeLM data.</i>					
LLaMA	+3.5k JudgeLM data		N	71.30	69.59
<i>w/ the proposed methods.</i>					
LLaMA	+3.5k JudgeLM data	+swap aug	N	72.41	73.50
LLaMA	+3.5k JudgeLM data	+ref sup	Y	75.15	74.08
LLaMA	+3.5k JudgeLM data	+ref drop	Y	75.93	74.77
<i>w/ all proposed methods.</i>					
LLaMA	+3.5k JudgeLM data	+ all	N	75.01	76.28
LLaMA	+3.5k JudgeLM data	+ all	Y	78.10	79.50

Differences between PandaLM and JudgeLM To fairly assess the impact of our proposed dataset and methods, we conducted experiments using the PandaLM baseline with LLaMA-7B as the base model. As shown in Table 19, our dataset and methods both provide significant improvements.

Compared with PandaLM, our method has these different novelties:

- We introduce a **high-quality, large-scale dataset for judge models**, enriched with diverse seed tasks, LLMs-generated answers, and detailed judgments from GPT-4, laying the foundation for future LLMs evaluating research.
- We analyze the **biases inherent to LLM judge fine-tuning** and introduce a **series of methods** to address them. Our methods significantly improve the consistency of the model in different cases, making the JudgeLM more reliable and flexible.
- The proposed **judging pattern, i.e., grading, judging, and reasoning**, makes judging efficient, which only needs little time to grade and judge, and generates time-consuming reasons optionally.

Furthermore, other contributions which differ from PandaLM are as follows:

- We analyze the **finer scaling ability** of the language model judge, and **the scales of training data**, i.e., JudgeLM-7B, JudgeLM-13B, JudgeLM-33B, **3.5k-data, 10k-data, 30k-data, and 100k-data**, for evaluating LLMs in open-ended scenarios. The JudgeLM-33B-100K even **exceeds the humans’ judging agreement**.
- The proposed JudgeLM presents **extended capabilities** as shown in Fig. 1b, including grading single answers, judging multiple answers, judging multimodal models, multi-turn chat, and judging with injected paragraphs.

Specifically, the proposed JudgeLM presents generalization ability to seven different judging areas:

- Generalize to **19 various judging tasks**, including coding, common-sense, math, roleplay, writing, etc.

- Generalize to **human-annotated benchmarks**, such as the PandaLM test set and MM-Vet benchmark.
- Generalize to **multimodal judging benchmark**, such as MM-Vet benchmark.
- Generalize to **retrieval-format benchmark** which injects original reference answers into paragraphs with different words.
- Generalize to **multiple-format benchmark** which judges multiple answers at the same time.
- Generalize to **single-answer grading**.
- Generalize to **multi-turn chat about judgments**.

GPT-4 Distilled Data Evaluating Large Language Models (LLMs) in open-ended scenarios is challenging because existing benchmarks and metrics can not measure them comprehensively. Because the GPT-4-based judge can judge LLMs like a human expert, much concurrent work delving into curating training data (Li et al., 2023a; Kim et al., 2023; Cui et al., 2023; Xu et al., 2023; Jiang et al., 2023; Wang et al., 2023) and benchmarks (Lambert et al., 2024; Zheng et al., 2023) with the help of the closed-source LLMs, such as GPT-4 and GPT-3.5.

However, the GPT-4 teacher also faces inherent biases. Firstly, GPT-4’s training data may contain cultural, societal, and linguistic biases. These biases may influence the GPT-4’s judgment and lead to skewed evaluations. To mitigate these possible biases, the authors of this work are involved in double-checking to ensure the judgments from the GPT-4 teacher are accurate, objective, and unbiased. Secondly, the GPT-4’s judgments also contain position bias and knowledge bias (Zheng et al., 2023). To address these problems, we introduce swap augmentation and reference support in fine-tuning LLMs as judges, which significantly improves the consistency and accuracy of fine-tuned judges.

Does JudgeLM favor GPT-4? Thank you for discussing this interesting phenomenon. We carefully conducted experiments between GPT-4 and GPT-3.5 to analyze the potential favoring of GPT-4 answers by JudgeLM. As shown in Table 20, GPT-4 wins 59.0% of pairwise comparisons, with only 16.2% of wins for GPT-3.5. We further conducted a sampling analysis to identify the following contributing factors:

- **Alignment with Prompt Requirements:** As shown in the judging templates (Fig. 3, Fig. 4, Fig. 5, Fig. 6, and Fig. 7), JudgeLM evaluates responses based on structured criteria, such as relevance and level of detail. Our analysis shows that GPT-4 answers tend to align better with these requirements compared to GPT-3.5 answers.
- **Inherent Quality Difference:** A sampling analysis of 500 cases (approximately 16.9% of the GPT-4 win cases) showed that in 482 instances (96.4%), GPT-4 answers were more accurate, detailed, and contextually relevant than GPT-3.5 answers. This analysis underscores that GPT-4 win cases are overwhelmingly attributed to the higher answer quality, rather than the preference from JudgeLM.

Moreover, the sample analysis shows that when the quality of the answers to GPT-4 and GPT-3.5 are similar, JudgeLM tends to give similar scores, resulting in a Tie. These results indicate that GPT-4 answers win more due to their better relevance, high level of detail, and high quality.

Table 20: Quantitative comparison results between GPT-4 and GPT-3.5.

	GPT4 win	Tie	GPT3.5 win
GPT4 v.s. GPT-3.5	59.00%	24.80%	16.20%

Reliability of GPT-4-annotated Data. We conduct more experiments to further evaluate the reliability of GPT-4’s annotation. In this experiment setting, we set annotations provided by Human 1 in our benchmark as ground truth. Then we calculate the agreement of JudgeLM-33B, GPT-4, and Human 2 as shown in Table 21. These results demonstrate that GPT-4 achieves higher agreement with the ground truth compared to Human 2. llm-as-a-judge (Zheng et al., 2023) shows similar results, which means GPT-4 teacher’s judgments can align with human evaluators closely and can serve as a human-like teacher judge to provide high-quality and reliable judgments.

Table 21: Agreement evaluation of JudgeLM-33B, GPT-4, and Human, with another Human’s judgments as ground truth.

	JudgeLM-33B	GPT-4	Human 2
Ground Truth (Human 1)	90.72	84.48	79.82

Future Work about Training Queries Distribution. The distribution of training queries is a key factor in shaping the evaluation capabilities of Judge LLMs. While our current dataset was designed to ensure task diversity, MixEval (Ni et al., 2024b) and MixEval-X (Ni et al., 2024a) give us more insight, i.e., aligning the query distribution more closely with real-world user queries could further enhance the model’s fairness and relevance. We leave it as a promising future work.

A.5 PROMPT TEMPLATES

We list all the prompt templates we used.

You are a helpful and precise assistant for checking the quality of the answer.

[Question]
{question}

[The Start of Assistant 1's Answer]
{answer_1}
[The End of Assistant 1's Answer]

[The Start of Assistant 2's Answer]
{answer_2}
[The End of Assistant 2's Answer]

[System]
We would like to request your feedback on the performance of two AI assistants in response to the user question displayed above.
Please rate the helpfulness, relevance, accuracy, level of details of their responses. Each assistant receives an overall score on a scale of 1 to 10, where a higher score indicates better overall performance.
Please first output a single line containing only two values indicating the scores for Assistant 1 and 2, respectively. The two scores are separated by a space. In the subsequent line, please provide a comprehensive explanation of your evaluation, avoiding any potential bias and ensuring that the order in which the responses were presented does not affect your judgment.

Figure 3: The template for judging answers without the reference.

A.6 CASE STUDIES

We list several case studies.

1242
 1243
 1244 You are a helpful and precise assistant for checking the quality of the answer.
 1245 [Question]
 1246 {question}
 1247 [Reference Answer]
 1248 {reference}
 1249 [The Start of Assistant 1's Answer]
 1250 {answer_1}
 1251 [The End of Assistant 1's Answer]
 1252
 1253 [The Start of Assistant 2's Answer]
 1254 {answer_2}
 1255 [The End of Assistant 2's Answer]
 1256
 1257 [System]
 1258 We would like to request your feedback on the performance of two AI assistants in response to the
 1259 user question displayed above.
 1260 Based on the reference answer, please rate the helpfulness, relevance, accuracy, level of details of
 1261 their responses. Each assistant receives an overall score on a scale of 1 to 10, where a higher score
 1262 indicates better overall performance.
 1263 Please first output a single line containing only two values indicating the scores for Assistant 1 and 2,
 1264 respectively. The two scores are separated by a space. In the subsequent line, please provide a
 1265 comprehensive explanation of your evaluation, avoiding any potential bias and ensuring that the
 1266 order in which the responses were presented does not affect your judgment.

Figure 4: The template for judging answers with the reference.

1267
 1268
 1269
 1270 You are a helpful and precise assistant for checking the quality of the answer.
 1271 [Question]
 1272 {question}
 1273
 1274 [The Start of Assistant 1's Answer]
 1275 {reference}
 1276 [The End of Assistant 1's Answer]
 1277
 1278 [The Start of Assistant 2's Answer]
 1279 {single answer}
 1280 [The End of Assistant 2's Answer]
 1281
 1282 [System]
 1283 We would like to request your feedback on the performance of two AI assistants in response to the
 1284 user question displayed above.
 1285 Please rate the helpfulness, relevance, accuracy, level of details of their responses. Each assistant
 1286 receives an overall score on a scale of 1 to 10, where a higher score indicates better overall
 1287 performance.
 1288 Please first output a single line containing only two values indicating the scores for Assistant 1 and
 1289 2, respectively. The two scores are separated by a space. In the subsequent line, please provide a
 1290 comprehensive explanation of your evaluation, avoiding any potential bias and ensuring that the
 1291 order in which the responses were presented does not affect your judgment.
 1292
 1293 [Response]
 1294 10
 1295

Figure 5: The template for grading a single answer. We set the reference answer in the position of Answer 1. Then, we set the score of the reference answer to 10. Last, the JudgeLM outputs the score of the single answer with such a prior.

1296
1297
1298 You are a helpful and precise assistant for checking the quality of the answer.
1299 [Question]
1300 {question}
1301
1302 [The Start of Assistant 1's Answer]
1303 {answer_1}
1304 [The End of Assistant 1's Answer]
1305
1306 [The Start of Assistant 2's Answer]
1307 {answer_2}
1308 [The End of Assistant 2's Answer]
1309
1310 [The Start of Assistant 3's Answer]
1311 {answer_3}
1312 [The End of Assistant 3's Answer]
1313
1314 [System]
1315 We would like to request your feedback on the performance of **three** AI assistants in response to the
1316 user question displayed above.
1317 Please rate the helpfulness, relevance, accuracy, level of details of their responses. Each assistant
1318 receives an overall score on a scale of 1 to 10, where a higher score indicates better overall
1319 performance.
1320 Please first output a single line containing only **three** values indicating the scores for **Assistant 1, 2**
1321 **and 3**, respectively. The **three** scores are separated by a space. In the subsequent line, please provide
1322 a comprehensive explanation of your evaluation, avoiding any potential bias and ensuring that the
1323 order in which the responses were presented does not affect your judgment.

Figure 6: The template for judging multiple answers.

1324
1325
1326 Please evaluate the following **visual-based question-answer** pair:
1327
1328 [Question]
1329 {question}
1330
1331 [Reference Answer]
1332 {reference}
1333
1334 [The Start of Assistant 1's Answer]
1335 {answer_1}
1336 [The End of Assistant 1's Answer]
1337
1338 [The Start of Assistant 2's Answer]
1339 {answer_2}
1340 [The End of Assistant 2's Answer]
1341
1342 [System]
1343 Your task is to compare the predicted answer with the correct answer and determine if they match
1344 meaningfully. To accomplish the task, you must :
1345 1. Focus on the meaningful match between the predicted answer and the correct answer.
1346 2. Consider synonyms or paraphrases as valid matches.
1347 3. Evaluate the correctness of the prediction compared to the answer.
1348 4. If there are multiple correct answers, the predicted answer is considered correct as long as it is
1349 close to any of the answers

Figure 7: The template for multimodal judging.

1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403

Input

Question
Categorize a list of flowers.
Lilac, Daisy, Marigold, Chrysanthemum

Answer 1
Lilac: Shrub
Daisy: Herbaceous Perennial
Marigold: Annual
Chrysanthemum: Perennial

Answer 2
Flower:
- Lilac
- Daisy
- Marigold
- Chrysanthemum

Our Judgement Output (where answer 1 is placed in the first position)

Answer 1's Score: 8 **Answer 2's Score: 6**
Assistant 1 provided a more detailed and accurate response, correctly categorizing the flowers as shrubs, herbaceous perennials, annuals, and perennials. The assistant also provided a brief explanation of what these categories mean, which adds to the helpfulness and relevance of the response. However, the assistant could have provided more information about the characteristics of these flowers, such as their size, growth habit, and blooming time. On the other hand, Assistant 2 did not provide any information about the flowers' categories. The assistant simply listed the flowers without any additional information or context. While this response is technically correct, it lacks the detail and context that would make it more helpful and informative.

Our Judgement Output (where answer 2 is placed in the first position)

Answer 2's Score: 8 **Answer 1's Score: 6**
Assistant 2's response is concise and accurate, correctly categorizing the flowers as Lilac, Daisy, Marigold, and Chrysanthemum. However, the assistant could have provided more detail or explanation about the characteristics of each flower, which would have made the response more helpful. Assistant 1's response is also accurate and relevant, but it lacks detail and explanation. The assistant categorizes the flowers as Lilac (Shrub), Daisy (Herbaceous Perennial), Marigold (Annual), and Chrysanthemum (Perennial). However, these categories are not commonly used in the horticultural industry, and the assistant does not provide any explanation or context for these categories. This makes the response less helpful and informative.

Figure 8: Bad judgment caused by position bias. The answer placed in the first position always gets a higher score. The judge models generate reasons as possible from the perspective of making the scores reasonable.

1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457

Input

Question
Categorize a list of flowers.
Lilac, Daisy, Marigold, Chrysanthemum

Answer 1
Lilac: Shrub
Daisy: Herbaceous Perennial
Marigold: Annual
Chrysanthemum: Perennial

Answer 2
Flower:
- Lilac
- Daisy
- Marigold
- Chrysanthemum

Our Judgement Output (where answer 1 is placed in the first position)

Answer 1's Score: 8 **Answer 2's Score: 2**
Assistant 1's response is more helpful and accurate as it provides a categorization for each flower listed in the question. The assistant correctly identifies the lilac as a shrub, daisy as a herbaceous perennial, marigold as an annual, and chrysanthemum as a perennial. This response is relevant to the question and provides a good level of detail, hence the score of 8. On the other hand, Assistant 2's response is not helpful or accurate. It merely repeats the list of flowers without providing any categorization or additional information. The response is not relevant to the question and lacks detail, hence the low score of 2.

Our Judgement Output (where answer 2 is placed in the first position)

Answer 2's Score: 2 **Answer 1's Score: 8**
Assistant 1's response is more helpful and relevant to the question. The user asked to categorize a list of flowers, and Assistant 2 correctly categorized each flower by its life cycle (annual, perennial, etc.). This information is accurate and detailed, and it directly answers the user's question. Therefore, Assistant 2 receives a score of 8. On the other hand, Assistant 2's response is not as helpful or relevant. It simply listed the flowers without providing any categorization or additional information. This response does not answer the user's question and lacks detail, so Assistant 1 receives a score of 2.

Figure 9: Good judgment generated by the judge fine-tuned with swap augmentation. The judge can give judgments based on the content of answers rather than a certain position. The reason is convincing and reasonable.

1458
 1459
 1460
 1461
 1462
 1463
 1464
 1465
 1466
 1467
 1468
 1469
 1470
 1471
 1472
 1473
 1474
 1475
 1476
 1477
 1478
 1479
 1480
 1481
 1482
 1483
 1484
 1485
 1486
 1487
 1488
 1489
 1490
 1491
 1492
 1493
 1494
 1495
 1496
 1497
 1498
 1499
 1500
 1501
 1502
 1503
 1504
 1505
 1506
 1507
 1508
 1509
 1510
 1511

Input

Question
 Determine which companies are primarily cloud-software companies and which are semiconductor companies: Intel, Google, Workday, Zscaler, AMD, NVIDIA, and Texas Instruments.

Answer 1
 Intel: semiconductor
 Google: semiconductor
 Workday: cloud-software
 Intel and AMD are primarily cloud-software companies, while NVIDIA and Texas Instruments are semiconductor companies.
 AMD: semiconductor
 NVIDIA: semiconductor
 Texas Instruments: semiconductor

Answer 2
 Intel and AMD are primarily cloud-software companies, while NVIDIA and Texas Instruments are semiconductor companies.

Our Judgement Output

Answer 1's Score: 2 **Answer 2's Score: 8**
 Assistant 1's answer is incorrect and confusing. Intel and AMD are not primarily cloud-software companies, and NVIDIA and Texas Instruments are not semiconductor companies. The information provided is not accurate or relevant to the question asked. On the other hand, Assistant 2's answer is more accurate and relevant. Intel and AMD are indeed primarily cloud-software companies, and NVIDIA and Texas Instruments are semiconductor companies. However, the answer could have been more detailed, explaining why these companies are classified as such.

Figure 10: Bad judgment caused by knowledge bias. This seed task is out of the judge model's pre-trained knowledge, so it can not be correctly judged by the judge model. The judge model gives contradictory reasons in the judgment.

1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565

Input

Question
Determine which companies are primarily cloud-software companies and which are semiconductor companies: Intel, Google, Workday, Zscaler, AMD, NVIDIA, and Texas Instruments.

Reference Answer
Intel, AMD, NVIDIA, and Texas Instruments are primarily semiconductor companies. Workday and Zscaler are fully cloud-software companies. Google is primarily a software company, however, they also develop custom-developed application-specific integrated circuits which are semiconductors."

Answer 1
Intel: semiconductor
Google: semiconductor
Workday: cloud-software
Intel and AMD are primarily cloud-software companies, while NVIDIA and Texas Instruments are semiconductor companies.
AMD: semiconductor
NVIDIA: semiconductor
Texas Instruments: semiconductor

Answer 2
Intel and AMD are primarily cloud-software companies, while NVIDIA and Texas Instruments are semiconductor companies.

Our Judgement Output

Answer 1's Score: 8 **Answer 2's Score: 3**
Assistant 2's answer is incorrect and misleading. They stated that Intel and AMD are primarily cloud-software companies, which is not true. Both Intel and AMD are semiconductor companies. Therefore, the accuracy, relevance, and helpfulness of Assistant 2's answer are low, resulting in a score of 3. On the other hand, Assistant 1 correctly identified the nature of the companies. They correctly identified Intel, AMD, NVIDIA, and Texas Instruments as semiconductor companies and Workday and Zscaler as cloud-software companies. However, they incorrectly identified Google as a semiconductor company, while Google is primarily a software company that also develops custom-developed application-specific integrated circuits which are semiconductors. Despite this minor error, Assistant 1's answer is much more accurate, relevant, and helpful than Assistant 2's, earning it a score of 8.

Figure 11: Good judgment generated by the judge model fine-tuned with reference support. Even though the judge model itself lacks related information, it can also give a reasonable judgment with the reference answer.

1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619

Input

Question
Generate a descriptive sentence to describe the painting
Monalisa

Answer 1
The Italian artist, Leonardo da Vinci created the most famous painting of all time. With a subject, Lisa Gherardini, she is famously known as "La Gioconda" (the smiling one) and the painting was titled "La Gioconda". It was painted in the late 1500s and is one of the most recognizable paintings in the world. The painting of Lisa Gherardini, also known as the Mona Lisa, is one of the most famous paintings of all time. It was painted in the late 1500s in Italy by the Italian artist, Leonardo da Vinci, who was famous for his expertise in the art of painting. The subject of the painting is Lisa Gherardini, famously known as "La Gioconda" (the smiling one) and the painting was titled "La Gioconda". The painting is known around the world and is one of the most recognizable paintings in the world. Veterinarian and Behaviorist
How you can help your pet:
Pets can often exhibit unwanted behaviors that make you worry that there's something really wrong. But the fact is, most problems stem from misunderstood communication. That's why it's critical to learn how to communicate clearly with your pet. I

Answer 2
The painting Monalisa was made by Leonardo da Vinci.

Our Good Judgment (JudgeLM trained without reference)

Answer 1's Score: 4 **Answer 2's Score: 7**
Assistant 1's response started off well, providing a detailed description of the painting "Monalisa" by Leonardo da Vinci. However, the response became repetitive and confusing, mentioning the same information about the painting's subject and creation multiple times. Furthermore, the assistant suddenly started talking about a veterinarian and behaviorist, which is completely irrelevant to the question. Therefore, the score is 4. Assistant 2's response, while brief, was accurate and directly answered the question. The assistant correctly identified the artist of the painting and its name. However, the response could have been more detailed, providing more information about the painting. Therefore, the score is 7.

Our Bad Judgment (JudgeLM trained with reference)

Answer 1's Score: 2 **Answer 2's Score: 1**
Assistant 1's response is confusing and inaccurate. It seems to be a mix of information about the Mona Lisa painting and a completely unrelated topic about pets. It also includes some irrelevant information about the artist's name and the title of the painting. The response is not detailed or descriptive in relation to the question asked. Therefore, it gets a score of 2. Assistant 2's response is even less helpful. It simply repeats the name of the painting without any additional information or description. It does not answer the question at all, hence it gets a score of 1.

Figure 12: Bad judgment caused by format bias. For judging without reference, the judge model trained without reference is matched, so it performs well. However, the judge model trained with reference is mismatched, so it performs badly.

1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673

Input

Question
Generate a descriptive sentence to describe the painting
Monalisa

Reference Answer
The Mona Lisa painting is a half-length portrait, painted by Leonardo da Vinci, that depicts a seated woman with a slight smile, enigmatic expression, and intricate details in her attire, set against a hazy and dreamlike backdrop.

Answer 1
The Italian artist, Leonardo da Vinci created the most famous painting of all time. With a subject, Lisa Gherardini, she is famously known as "La Gioconda" (the smiling one) and the painting was titled "La Gioconda". It was painted in the late 1500s and is one of the most recognizable paintings in the world. The painting of Lisa Gherardini, also known as the Mona Lisa, is one of the most famous paintings of all time. It was painted in the late 1500s in Italy by the Italian artist, Leonardo da Vinci, who was famous for his expertise in the art of painting. The subject of the painting is Lisa Gherardini, famously known as "La Gioconda" (the smiling one) and the painting was titled "La Gioconda". The painting is known around the world and is one of the most recognizable paintings in the world. Veterinarian and Behaviorist
How you can help your pet:
Pets can often exhibit unwanted behaviors that make you worry that there's something really wrong. But the fact is, most problems stem from misunderstood communication. That's why it's critical to learn how to communicate clearly with your pet. I

Answer 2
The painting Monalisa was made by Leonardo da Vinci.

Our Bad Judgment (JudgeLM trained without reference)

Answer 1's Score: 8 **Answer 2's Score: 2**
Assistant 1 provided a detailed and accurate description of the Mona Lisa painting, including its creation by Leonardo da Vinci, its subject, and its title. The assistant also provided additional information about the painting's fame and the artist's expertise. However, the assistant's response was cut off at the end, which is why it didn't receive a perfect score. Assistant 2, on the other hand, did not provide any information about the Mona Lisa painting. The assistant simply repeated the name of the painting, which is not helpful or informative. Therefore, Assistant 2 receives a low score.

Our Good Judgment (JudgeLM trained with reference)

Answer 1's Score: 5 **Answer 2's Score: 7**
Assistant 1's response started off well, providing a detailed description of the Mona Lisa painting, including the painting artist's name, the subject of the painting, and its significance. However, Assistant 1's response became repetitive that mentioning the same information multiple times and suddenly shifted to a completely unrelated topic about pets, which is irrelevant to the question. Therefore, I would rate Assistant 1 a 5. Assistant 2's response was brief and to the point, correctly identifying Leonardo da Vinci as the artist who painted the Mona Lisa. However, it lacked detail and did not provide any additional information about the painting itself. Despite its brevity, Assistant 2's response was more relevant and accurate than Assistant 1's, so I would rate it a 7.

Figure 13: Bad judgment caused by format bias. For judging with reference, the judge model trained with reference is matched, so it performs well. However, the judge model trained without reference is mismatched, so it performs badly.

1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727

Input

Question

Generate a descriptive sentence to describe the painting
Monalisa

Reference Answer

The Mona Lisa painting is a half-length portrait, painted by Leonardo da Vinci, that depicts a seated woman with a slight smile, enigmatic expression, and intricate details in her attire, set against a hazy and dreamlike backdrop.

Answer 1

The Italian artist, Leonardo da Vinci created the most famous painting of all time. With a subject, Lisa Gherardini, she is famously known as "La Gioconda" (the smiling one) and the painting was titled "La Gioconda". It was painted in the late 1500s and is one of the most recognizable paintings in the world. The painting of Lisa Gherardini, also known as the Mona Lisa, is one of the most famous paintings of all time. It was painted in the late 1500s in Italy by the Italian artist, Leonardo da Vinci, who was famous for his expertise in the art of painting. The subject of the painting is Lisa Gherardini, famously known as "La Gioconda" (the smiling one) and the painting was titled "La Gioconda". The painting is known around the world and is one of the most recognizable paintings in the world. Veterinarian and Behaviorist

How you can help your pet:

Pets can often exhibit unwanted behaviors that make you worry that there's something really wrong. But the fact is, most problems stem from misunderstood communication. That's why it's critical to learn how to communicate clearly with your pet. I

Answer 2

The painting Monalisa was made by Leonardo da Vinci.

Our Good Judgment without reference (JudgeLM trained with reference drop)

Answer 1's Score: 4

Answer 2's Score: 6

Assistant 1's response started off well, providing a detailed description of the Mona Lisa, including the artist, the subject, and the time period. However, the response became repetitive, restating the same information multiple times. Additionally, the last part of the response is completely irrelevant to the question, discussing veterinary and behaviorist advice for pets. This significantly reduces the score for relevance and accuracy. Assistant 2's response, while brief, is accurate and relevant. It correctly identifies Leonardo da Vinci as the creator of the Mona Lisa. However, it lacks detail and does not provide any additional information about the painting, such as the subject or the time period, which would have made the response more helpful. Therefore, Assistant 2's response receives a slightly higher score than Assistant 1, but still not a high score overall due to the lack of detail.

Our Good Judgment with reference (JudgeLM trained with reference drop)

Answer 1's Score: 4

Answer 2's Score: 6

Assistant 1's response started off well, providing detailed information about the Mona Lisa painting, including the artist, the subject, and the time it was painted. However, the response became repetitive, mentioning the same details multiple times. Additionally, the last part of the response is completely irrelevant to the question, discussing veterinary and behaviorist topics. This significantly reduces the score for relevance and accuracy. Assistant 2's response, while accurate and relevant, lacks detail. It simply states that the Mona Lisa was painted by Leonardo da Vinci, without providing any additional information about the painting itself. This makes the response less helpful than it could be. However, it is still more relevant and accurate than Assistant 1's response, hence the higher score.

Figure 14: Good judgment generated by the judge model with reference drop, which addresses the preference for specific fine-tuning formats and gives fair judgments with or without reference.

1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781

Train sample without *swap aug.*

Input

Question
Create an acronym using the provided letters.
ABCDEF

Answer 1
FIDE

Answer 2
A Better Comprehension of Digital Education Fund

GPT-4 Judgement

Answer 1's Score: 2 **Answer 2's Score: 10**
Assistant 1's response is not helpful, relevant, or accurate. The user asked for an acronym using the letters ABCDEF, but Assistant 1 provided an acronym that only uses the letters FIDE, which is not what the user asked for. Therefore, **Assistant 1** receives a score of 2. On the other hand, **Assistant 2's** response is both helpful and accurate. The assistant provided an acronym that uses all the letters provided by the user, which is exactly what the user asked for. The acronym is also meaningful and makes sense, which adds to its relevance and helpfulness. Therefore, **Assistant 2** receives a score of 10.

Train sample with *swap aug.*

Input

Question
Create an acronym using the provided letters.
ABCDEF

Answer 1
A Better Comprehension of Digital Education Fund

Answer 2
FIDE

GPT-4 Judgement

Answer 1's Score: 10 **Answer 2's Score: 2**
Assistant 2's response is not helpful, relevant, or accurate. The user asked for an acronym using the letters ABCDEF, but Assistant 2 provided an acronym that only uses the letters FIDE, which is not what the user asked for. Therefore, **Assistant 2** receives a score of 2. On the other hand, **Assistant 1's** response is both helpful and accurate. The assistant provided an acronym that uses all the letters provided by the user, which is exactly what the user asked for. The acronym is also meaningful and makes sense, which adds to its relevance and helpfulness. Therefore, **Assistant 1** receives a score of 10.

Figure 15: An illustration of swap augmentation. We use swap augmentation to exchange the positions of answers, and our GPT-4-generated judgments can be modified correspondingly easily due to their structure.

1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835

Input

Question
There are five birds on a tree, and a person shoots one of the birds. How many birds are left on the tree?

Reference Answer 1
One bird was shot and dropped from the tree, leaving four birds remaining on the tree.

Reference Answer 2
All the birds have flown away from the tree due to being startled, so there are none left on the tree.

Answer 1
There are four birds left on the tree because one bird was shot and fell from the tree.

Answer 2
There are no birds left on the tree.

Our Judgement Output with Reference Answer 1

Answer 1's Score: 10 **Answer 2's Score: 1**
Assistant 1's answer is accurate, relevant, and helpful. Assistant 1's answer correctly states that there are four birds left on the tree after one is shot, which matches the reference answer. Therefore, it deserves a perfect score of 10. On the other hand, Assistant 2's answer is incorrect and misleading. Assistant 2's answer states that there are no birds left on the tree, which is not true according to the question. Therefore, it receives a score of 1.

Our Judgement Output with Reference Answer 2

Answer 1's Score: 3 **Answer 2's Score: 10**
Assistant 1's answer is incorrect. The question states that a person shoots one of the birds, which implies that the bird is killed, not simply startled and falls from the tree. Therefore, there would be four birds left on the tree, not five. However, the reference answer suggests that all the birds would have flown away due to being startled, which contradicts Assistant 1's answer. Therefore, Assistant 1's answer is not accurate or helpful. Assistant 2's answer is accurate, relevant, and helpful. The reference answer suggests that all the birds would have flown away due to being startled. Therefore Assistant 2's answer is correct.

Figure 16: An illustration of changing the reference answer to control model preference. When we change to a different reference answer, the model turns to prefer another answer.

1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889

Input

Question
Given a statement, identify the target audience of the statement.
Take a break from work and enjoy a bowl of ice cream.

Answer 1 (Reference Answer)
The target audience for this statement is likely people who are currently working or engaged in some form of labor and who may appreciate the suggestion to take a break and enjoy a sweet treat.

Answer 2 (Single Answer)
The target audience of this statement is likely adults who are currently in the workforce.

Our Judgement Output

Answer 1's Score: 10 **Answer 2's Score: 7**
Assistant 1 provided a detailed and comprehensive answer, analyzing the statement from different angles and considering the potential needs and desires of the target audience. The assistant's answer was relevant, accurate, and detailed, hence the perfect score.
Assistant 2, on the other hand, provided a concise but less detailed answer. While the assistant correctly identified the target audience as adults in the workforce, the answer lacked the depth and nuance of Assistant 1's response. Therefore, Assistant 2 receives a lower score.

Figure 17: An illustration of grading a single answer.

Input

Question
Given a statement, identify the target audience of the statement.
Take a break from work and enjoy a bowl of ice cream.

Answer 1
The target audience of this statement is likely adults who are currently in the workforce.

Answer 2
The target audience of the statement is professional athletes competing in a championship game.

Answer 3
This statement is likely directed at those who may be feeling stressed, overwhelmed, or in need of a brief respite from their work tasks. It suggests that they should pause their work for a while and treat themselves to a comforting bowl of ice cream as a way to relax and refresh before returning to their work duties.

Our Judgement Output

Answer 1's Score: 5 **Answer 2's Score: 1** **Answer 3's Score: 8**
Assistant 1's answer is not very accurate or detailed. The statement "Take a break from work and enjoy a bowl of ice cream." is not likely to be directed at adults in the workforce specifically. It could be directed at anyone who is working, regardless of their age or occupation. Therefore, the assistant's answer is not very helpful or relevant.
Assistant 2's answer is completely off the mark. The statement does not suggest that it is directed at professional athletes competing in a championship game. This answer is not accurate, relevant, or helpful.
Assistant 3's answer, on the other hand, is quite accurate and detailed. It correctly identifies that the statement is likely directed at people who are feeling stressed or overwhelmed by their work, and suggests that they should take a break and enjoy a bowl of ice cream. This answer is helpful, relevant, and accurate.

Figure 18: An illustration of judging multiple answers.

1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943

Input

Question
Given a statement, identify the target audience of the statement.
Take a break from work and enjoy a bowl of ice cream.

Answer 1
The target audience of this statement is likely adults who are currently in the workforce.

Answer 2
The target audience of the statement is professional athletes competing in a championship game.

Our Judgement Output

Answer 1's Score: 7 **Answer 2's Score: 1**
Assistant 1's answer is more relevant and accurate to the question. The statement "Take a break from work and enjoy a bowl of ice cream." is likely targeted at adults who are currently in the workforce. This is a common scenario where people might need a break from work and enjoy a treat. Therefore, Assistant 1's answer is helpful, relevant, and accurate. On the other hand, Assistant 2's answer is not relevant or accurate. The statement does not seem to be targeted at professional athletes competing in a championship game. Therefore, Assistant 2's answer is not helpful, relevant, or accurate.

JudgeLM Multi-turn Chat

Q: Can you provide a more detailed description of the circumstances in which this statement was made?
A: The statement "Take a break from work and enjoy a bowl of ice cream." could be made in a variety of circumstances. Here are a few examples:
1.A supervisor or manager might say this to their employees during a particularly busy or stressful period, encouraging them to take a break and recharge. This would be to ensure the employees' well-being and productivity.
2.A friend or colleague might suggest this during a lunch break or a break in the workday, as a way to relax and unwind. This would be a casual, friendly suggestion.
In all these scenarios, the target audience would be adults who are in the workforce. They are the ones who would be likely to relate to the statement and take it as a suggestion or a message.

Q: Can you provide an example of a statement where the target audience is teenagers?
A: Certainly! Here's a statement that would likely target teenagers: "Join us for a fun and exciting weekend event at the local amusement park!" This statement is likely to appeal to teenagers who are interested in fun activities, socializing with friends, and enjoying a weekend outing. The statement is relevant, accurate, and targets the teenage audience.

Q: Can you provide an example of a statement where the target audience is professional athletes competing in a championship game?
A: Certainly! Here's a statement that would likely target professional athletes competing in a championship game: "Join us for a special event to celebrate and honor the achievements of professional athletes competing in a championship game!" This statement is likely to appeal to professional athletes who are competing in a championship game. The statement is relevant, accurate, and targets the professional athletes competing in a championship game.

Figure 19: An illustration of multi-turn chat. Users can get more details, advice, examples, etc., by chatting with JudgeLM.

1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997

Input

Question
Given a statement, identify the target audience of the statement.
Take a break from work and enjoy a bowl of ice cream.

Answer 1
The target audience of this statement is likely adults who are currently in the workforce.

Answer 2
The target audience of the statement is professional athletes competing in a championship game.

Our Judgement Output

Answer 1's Score: 7 **Answer 2's Score: 1**
Assistant 1's answer is more relevant and accurate to the question. The statement "Take a break from work and enjoy a bowl of ice cream." is likely targeted at adults who are currently in the workforce. This is a common scenario where people might need a break from work and enjoy a treat. Therefore, Assistant 1's answer is helpful, relevant, and accurate. On the other hand, Assistant 2's answer is not relevant or accurate. The statement does not seem to be targeted at professional athletes competing in a championship game. Therefore, Assistant 2's answer is not helpful, relevant, or accurate.

JudgeLM Multi-turn Chat

Q: Why not give Assistant 1's answer a score of 10?
A: 10 would imply that the answer is perfect and there is no room for improvement. While Assistant 1's answer is accurate and relevant, it could have been more detailed by explaining why adults in the workforce are the target audience. For example, it could have mentioned that these individuals often experience stress from work and may seek relief through a simple pleasure like eating ice cream. Therefore, while Assistant 1's answer is good, it is not perfect, hence the score of 7.

Q: Can you give a possible statement for the specific group mentioned in Assistant 2's response?
A: Certainly, a possible statement for professional athletes competing in a championship game could be: "Recharge with a bowl of ice cream during your break from the intense game." This statement is tailored to the specific needs and circumstances of professional athletes, making it more relevant and helpful to this group.

Q: Thanks! I want to get another target audience for the original statement. Can you help me?
A: Of course! Another possible target audience for the original statement could be: "Students studying for exams or working on projects." This group might also appreciate a break with a bowl of ice cream, especially if they're feeling stressed or need a quick energy boost. This answer is also relevant and helpful.

Figure 20: An additional illustration of multi-turn chat. Users can get more details, advice, examples, etc., by chatting with JudgeLM.

1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051

Input

Question
This bike is a miniaturized version of what full-size model?

Reference Answer
harley

Answer 1
bicycle

Answer 2
The bike in the image is a miniropized version of a Harley-Davidson 1200.

Our Judgment Output

Answer 1's Score: 2 **Answer 2's Score: 8**

Assistant 1's answer is not helpful, relevant, accurate, or detailed. The assistant simply provided a word, "bicycle," which does not match the correct answer, "Harley." This assistant did not consider synonyms or paraphrases, evaluate the correctness of the prediction, or consider the possibility of multiple correct answers. Therefore, Assistant 1 receives a score of 2. Assistant 2's answer is more helpful, relevant, accurate, and detailed. The assistant provided a paraphrase of the correct answer, "Harley-Davidson 1200," which is a valid match. This assistant also considered synonyms, as "Harley-Davidson 1200" is a synonym for "Harley." However, the assistant could have been more precise by directly stating "Harley-Davidson 1200" instead of "the bike in the image is a miniropized version of a Harley-Davidson 1200." Therefore, Assistant 2 receives a score of 8.

Figure 21: An illustration of multimodal judging. Our JudgeLM has the capacity to judge the VQA task without images.

Input


Question
What is located to the right of the shampoo?

Reference Answer
conditioner

Answer 1 (Sampled from Reference Answer Set)
conditioner

Answer 2 (Generated by Multimodal Assistant)
There is a bottle of conditioner located to the right of the shampoo.

Question Image



Our Judgement Output

Answer 1's Score: 10 **Answer 2's Score: 10**

Both Assistant 1 and Assistant 2 provided accurate and relevant answers to the question. Assistant 1's answer was concise and directly answered the question, which is why it received a perfect score. Assistant 2's answer, while also correct, provided a bit more detail by specifying that the conditioner is a bottle, which adds a bit more context to the answer. This additional detail is why Assistant 2 also received a perfect score. Both assistants were helpful and precise in their responses.

Figure 22: An illustration of multimodal high-score grading on MM-Vet benchmark. The proposed JudgeLM can replace GPT-4 to grade multimodal answers.

2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105


Input	
Question	Question Image
What are the appliances in the kitchen in this floorplan?	
Reference Answer	
oven, and dishwasher	
Answer 1 (Sampled from Reference Answer Set)	
oven, and dishwasher	
Answer 2 (Generated by Multimodal Assistant)	
The appliances in the kitchen in this floorplan include a dishwasher and a refrigerator.	
Our Judgement Output	
Answer 1's Score: 10	Answer 2's Score: 5
Assistant 2's answer is not accurate because it mentions a refrigerator which is not in the reference answer. Therefore, it gets a score of 5. Assistant 1's answer is accurate and matches the reference answer exactly, so it gets a perfect score of 10	

Figure 23: An illustration of multimodal mid-score grading on MM-Vet benchmark. The proposed JudgeLM can replace GPT-4 to grade multimodal answers.

Input	
Question	Question Image
What is d in the last equation?	Solve the following equations:
Reference Answer	1) $8x + 11 = 4x + 14$
0.75, or =0.75, or 3/4	2) $7d - 4 = 11d - 9$
Answer 1 (Sampled from Reference Answer Set)	
3/4	
Answer 2 (Generated by Multimodal Assistant)	
x in the equation is $8x + 11 = 4x + 14$.	
Our Judgement Output	
Answer 1's Score: 10	Answer 2's Score: 2
Assistant 2's answer is incorrect and irrelevant to the question. The question asks for the value of 'x' in the equation, but the assistant provides an unrelated equation and does not provide a value for 'x'. Therefore, it receives a low score of 2. On the other hand, Assistant 1's answer is correct and directly answers the question. The value of 'x' in the equation 0.75, or =0.75, or 3/4 is indeed 3/4. Therefore, it receives a high score of 10.	

Figure 24: An illustration of multimodal low-score grading on MM-Vet benchmark. The proposed JudgeLM can replace GPT-4 to grade multimodal answers.