Thyme: Think Beyond Images

Anonymous Author(s)
Affiliation
Address
email

Abstract

Following OpenAI's introduction of the "thinking with images" concept, recent efforts have explored stimulating the use of visual information in the reasoning process to enhance model performance in perception and reasoning tasks. However, to the best of our knowledge, no open-source work currently offers a feature set as rich as proprietary models (OpenAI O3 [30]), which can perform diverse image manipulations and simultaneously enhance logical reasoning capabilities through code.

In this paper, we make a preliminary attempt in this direction by introducing Thyme (Think Beyond Images), a novel paradigm for enabling multimodal large language models to transcend existing "think with images" approaches by autonomously generating and executing diverse image processing and computational operations via executable code (Figure 2). This approach not only facilitates a rich, on-the-fly set of image manipulations (e.g., cropping, rotation, contrast enhancement), but also allows for mathematical computations, all while maintaining high autonomy in deciding when and how to apply these operations. We activate this capability through a two-stage training strategy: an initial Supervised Fine-Tuning (SFT) on a curated dataset of 500K samples to teach code generation, followed by a Reinforcement Learning (RL) phase to refine decision-making. For the RL stage, we manually collect and design high-resolution questionanswer pairs to increase the learning difficulty, and we propose GRPO-ATS (Group Relative Policy Optimization with Adaptive Temperature Sampling), an algorithm that applies distinct temperatures to text and code generation to balance reasoning exploration with code execution precision. We conduct extensive experimental analysis and ablation studies. As shown in Figure 1, comprehensive evaluations on nearly 20 benchmarks show that Thyme yields significant and consistent performance gains, particularly in challenging high-resolution perception and complex reasoning tasks.

29 1 Introduction

5

6

8

9

11

12

13

14

15

16

17

20

21

22

23

24

25

26

27

28

Recent years have witnessed considerable interest in enabling multimodal large language models (MLLMs) [2, 42, 38, 50, 40, 4, 10] to "think with images"—that is, to incorporate visual inputs as part of their reasoning process. Existing approaches to realize this capability generally fall into two categories. One category involves *thinking with generated images* methods [5, 56, 46], in which the model first generates an image to guide subsequent reasoning. This approach offers significant advantages in scenarios requiring imagination or auxiliary visual cues, such as drawing auxiliary lines to solve mathematical problems. However, generated images often suffer from quality limitations that hinder the preservation




Figure 1: **Benchmark performance of Thyme.** The comprehensive set of image manipulation capabilities enables Thyme to achieve significant improvements over the baseline in perception tasks. By leveraging its ability to convert complex mathematical reasoning into executable code, it consistently outperforms baselines in mathematical reasoning benchmarks. Furthermore, the observed gains across a wide range of general benchmarks further validate the effectiveness of our training approach.

of fine-grained original details, thus constraining improvements in core visual perception tasks. Moreover, the substantial computational cost associated with image generation results in considerable inference latency, which undermines real-time applicability. The other category focuses on *thinking with cropping*, in which the model is trained to select relevant image regions (e.g., by outputting bounding boxes [37, 59, 14, 34, 59, 67, 42]), which are 42 then cropped and processed externally. While this strategy enhances perception accuracy 43 and mitigates hallucination, its functionality remains relatively limited. Specifically, it can 44 only perform cropping through bounding box outputs, falling short of the multifunctionality 45 demonstrated by OpenAI's O3 [30], which supports a broader range of operations such as 46 rotation, contrast enhancement, and even coding. 47

To overcome these challenges, we propose a novel paradigm called **Th**ink Beyond I**m**ag**e**s (Thyme), illustrated in Figure 2, guided by four core principles:

Rich Functionality: Enables the model to support a wide range of common image operations such as cropping, scaling, rotating, and contrast enhancement, as well as complex mathematical computations.

53 54

55

71

- High Autonomy: Thyme exhibits high autonomy, capable of deciding whether to perform image operations, determining what operations to apply, and executing the functions by dynamically generating code — all without human intervention for specific tasks.
- Efficient End-to-End Training: We utilize an end-to-end supervised finetuning + reinforcement learning (SFT+RL) to minimize training costs and rapidly unlock diverse model capabilities. Notably, the SFT stage requires only 200 GPU hours to activate all the functionalities mentioned above, while the RL stage further strengthens these abilities.
- Significant and Stable Performance Gains: We evaluate nearly 20 benchmarks spanning three major categories: perception, reasoning, and general tasks. Under the Thyme paradigm, the model achieves consistent and substantial performance improvements across all these task categories.

64 To realize this vision, our technical roadmap comprises the following key components:

- ♦ SFT Data Construction: Leveraging over 4 million raw data sources, we curate a high-quality SFT dataset of approximately 500K samples encompassing diverse scenarios: (a)
 image operations and computations requiring no coding; (b) cropping of complex or high-resolution images; (c) correction of images rotated by large angles; (d) enhancement of low-contrast images; (e) tasks involving complex code-based computations to boost understanding; and (f) multi-turn interactive scenarios, such as iterative magnification.
 - ♦ **SFT Training Strategy:** To accommodate the diversity of functionality, we implement specific training schemes. Specifically, outputs and environment feedback from the sandbox




Figure 2: Overall pipeline of the Thyme, illustrating the interaction between the model and the sandbox for iterative reasoning and code execution. Key processes such as reasoning, code generation, sandbox execution, and result feedback are highlighted.

are masked during loss computation to prevent gradient contamination; only the model's last-round response in multi-turn dialogues is used for loss calculation; and annealing techniques are applied on long-tail complex computation samples to thoroughly activate the model's Thyme capabilities.

- **RL Data Construction.** Our RL dataset primarily consists of two parts. The first part involves filtering open-source data, which contains a mixture of perception and reasoning tasks. However, the image resolution and complexity in public datasets are limited. Therefore, we manually collect and annotate 10,000 high-resolution and perceptually challenging complex perception images. These images are carefully curated for high resolution and complexity, focusing on enhancing the model's perceptual capabilities and addressing more difficult tasks.
- RL Algorithm Design. During the reinforcement learning phase, we observe that using a 84 85 high sampling temperature for code generation leads to low code usability—sampling any invalid characters or spaces when generating variable names will cause the entire code 86 snippet to fail execution. To mitigate this, we propose GRPO with Adaptive Temperature Sampling (GRPO-ATS), which applies different temperatures for text and code generation. Specifically, a temperature of 1.0 encourages exploration during text generation, while a temperature of 0.0 minimizes randomness during code generation, thereby ensuring code validity and reducing runtime errors.
 - Sandbox Design. We develop a secure sandbox environment capable of executing modelgenerated code within strict time limits and returning results. This environment minimizes the model's code burden by automatically handling formatting, variable definitions, and boundary conditions related to image operations, significantly improving code usability without altering its semantic intent.

Thyme effectively fulfills our vision by combining high autonomy with rich functionality. It 97 can assess the complexity of a given problem and determine whether tool usage is necessary. 98 When required, it autonomously defines and invokes tools through code, even performing 99 multiple operations such as cropping, zooming, and rotating in a single execution. More-100 over, the SFT training phase requires only about 200 GPU hours to activate the model's fundamental abilities to perform various image manipulations and computations, reflecting 102 favorable computational efficiency. We conduct comprehensive evaluations of Thyme across 103 more than 20 multimodal benchmarks. Experimental results in Figure 1 demonstrate that 104 Thyme exhibits significant and consistent advantages in fundamental perception, complex 105 reasoning, and computation tasks. 106

Preliminary and Overall Pipeline

73

74

75 76

77

78

79

80

81

82

83

87

88

89

90

91

92

93

94 95

96

107

As shown in Figure 2, the overall pipeline mainly consists of two components: the **model** and the **sandbox**. Given a user input, the model first generates a reasoning process, which



Figure 3: **SFT Data Construction Pipeline.** First, samples are taken from an existing dataset and prompts are constructed based on the target functions (such as cropping, rotating, etc.). The model generates a thinking process and corresponding code based on the prompt. The code is then executed in a sandbox environment to filter out samples that fail to run properly. The remaining samples are reviewed by an additional MLLM to verify whether the code execution results align with the thinking process and effectively answer the question, eliminating invalid code samples. Finally, manual review is conducted to remove low-quality samples, ensuring the quality of the cold-start dataset.

includes analyzing the problem and deciding, based on the type and difficulty of the problem, whether to generate code.

If **no code generation is required**, this implies the problem is simple, or that through previous dialogue rounds, relevant code operations have already successfully solved the problem. In such cases, the answer is returned directly. If **code generation is needed**, the model autonomously produces the code. Our training data covers several types of image operations such as *cropping*, *zooming*, *rotation*, *contrast enhancement*, *and computations*. The model may implement one or a combination of these functions in the generated code, for example performing cropping, zooming, and contrast enhancement simultaneously. The input parameters of these operations, such as the contrast enhancement factor, crop coordinates, and zoom ratio, are all decided by the model itself with no external constraints.

The generated code is then executed within an external sandbox, whose main function is to securely handle the input code and return execution results. Inside the sandbox, we utilize Python's built-in modules such as ast, autopep8, etc., to perform code formatting, correct input-output variable properties, and fix code input parameters. This is done without affecting the code functionality but to avoid errors caused by trivial code details, thereby reducing the model's code burden and improving code usability.

Finally, the code execution results are returned to the model for the next dialogue round, and the model conducts reasoning based on these results to continue the interaction. We demonstrate the construction process and considerations for the sandbox section in Section A.

130 3 Thyme-SFT Cold Start

127

133

In this section, we introduce the data construction, data composition, and training strategies employed for the cold start of Thyme.

3.1 Training Data Construction Pipeline

This subsection details the construction of the training datasets, which are organized into 134 three task categories reflecting increasing complexity. The first category includes tasks 135 suitable for direct answer generation without the need for code. The second category 136 comprises tasks that require image-based operations, such as cropping, rotation, contrast enhancement, as well as mathematical computations. Finally, the third category consists of tasks that extend over multiple interaction rounds—for instance, cases where initial image 139 manipulations fail or require refinement, and complex problems that involve multi-turn reasoning and calculations. All original prompts are sourced from a variety of open datasets, including LLaVA-OV-Image [17], MM-RLHF [62], SMR [61], V* [47], MM-Eureka [27], arXivQA [19], and Retool [8], ensuring broad coverage and diversity. The overall data construction pipeline is shown in Figure 3 and data samples are shown in Figure 4. We defer the detailed data taxonomy and construction methodology to Appendix B.




Figure 4: **Visualization of SFT Data instances**. The left side presents a sample of data related to image processing operations, while the right side showcases a sample of data related to complex computations.

146 3.2 Training Strategy

161

162

163

164

165

166

168 169

170 171

172

178

Our system prompt and user prompt are presented in Table 2 and Table 3, respectively. In the system prompt, we explicitly define the task format, the expected output code style, and the format for sandbox environment execution results, ensuring the model clearly understands the task requirements. Meanwhile, the user prompt includes the image path and image size, facilitating proper image loading and preventing out-of-bounds operations. It also specifies the required output format.

We formalize the training process of Thyme to facilitate a clearer understanding of the employed training techniques. Given an image I and a question Q, the model generates a sequence of thinking process T along with optional code C. If code is generated, an external sandbox executes it and returns the execution result S, which may be one or multiple images, or a computed numeric result. The model iteratively interacts based on the previous execution results, continuing this procedure until the question is resolved and the final answer a is produced. Therefore, each training sample can be represented as:

$$X = \{(I, Q); ([T_0, C_0, S_0], \dots, [T_t, a])\}$$

where t denotes the maximum number of interaction rounds for the sample.

During training, we encountered several challenges. First, due to the special nature of tworound dialogue data, some unexpected patterns emerged: the model tends to generate an incorrect or insufficient analysis and code in the first round, then corrects it in the second round, rendering the first round essentially ineffective. The second challenge is the relatively small quantity of math data compared to image manipulation data; when trained jointly, the model barely learns to generate computation-related code.

To address these issues, we devise several training-phase strategies:

- \diamond Train on the Last Round Only: For samples with two or more rounds, mask out all content before and including the last <sandbox_output></sandbox_output> tag, such that the model learns only to generate outputs corresponding to the final round. In other words, all $[T_{t-1}, C_{t-1}, S_{t-1}]$ are masked out, and only the logic and results of the last round are learned.
- Sandbox Content Exclusion: Throughout all training stages, we exclude the sandbox identifier $sandbox_output > markers$ and sandbox execution results from the training targets. Formally, all $S_{i=1...t}$ are masked out and do not participate in training, thereby preventing the model from learning to directly predict sandbox outputs.
 - Math Data Annealing: To prevent the math data from being overwhelmed by image operation data, first train on all image-related data, then fine-tune exclusively on math data



Figure 5: **Visualization of RL Data Instances**. Thyme RL data focuses on complex scenarios and high-resolution image interpretation. Human annotators identify challenging objects within the images, design corresponding questions, and provide answers, along with the appropriate bounding boxes.

with a lower learning rate. Since math data usually involves multi-turn code with weak inter-round correlations, all rounds are learned jointly in this phase instead of applying the last-round-only strategy.

182 4 Thyme-RL

196

197

198

199

200

201

202

205

We present the construction of RL data for Thyme, including the selection of data from public datasets and the manual creation of complex real-world visual question answering data to enhance task difficulty. Finally, we introduce the algorithmic and architectural innovations implemented during the RL phase.

187 4.1 RL Data Construction and Annotation

Public Data Selection: Similar to the existing study [67], we curate RL data from a diverse range of prompt sources, including V* [47], arXivQA [19], and ThinkLite-VL [45], targeting both perception tasks, and reasoning tasks, respectively. Manual verification removes instances where the questions and images do not match or lack relevance.

Complex Image Data and Question Construction: Publicly available datasets generally contain images with limited resolution and insufficient perceptual complexity, which substantially restricts the effectiveness of the Thyme framework in reinforcement learning. To address this gap, the following pipeline constructs relevant data:

 Manually collect 30,000 high-resolution images from the internet, each with either width or height exceeding 2048 pixels, to ensure sufficient image complexity.

⋄ Employ a team of 15 annotators to label these images. The annotation guidelines appear in Section D. Specifically, annotators design, for each image, a concrete question targeting small and challenging-to-recognize objects occupying no more than 5% of the image resolution, ensuring high recognition difficulty. Users require zooming in on the image to clearly identify these small objects.

All annotation data undergo at least one round of cross-checking, followed by unified inspection and acceptance by three multimodal experts to ensure data quality.

4.2 Preliminary of Reinforcement Learning Algorithm

Training Algorithm: We adopt a fully on-policy variant of Group Relative Policy Optimization (GRPO) [35] algorithm. For each problem consisting of an image I and a question Q, the algorithm samples a group of interaction trajectories $\{\tau_1, \tau_2, \ldots, \tau_G\}$ from the policy π_{θ} , where each trajectory τ_i represents a complete multi-round interaction:

$$\tau_i = \{(I, Q); ([T_{i,0}, C_{i,0}, S_{i,0}], \dots, [T_{i,t_i}, a_i])\}$$

The policy is updated by maximizing the following objective:

211

212 213

215

216

219

220

221

222

223

227

228

229

230

231

232

233

235

236

238

242

243

244

245 246

247

248

249

250

251

252

253

254

$$\mathcal{J}_{\text{GRPO}}(\theta) = \mathbb{E}_{(I,Q) \sim D, \{\tau_i\}_{i=1}^G \sim \pi_{\theta}(\cdot | I, Q)} \left[\frac{1}{\sum_{i=1}^G |\tau_i|} \sum_{i=1}^G \sum_{j=1}^{|\tau_i|} (A_{i,j} - \beta \mathbb{D}_{\text{KL}}[\pi_{\theta} | | \pi_{\text{ref}}]) \right]$$

where $|\tau_i|$ is the total number of tokens generated by the model in trajectory i, specifically: $|\tau_i| = \sum_{k=0}^{t_i} |T_{i,k}| + \sum_{k=0}^{t_{i-1}} |C_{i,k}| + |a_i|$ and $A_{i,j}$ is the advantage computed from the final rewards $\{r_1, r_2, \ldots, r_G\}$ of the complete trajectories in the same group: $A_{i,j} = \frac{r_i - \max(\{r_i\}_{i=1}^G)}{\operatorname{std}(\{r_i\}_{i=1}^G)}$ for each token j in τ_i The term $-\beta \mathbb{D}_{\mathrm{KL}}[\pi_\theta||\pi_{\mathrm{ref}}]$ penalizes large deviations of the current policy π_θ from a reference policy π_{ref} , with β controlling the strength of the constraint. The reward r_i evaluates the quality of the entire trajectory, including the effectiveness of code generation, sandbox utilization, and the correctness of the final answer a_i . Importantly, during the RL stage, the trajectory length $|\tau_i|$ and the summation over tokens in the advantage calculation exclude the sandbox-related content $S_{i,k}$, as these are external observations rather than outputs of the policy model.

4.3 GRPO with Adaptive Temperature Sampling

Our motivation is that code generation and textual reasoning require different sampling parameters. Code generation tasks—such as image manipulation and numerical computation—follow predictable logical sequences. These sequences typically involve loading data, defining parameters, executing operations, and saving results. Such processes require precision rather than exploration. Empirical evidence shows that high temperature settings significantly reduce code reliability. Even minor errors, like an unexpected space character during variable definition, can cause complete code failure. Therefore, we set the temperature to 0 during code generation phases to ensure deterministic output. For natural language reasoning, however, we employ a temperature of 1.0. This setting encourages broader conceptual exploration and diverse expression. As shown in Figure 6, our system implements dynamic temperature adjustment. When the <code> token appears, the temperature




Figure 6: **GRPO-ATS Sampling Pieline.** The model sets the temperature τ to 0 when generating code to reduce diversity and ensure accuracy; when generating the reasoning process, the temperature is set to 1 to encourage exploration. Sandbox outputs do not participate in training or advantage estimation.

drops to 0. After code generation completes, the system returns to the default temperature setting for normal text generation. In our experiments, we observe two main benefits :

- It improves sample efficiency. During rollouts of RL, many samples become unusable due to chaotic or erroneous code generation, for example, continuously attempting to generate code incorrectly and failing until the maximum interaction steps are exhausted. Lowering the code temperature helps these samples recover and become valid.
- It prevents the model from collapsing into completely avoiding code generation. Since writing code is more error-prone than natural language reasoning, without adjusting the sampling parameters, most code produced during training rollouts is invalid. Over time, this causes the model to become overly conservative and tend to avoid writing code altogether. Reducing the temperature and thus increasing the usability of generated code effectively mitigates this issue.

Sampling Optimization: Another major challenge stems from the multi-turn interactive nature of the task: the maximum number of interaction rounds imposes a strict sampling time budget, as extended or repetitive dialogues significantly increase computational overhead. When the model enters a cycle of repetitive errors, it produces redundant outputs across multiple turns, thereby wasting computational resources on invalid samples. To mitigate

Table 1: **Performance Comparison on the MME-Realworld.** Thyme-7B demonstrates substantial improvements over the Qwen2.5-VL-7B baseline, particularly in more challenging perception and reasoning domains such as Monitoring and Autonomous Driving, where the baseline's performance is weaker.

Model Qwen2.5-VL-7B Thyme-VL-7B	Monitoring 38.75 49.27	Autonomous Driving 22.70 37.46	eption OCR 87.00 88.36	Diagram and Table 78.83 80.86	Remote Sensing 45.40 53.93	Overall 60.94 67.10
Improvement ↑	27.14%	64.99%	1.56%	2.57%	18.80%	10.10%
		Reas	oning			
Model	Monitoring	Autonomous Driving	OCR	Diagram and Table	Remote Sensing	Overall
Qwen2.5-VL-7B	26.10	24.25	64.80	63.40	-	38.59
Thyme-VL-7B	47.39	32.29	70.60	70.40	-	48.38
$Improvement \uparrow$	81.57%	33.16%	8.95%	11.04%	-	25.37%

this, we implement an early termination mechanism during training. Specifically, we utilize the Rabin-Karp rolling hash algorithm [16, 15] to count occurrences of all substrings of fixed length within the model's output. If any substring repeats so frequently that the cumulative length of its occurrences exceeds 50% of the total output length, we classify the output as repetitive. Once this criterion is met, the sampling process for that particular sample is immediately halted to avoid unnecessary computation. Additionally, during training, we enforce a manual cap on the maximum allowed number of dialogue turns, denoted as max iterations. Dialogues that exceed this limit without terminating are truncated to control context length, thereby improving training efficiency.

4.4 Reward Function Design:

- ♦ Formatting Reward: The model's output is required to conform to a strict structure, enclosed by <think></think> tags followed by <answer></answer> tags. This encourages the model to explicitly perform reasoning before producing a final answer, improving the interpretability.
- Result Reward: Since not all targets are strictly numerical or formulaic answers amenable to rule-based comparison, we first apply a rule-based method to directly compare the model output with the ground truth answer. If the rule-based matching fails, we then utilize an auxiliary MLLM, Qwen-2.5-VL-72B, to compare the model-generated output against the ground truth by assessing semantic equivalence and correctness. This hybrid reward approach, combining rule-based and model-based evaluation, improves scoring efficiency and is well-suited for open-ended question answering scenarios.
- Consistency Reward [42, 60]: This component evaluates whether the final answer is logically derived from the preceding reasoning steps, ensuring coherence between the thought process and the conclusion.

Integrating the consistency reward alongside formatting and result rewards can cause unintended behavior: the model might receive a high total reward by maintaining consistency even when the chosen answer is incorrect. To prevent this, we define the final reward as follows: Final Reward r= Result Reward \times (1 + 0.5 \times Consistency Reward) + 0.5 \times Formatting Reward. This formulation ensures that the consistency bonus is considered only when the model's answer is correct, avoiding excessive prioritization of consistency at the expense of answer accuracy.

5 Experiments

Due to space constraints, we relegate the, experimental setup, baselines and evaluation benchmarks, as well as the ablation studies and case analyses of model outputs to the appendix C. In the main paper, we focus on demonstrating the performance improvements brought by Thyme to the model.

Main Results: Figure 1 and Table 4 presents a comprehensive comparison between Thyme and other leading multimodal models across a range of benchmarks covering *Perception*, *Reasoning*, and *General* tasks. In perception tasks, Thyme demonstrates clear advantages even over larger-scale models such as Qwen2.5-VL 32B, indicating that simply scaling model size does not effectively address perception challenges. Instead, Thyme's test-time scaling strategy proves highly beneficial for perception tasks. Furthermore, by converting complex computations into executable code through training, Thyme achieves notable improvements in reasoning abilities. However, in this domain, the benefits of scaling model size are more pronounced, suggesting that reasoning and logical inference capabilities largely depend on the inherent knowledge within the model itself. Thyme mainly enhances visual recognition quality and helps avoid the model independently predicting overly complex computations. Finally, due to the improvements in both perception and reasoning, Thyme shows significant gains in many general tasks, particularly with a substantial reduction in hallucination.

Delve deep into perception tasks: Taking MME-Realworld as an example, it includes many high-resolution perception tasks in real-world scenarios. In Table 5, we show the performance of Thyme and the baseline on various tasks. It can be seen that on tasks where the baseline model already performs well, such as OCR, Diagram and Table, achieving accuracy of over 60% and even close to 90%, the improvement from Thyme is limited. However, for more difficult tasks where Qwen2.5-VL-7B's perception is relatively poor, such as monitoring and autonomous driving, Thyme shows an improvement of over 25% in both perception and reasoning tasks, with the improvement in reasoning tasks being more pronounced.

316 6 Conclusion and Limitations

We introduce **Thyme**, a novel paradigm that empowers MLLMs to autonomously generate and execute code for a wide range of image manipulations and complex computations. Our approach utilizes a two-stage training strategy, beginning with a comprehensive SFT phase on a curated 500K-sample dataset to instill foundational coding abilities for tasks like cropping, rotation, and mathematical calculations. This is followed by a RL phase, where we employ our proposed GRPO-ATS algorithm to refine the model's decision-making and executional precision. GRPO-ATS adaptively uses different sampling temperatures for text and code generation, which effectively balances creative reasoning with the need for accurate, executable code. Extensive evaluations across nearly 20 benchmarks demonstrate that Thyme achieves significant and consistent performance improvements over the baseline, particularly in challenging high-resolution perception and complex reasoning tasks.

Our work has several limitations that open avenues for future research:

- Model Capability. The performance of Thymeis inherently constrained by the
 capabilities of its base model. The current model's proficiency in precise object
 localization and sophisticated code generation is limited. This can occasionally lead
 to the generation of incorrect cropping operations or non-standard, unexecutable
 code. We believe that leveraging more powerful foundation models (i.e., a stronger
 base model) could significantly mitigate these issues, leading to more reliable and
 accurate tool use.
- Evaluation Scope. Our evaluation is limited by the nature of existing benchmarks. The majority of image data in widely-used benchmarks consists of high-quality, well-oriented images from everyday scenarios. Consequently, there is a lack of robust numerical evaluation for certain image manipulation capabilities that Thyme enables, such as correcting for image rotation or enhancing low-contrast images, as these scenarios are underrepresented. The development of new benchmarks specifically designed to assess these advanced image processing operations would be invaluable for a more comprehensive evaluation of models like Thyme.

44 References

- Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, et al. Qwen2. 5-vl technical report. *arXiv* preprint *arXiv*:2502.13923, 2025.
- Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng
 Wang, Shijie Wang, Jun Tang, Humen Zhong, Yuanzhi Zhu, Mingkun Yang, Zhaohai
 Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, Jiabo Ye, Xi Zhang,
 Tianbao Xie, Zesen Cheng, Hang Zhang, Zhibo Yang, Haiyang Xu, and Junyang Lin.
 Qwen2.5-vl technical report. arXiv, 2025.
- Lin Chen, Jinsong Li, Xiaoyi Dong, Pan Zhang, Yuhang Zang, Zehui Chen, Haodong Duan, Jiaqi Wang, Yu Qiao, Dahua Lin, et al. Are we on the right way for evaluating large vision-language models? *arXiv*:2403.20330, 2024.
- Zhe Chen, Jiannan Wu, Wenhai Wang, Weijie Su, Guo Chen, Sen Xing, Muyan Zhong, Qinglong Zhang, Xizhou Zhu, Lewei Lu, Bin Li, Ping Luo, Tong Lu, Yu Qiao, and Jifeng Dai. Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks. *arXiv preprint arXiv*:2312.14238, 2023.
- Ethan Chern, Zhulin Hu, Steffi Chern, Siqi Kou, Jiadi Su, Yan Ma, Zhijie Deng, and Pengfei Liu. Thinking with generated images. *arXiv preprint arXiv*:2505.22525, 2025.
- [6] DeepSeek-AI. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv*, 2025.
- [7] Haodong Duan, Junming Yang, Yuxuan Qiao, Xinyu Fang, Lin Chen, Yuan Liu, Xiaoyi
 Dong, Yuhang Zang, Pan Zhang, Jiaqi Wang, et al. Vlmevalkit: An open-source toolkit
 for evaluating large multi-modality models. In *Proceedings of the 32nd ACM international* conference on multimedia, pages 11198–11201, 2024.
- [8] Jiazhan Feng, Shijue Huang, Xingwei Qu, Ge Zhang, Yujia Qin, Baoquan Zhong,
 Chengquan Jiang, Jinxin Chi, and Wanjun Zhong. Retool: Reinforcement learning for
 strategic tool use in llms. arXiv preprint arXiv:2504.11536, 2025.
- [9] Chaoyou Fu, Haojia Lin, Zuwei Long, Yunhang Shen, Meng Zhao, Yifan Zhang, Shaoqi Dong, Xiong Wang, Di Yin, Long Ma, et al. Vita: Towards open-source interactive omni multimodal llm. *arXiv*, 2024.
- 10 Chaoyou Fu, Haojia Lin, Xiong Wang, Yi-Fan Zhang, Yunhang Shen, Xiaoyu Liu, Haoyu Cao, Zuwei Long, Heting Gao, Ke Li, et al. Vita-1.5: Towards gpt-4o level real-time vision and speech interaction. arXiv preprint arXiv:2501.01957, 2025.
- ³⁷⁷ [11] Chaoyou Fu, Yi-Fan Zhang, Shukang Yin, Bo Li, Xinyu Fang, Sirui Zhao, Haodong Duan, Xing Sun, Ziwei Liu, Liang Wang, et al. Mme-survey: A comprehensive survey on evaluation of multimodal llms. *arXiv*, 2024.
- Xingyu Fu, Yushi Hu, Bangzheng Li, Yu Feng, Haoyu Wang, Xudong Lin, Dan Roth,
 Noah A Smith, Wei-Chiu Ma, and Ranjay Krishna. Blink: Multimodal large language
 models can see but not perceive. In *European Conference on Computer Vision*, pages
 148–166. Springer, 2024.
- Wenxuan Huang, Bohan Jia, Zijie Zhai, Shaosheng Cao, Zheyu Ye, Fei Zhao, Yao Hu,
 and Shaohui Lin. Vision-r1: Incentivizing reasoning capability in multimodal large
 language models. arXiv, 2025.
- Xinyu Huang, Yuhao Dong, Weiwei Tian, Bo Li, Rui Feng, and Ziwei Liu. High resolution visual reasoning via multi-turn grounding-based reinforcement learning.
 arXiv preprint arXiv:2507.05920, 2025.
- [15] Richard M Karp and Michael O Rabin. Efficient randomized pattern-matching algorithms. *IBM journal of research and development*, 31(2):249–260, 1987.

- ³⁹² [16] Charles Eric Leiserson, Ronald L Rivest, Thomas H Cormen, and Clifford Stein. *Intro-*³⁹³ *duction to algorithms*, volume 3. MIT press Cambridge, MA, USA, 1994.
- [17] Bo Li, Yuanhan Zhang, Dong Guo, Renrui Zhang, Feng Li, Hao Zhang, Kaichen Zhang,
 Peiyuan Zhang, Yanwei Li, Ziwei Liu, et al. Llava-onevision: Easy visual task transfer.
 arXiv preprint arXiv:2408.03326, 2024.
- Feng Li, Hao Zhang, Yi-Fan Zhang, Shilong Liu, Jian Guo, Lionel M Ni, PengChuan Zhang, and Lei Zhang. Vision-language intelligence: Tasks, representation learning, and large models. *arXiv*, 2022.
- [19] Lei Li, Yuqi Wang, Runxin Xu, Peiyi Wang, Xiachong Feng, Lingpeng Kong, and Qi Liu.
 Multimodal arxiv: A dataset for improving scientific comprehension of large vision-language models. arXiv preprint arXiv:2403.00231, 2024.
- Yadong Li, Jun Liu, Tao Zhang, Song Chen, Tianpeng Li, Zehuan Li, Lijun Liu, Lingfeng
 Ming, Guosheng Dong, Da Pan, et al. Baichuan-omni-1.5 technical report. arXiv, 2025.
- Yifan Li, Yifan Du, Kun Zhou, Jinpeng Wang, Wayne Xin Zhao, and Ji-Rong Wen.
 Evaluating object hallucination in large vision-language models. arXiv:2305.10355,
 2023.
- Yuliang Liu, Zhang Li, Mingxin Huang, Biao Yang, Wenwen Yu, Chunyuan Li, Xucheng Yin, Cheng lin Liu, Lianwen Jin, and Xiang Bai. Ocrbench: On the hidden mystery of ocr in large multimodal models. *arXiv*:2305.07895, 2023.
- [23] Ziyu Liu, Zeyi Sun, Yuhang Zang, Xiaoyi Dong, Yuhang Cao, Haodong Duan, Dahua
 Lin, and Jiaqi Wang. Visual-rft: Visual reinforcement fine-tuning. arXiv, 2025.
- 413 [24] Jinda Lu, Junkang Wu, Jinghan Li, Xiaojun Jia, Shuo Wang, YiFan Zhang, Junfeng
 414 Fang, Xiang Wang, and Xiangnan He. Dama: Data- and model-aware alignment of
 415 multi-modal llms. *arXiv*, 2025.
- [25] Pan Lu, Hritik Bansal, Tony Xia, Jiacheng Liu, Chunyuan Li, Hannaneh Hajishirzi,
 Hao Cheng, Kai-Wei Chang, Michel Galley, and Jianfeng Gao. Mathvista: Evaluating
 mathematical reasoning of foundation models in visual contexts. In *ICLR*, 2024.
- 419 [26] Ahmed Masry, Do Xuan Long, Jia Qing Tan, Shafiq Joty, and Enamul Hoque. Chartqa:
 420 A benchmark for question answering about charts with visual and logical reasoning.
 421 arXiv preprint arXiv:2203.10244, 2022.
- Fanqing Meng, Lingxiao Du, Zongkai Liu, Zhixiang Zhou, Quanfeng Lu, Daocheng Fu, Botian Shi, Wenhai Wang, Junjun He, Kaipeng Zhang, et al. Mm-eureka: Exploring visual aha moment with rule-based large-scale reinforcement learning. *arXiv*, 2025.
- ⁴²⁵ [28] OpenAI. Hello gpt-40, 2024.
- 426 [29] OpenAI. Introducing openai o1-preview. 2024.
- 427 [30] OpenAI. Thinking with images. https://openai.com/index/thinking-with-images/, 2025.
- Yingzhe Peng, Gongrui Zhang, Miaosen Zhang, Zhiyuan You, Jie Liu, Qipeng Zhu, Kai Yang, Xingzhong Xu, Xin Geng, and Xu Yang. Lmm-r1: Empowering 3b lmms with strong reasoning abilities through two-stage rule-based rl. *arXiv*, 2025.
- Runqi Qiao, Qiuna Tan, Guanting Dong, Minhui Wu, Chong Sun, Xiaoshuai Song, Zhuoma GongQue, Shanglin Lei, Zhe Wei, Miaoxuan Zhang, et al. We-math: Does your large multimodal model achieve human-like mathematical reasoning? *arXiv* preprint arXiv:2407.01284, 2024.
- Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. *Advances in Neural Information Processing Systems*, 36:53728–53741, 2023.

- [34] Hao Shao, Shengju Qian, Han Xiao, Guanglu Song, Zhuofan Zong, Letian Wang,
 Yu Liu, and Hongsheng Li. Visual cot: Advancing multi-modal language models with
 a comprehensive dataset and benchmark for chain-of-thought reasoning. Advances in
 Neural Information Processing Systems, 37:8612–8642, 2024.
- [35] Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Mingchuan Zhang,
 Y. K. Li, Y. Wu, and Daya Guo. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *CoRR*, abs/2402.03300, 2024.
- [36] Haozhan Shen, Peng Liu, Jingcheng Li, Chunxin Fang, Yibo Ma, Jiajia Liao, Qiaoli Shen,
 Zilun Zhang, Kangjia Zhao, Qianqian Zhang, et al. Vlm-r1: A stable and generalizable
 r1-style large vision-language model. arXiv, 2025.
- Haozhan Shen, Kangjia Zhao, Tiancheng Zhao, Ruochen Xu, Zilun Zhang, Mingwei
 Zhu, and Jianwei Yin. Zoomeye: Enhancing multimodal llms with human-like zooming
 capabilities through tree-based image exploration. arXiv preprint arXiv:2411.16044, 2024.
- [38] Wei Shen, Jiangbo Pei, Yi Peng, Xuchen Song, Yang Liu, Jian Peng, Haofeng Sun,
 Yunzhuo Hao, Peiyu Wang, and Yahui Zhou. Skywork-r1v3 technical report. arXiv
 preprint arXiv:2507.06167, 2025.
- Yunhang Shen, Chaoyou Fu, Shaoqi Dong, Xiong Wang, Yi-Fan Zhang, Peixian Chen,
 Mengdan Zhang, Haoyu Cao, Ke Li, Xiawu Zheng, Yan Zhang, Yiyi Zhou, Ran He,
 Caifeng Shan, Rongrong Ji, and Xing Sun. Long-vita: Scaling large multi-modal models
 to 1 million tokens with leading short-context accuracy, 2025.
- 458 [40] ByteDance Seed Team. Seed1.5-vl technical report. *arXiv preprint arXiv:2505.07062*, 459 2025.
- 460 [41] Chameleon Team. Chameleon: Mixed-modal early-fusion foundation models. *arXiv*, 2024.
- [42] Kwai Keye Team, Biao Yang, Bin Wen, Changyi Liu, Chenglong Chu, Chengru Song,
 Chongling Rao, Chuan Yi, Da Li, Dunju Zang, et al. Kwai keye-vl technical report.
 arXiv preprint arXiv:2507.01949, 2025.
- Ke Wang, Junting Pan, Weikang Shi, Zimu Lu, Mingjie Zhan, and Hongsheng Li. Measuring multimodal mathematical reasoning with math-vision dataset. arXiv:2402.14804, 2024.
- [44] Wenbin Wang, Liang Ding, Minyan Zeng, Xiabin Zhou, Li Shen, Yong Luo, Wei Yu,
 and Dacheng Tao. Divide, conquer and combine: A training-free framework for high resolution image perception in multimodal large language models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 7907–7915, 2025.
- [45] Xiyao Wang, Zhengyuan Yang, Chao Feng, Hongjin Lu, Linjie Li, Chung-Ching Lin,
 Kevin Lin, Furong Huang, and Lijuan Wang. Sota with less: Mcts-guided sample selection for data-efficient visual reasoning self-improvement. arXiv preprint arXiv:2504.07934, 2025.
- [46] Junfei Wu, Jian Guan, Kaituo Feng, Qiang Liu, Shu Wu, Liang Wang, Wei Wu, and
 Tieniu Tan. Reinforcing spatial reasoning in vision-language models with interwoven
 thinking and visual drawing. arXiv preprint arXiv:2506.09965, 2025.
- Penghao Wu and Saining Xie. V?: Guided visual search as a core mechanism in multimodal llms. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 13084–13094, 2024.
- 482 [48] xAI. Grok-1.5 vision preview, 2024.
- 483 [49] Yijia Xiao, Edward Sun, Tianyu Liu, and Wei Wang. Logicvista: Multimodal llm logical reasoning benchmark in visual contexts. *arXiv preprint arXiv:2407.04973*, 2024.
- 85 [50] LLM-Core-Team Xiaomi. Mimo-vl technical report, 2025.

- Ijinheng Xie, Weijia Mao, Zechen Bai, David Junhao Zhang, Weihao Wang,
 Kevin Qinghong Lin, Yuchao Gu, Zhijie Chen, Zhenheng Yang, and Mike Zheng Shou.
 Show-o: One single transformer to unify multimodal understanding and generation.
 arXiv, 2024.
- [52] Tianyi Xiong, Xiyao Wang, Dong Guo, Qinghao Ye, Haoqi Fan, Quanquan Gu, Heng
 Huang, and Chunyuan Li. Llava-critic: Learning to evaluate multimodal models.
 CVPR, 2024.
- Weiye Xu, Jiahao Wang, Weiyun Wang, Zhe Chen, Wengang Zhou, Aijun Yang, Lewei
 Lu, Houqiang Li, Xiaohua Wang, Xizhou Zhu, et al. Visulogic: A benchmark for
 evaluating visual reasoning in multi-modal large language models. arXiv preprint
 arXiv:2504.15279, 2025.
- [54] Tao Yu, Chaoyou Fu, Junkang Wu, Jinda Lu, Kun Wang, Xingyu Lu, Yunhang Shen,
 Guibin Zhang, Dingjie Song, Yibo Yan, et al. Aligning multimodal llm with human
 preference: A survey. arXiv, 2025.
- Weihao Yu, Zhengyuan Yang, Lingfeng Ren, Linjie Li, Jianfeng Wang, Kevin Lin, Chung-Ching Lin, Zicheng Liu, Lijuan Wang, and Xinchao Wang. Mm-vet v2: A challenging benchmark to evaluate large multimodal models for integrated capabilities. *arXiv* preprint arXiv:2408.00765, 2024.
- Huanyu Zhang, Chengzu Li, Wenshan Wu, Shaoguang Mao, Yifan Zhang, Haochen
 Tian, Ivan Vulić, Zhang Zhang, Liang Wang, Tieniu Tan, et al. Scaling and beyond: Advancing spatial reasoning in mllms requires new recipes. arXiv preprint arXiv:2504.15037, 2025.
- [57] Renrui Zhang, Dongzhi Jiang, Yichi Zhang, Haokun Lin, Ziyu Guo, Pengshuo Qiu,
 Aojun Zhou, Pan Lu, Kai-Wei Chang, Yu Qiao, et al. Mathverse: Does your multi-modal
 llm truly see the diagrams in visual math problems? In European Conference on Computer
 Vision, pages 169–186. Springer, 2024.
- 512 [58] Shaolei Zhang, Qingkai Fang, Zhe Yang, and Yang Feng. Llava-mini: Efficient image 513 and video large multimodal models with one vision token, 2025.
- [59] Xintong Zhang, Zhi Gao, Bofei Zhang, Pengxiang Li, Xiaowen Zhang, Yang Liu, Tao
 Yuan, Yuwei Wu, Yunde Jia, Song-Chun Zhu, et al. Chain-of-focus: Adaptive visual
 search and zooming for multimodal reasoning via rl. arXiv preprint arXiv:2505.15436,
 2025.
- [60] Yi-Fan Zhang, Xingyu Lu, Xiao Hu, Chaoyou Fu, Bin Wen, Tianke Zhang, Changyi Liu,
 Kaiyu Jiang, Kaibing Chen, Kaiyu Tang, et al. R1-reward: Training multimodal reward
 model through stable reinforcement learning. arXiv preprint arXiv:2505.02835, 2025.
- [61] Yi-Fan Zhang, Qingsong Wen, Chaoyou Fu, Xue Wang, Zhang Zhang, Liang Wang, and Rong Jin. Beyond llava-hd: Diving into high-resolution large multimodal models. *arXiv preprint arXiv:2406.08487*, 2024.
- [62] Yi-Fan Zhang, Tao Yu, Haochen Tian, Chaoyou Fu, Peiyan Li, Jianshu Zeng, Wulin
 Xie, Yang Shi, Huanyu Zhang, Junkang Wu, et al. Mm-rlhf: The next step forward in multimodal llm alignment. arXiv preprint arXiv:2502.10391, 2025.
- 527 [63] Yi-Fan Zhang, Weichen Yu, Qingsong Wen, Xue Wang, Zhang Zhang, Liang Wang, Rong Jin, and Tieniu Tan. Debiasing multimodal large language models. arXiv preprint arXiv:2403.05262, 2024.
- [64] Yi-Fan Zhang, Huanyu Zhang, Haochen Tian, Chaoyou Fu, Shuangqing Zhang, Junfei
 Wu, Feng Li, Kun Wang, Qingsong Wen, Zhang Zhang, et al. Mme-realworld: Could
 your multimodal llm challenge high-resolution real-world scenarios that are difficult
 for humans? arXiv preprint arXiv:2408.13257, 2024.

- Yi-Fan Zhang, Huanyu Zhang, Haochen Tian, Chaoyou Fu, Shuangqing Zhang, Junfei
 Wu, Feng Li, Kun Wang, Qingsong Wen, Zhang Zhang, et al. Mme-realworld: Could
 your multimodal llm challenge high-resolution real-world scenarios that are difficult
 for humans? *ICLR*, 2024.
- [66] Jiaxing Zhao, Xihan Wei, and Liefeng Bo. R1-omni: Explainable omni-multimodal
 emotion recognition with reinforcing learning. arXiv, 2025.
- 540 [67] Ziwei Zheng, Michael Yang, Jack Hong, Chenxiao Zhao, Guohai Xu, Le Yang, Chao
 541 Shen, and Xing Yu. Deepeyes: Incentivizing" thinking with images" via reinforcement
 542 learning. arXiv preprint arXiv:2505.14362, 2025.
- [68] Jinguo Zhu, Weiyun Wang, Zhe Chen, Zhaoyang Liu, Shenglong Ye, Lixin Gu, Hao Tian,
 Yuchen Duan, Weijie Su, Jie Shao, et al. Internvl3: Exploring advanced training and
 test-time recipes for open-source multimodal models. arXiv preprint arXiv:2504.10479,
 2025.

547 A Sandbox Building

568

Our framework requires a robust sandbox with two essential properties. First, it ensures basic security and robustness for the operating system, guaranteeing that any image processing or computational operations executed within the sandbox complete within a reasonable timeframe or throw appropriate errors. At the same time, it prevents unauthorized system modifications, such as file deletion or renaming, which could corrupt existing data or runtime configurations.

We observe that smaller models (e.g., 7B parameters) often struggle to generate flawless code, frequently encountering minor issues such as formatting problems (improper indentation), boundary condition errors (cropping boxes exceeding image dimensions), and input/output handling (omitting input variables or output printing). Therefore, the sandbox design aims to reduce the model's coding burden by automatically handling these minor issues when possible.

To address sandbox security and robustness, we apply the following strategies:

- We define a list of dangerous operations—such as remove, unlink, move, and rename—that
 may cause system data or configuration failures. Before execution, the code is scanned for
 these operations; if it contains any, execution skips and a warning raises as an error.
- We limit the maximum execution time, empirically set to 10 seconds. Exceeding this limit
 results in a timeout error. These measures help ensure code isolates from the local system
 and runs safely.

To reduce the model's code generation burden, we implement the following optimizations:

- ♦ We apply Python's built-in autopep8 for code formatting and indentation alignment.
- Using the ast module, we traverse the code to identify variables in tuple formats. If
 variable names contain box or coord, we infer they represent cropping parameters; these
 parameters adjust to fit within the input image boundaries to avoid execution errors.
- before execution, we preset local variables such as image_path and import packages like cv2. After execution, we check for newly created variables indicative of processed outputs (e.g., those containing 'processed_path') to ensure correct execution even if input/output variables do not explicitly define in the model-generated code.
- Additionally, we observe that when the model outputs multiple code segments, context or
 variable dependencies often arise; for example, certain Python packages are imported only
 in the first segment, while subsequent segments rely on them directly. To address this,
 we record all variables throughout the model's code execution process and incorporate
 historical context in multi-round sandbox invocations.

B Long-CoT Data Construction

Focusing first on the simplest category, which involves no code generation, the objective is to train the model to confidently bypass the intermediate coding step and directly produce accurate final answers for relatively straightforward questions. These samples derive from LLaVA-OV-Image data, where for each given question and accompanying image, Qwen2.5-VL-72B assesses whether code generation is necessary. The prompt template guiding Qwen2.5-VL-72B's decision-making process is illustrated in Table 8. From the entire pool of samples requiring no tool intervention, we randomly select 100k samples to constitute this training subset.

Real-World Thyme Data: Moving towards increased complexity, samples requiring code-based operations undergo rigorous verification and quality control. Initially, all code snippets pass through our sandbox environment where non-executable codes are discarded to ensure only valid samples proceed. Subsequently, the execution outputs, alongside the model's own analysis and answers, feed back into Qwen2.5-VL-72B to verify whether the intended goals—such as clearer identification of the target region by cropping or enhanced readability through rotation—are effectively achieved. The model flags and eliminates any samples where code does not fulfill those expectations. To further enhance data reliability, two multimodal experts perform an additional round of meticulous screening, filtering out ambiguous or borderline cases beyond the model's discernment. These samples reflect realistic and complex visual-question answering scenarios drawn from more than 4 million instances across public datasets, culminating in a refined collection of 50k high-quality, executable QA pairs.

Manually Constructed Thyme Data: Given that real-world Thyme data often have high complexity and quality but limited quantity—we complement this by deliberately creating an additional manually constructed dataset¹. This curated data supplements and enriches the training distribution, helping the model perform robustly across various task types. The verification and filtering protocols for this synthetic dataset parallel those used for real-world data, ensuring consistent quality standards.

- ⋄ Coding Data 1: Cropping This dataset draws primarily from V*, which features questions paired with images, corresponding answers, and ground truth bounding box coordinates for target objects. By applying the prompt outlined in Table 9, the model is prompted to explain the rationale behind cropping the object and its contribution to problem-solving. Cropping then proceeds based on the ground truth coordinates before providing answers. Despite leveraging accurate bounding box information, code generation quality constraints restrict the final dataset size to 28k samples.
- ♦ Coding Data 2: Rotation Addressing the scarcity of rotated image samples in conventional training datasets, we augment the data by randomly rotating images within the collected pool at angles ranging from 30° to 335°. Applying the prompt template in Table 10, the model generates appropriate processing code and accompanying analytical commentary informed by ground truth rotation angles. Notably, we observe the relative insensitivity of existing MLLMs to rotation angles; that is, without ground truth inputs, the majority of samples cannot be reoriented correctly. After careful filtering, this yields a set of 14k high-fidelity samples.
- ◇ Coding Data 3: Low-Contrast Enhancement Derived mainly from OCR data within LLaVA-OV-Image, this subset targets scenarios in which contrast enhancement reduces the difficulty of text recognition, thereby aiding the model's text extraction capabilities. We repurpose prompts akin to those in Table 9, swapping out cropping directives for contrast enhancement instructions. Qwen2.5-VL-72B generates explanations of the enhancement's purpose, corresponding code, and final visual results. The curated dataset contains approximately 10k high-quality training examples.

¹Most real-world data features high-resolution images or complex problems where additional image processing significantly improves perceptual effectiveness. In contrast, manually constructed data often contains smaller resolution images (e.g., V*), where using prompts from Table 8 might cause the model to simply output answers, necessitating specialized construction procedures.

Coding Data 4: Computational Code — To not only support image manipulation but also foster enhanced logical reasoning through mathematical computation, we construct a specialized math-centric dataset. Its principal source is MM-Eureka and Retool. Initial long-chain-of-thought solutions are generated by Gemini 2.5 Pro, which are then transformed by GPT-40 into executable code segments. This process results in 15k samples focused on computational reasoning via code.

Multi-Round Conversation: Except for the Computational Code data, all the aforementioned datasets involve only a single round of code generation and execution. Our experiments reveal that models trained solely on single-turn interactions lack error-correction capabilities. Specifically, even if the model incorrectly crops a sub-region, it proceeds to generate an answer based on the flawed crop without attempting to re-crop or further adjust the targeted area. To address this limitation, we manually construct multi-round conversational datasets aimed at teaching the model to leverage historical code execution outcomes for deeper analysis and error rectification. This multi-round data is categorized into two types:

- ♦ Further Enhancement: The model refines or augments previous results based on feedback. We sample data from V* and utilize the prompt shown in Table 9, but initially provide a larger bounding box that fully contains the ground truth cropping box. Based on the code execution results from this first round, the model generates further analysis and code to crop precisely to the ground truth bounding box.
- Error Correction: The model detects and fixes mistakes identified in earlier steps. Similarly,
 we provide an incorrect bounding box in the first step. In the second step, the model
 generates the corrected bounding box with an explanation on why the cropping region
 needs adjustment.

Such multi-round data effectively instructs the model to revise its prior image manipulation errors and further enhance the quality of its operations.

656 C Extended Experiments

657 C.1 Experimental Setting

Hyperparameters: Our training procedure is divided into three main stages. The first stage is Thyme-SFT, which begins with training on image manipulation-related data, followed by annealing on mathematical code-related data. The learning rates for these two phases are set to 1×10^{-5} and 1×10^{-6} , respectively, while all other hyperparameters remain consistent. The batch size is set to 128, and a total of 3 epochs are trained. The checkpoint from the final epoch of this stage is used to initialize the subsequent phase. The warmup ratio is configured to 0.05. The reinforcement learning stage utilizes a learning rate of 5×10^{-7} , with training conducted for 1 epoch. The KL divergence coefficient is set to 0.001, the batch size is 256, the number of rollouts is 4, and the repetition penalty is configured to 1.05. We select Qwen 2.5 VL 7B as the backbone [2]. All training is conducted on 32 NVIDIA H800 GPUs, requiring approximately 224 GPU hours in total. The annealing stage consumes around 8 GPU hours, whereas the reinforcement learning stage demands over 1200 GPU hours.

C.2 Benchmarks and baselines

Benchmarks and metrics: We mainly select three categories of benchmarks. The first category focuses on perception tasks because Thyme's image operations mainly aim to enhance perception ability. These benchmarks include the MME-RealWorld [64] series, HR Bench [44], V* [47], RealWorld QA [48], etc. We report results for different splits of each benchmark. For example, for the MME-RealWorld series, we report perception and

²Although Gemini 2.5 Pro produces detailed and comprehensive solutions, its code tends to be overly complex and heavily annotated, making it less suitable for model training. Therefore, GPT-40 handles code conversion to produce leaner implementations.

You are a helpful assistant.

Solve the following problem step by step, and optionally write Python code for image manipulation to enhance your reasoning process. The Python code will be executed by an external sandbox, and the processed image or result (wrapped in <sandbox_output></sandbox_output>) can be returned to aid your reasoning and help you arrive at the final answer.

Reasoning & Image Manipulation (Optional but Encouraged):

- You have the capability to write executable Python code to perform image manipulations (e.g., cropping to a Region of Interest (ROI), resizing, rotation, adjusting contrast) or perform calculation for better reasoning.
- The code will be executed in a secure sandbox, and its output will be provided back to you for further analysis.
- All Python code snippets **must** be wrapped as follows:

```
<code>
```python
your code.
</code>
```

 At the end of the code, print the path of the processed image (processed\_path) or the result for further processing in a sandbox environment.

# Table 3: **User Prompt for SFT.**

```
<image>

User's Question: [User Question]

User Image Path: [Image Path]

User Image Size: [Image Size]

Output Format (strict adherence required):

<think>Your detailed reasoning process, including any code, should go here.

<answer>Your final answer to the user's question goes here.</answer>
```

reasoning accuracy separately. For HR Bench, we report Fine-grained Single-instance Per-676 ception (FSP) and Fine-grained Cross-instance Perception (FCP) separately. For V\* [47], we 677 report recognition and spatial relationship reasoning performance. The second category is reasoning tasks since Thyme not only manipulates images but also can transform complex computations into code, thus its reasoning ability is also strengthened. Therefore, we select 680 MathVision [43], MathVista [25], MathVerse [57], LogicVista [49], WeMath [32], and Visu-681 Logic [53] to verify the model's reasoning ability. The third category consists of more general 682 tasks, which primarily verify whether the model gains some performance improvement 683 in general tasks as perception and reasoning abilities increase. These benchmarks include 684 Hallucination bench [21], MMStar [3], MMVet Hard [55], OCR Bench [22], Chart QA [26], and BLINK [12].

Table 4: **Performance Comparison on Perception, Reasoning, and General Tasks.** For all open-source models, the best performance for each metric is **bolded**, and the second best is <u>underlined</u>. Gold-colored font indicates improvement over the baseline Qwen 2.5-VL 7B.

Benchmark	Split	Thyme-VL 7B	Qwen2.5-VL 7B	InternVL3 8B	<b>Qwen2.5-VL</b> 32B	GPT-40	
Perception							
	FSP	91.0 <sub>+5.8</sub>	85.2	78.8	<u>87.5</u>	66.8	
HRbench-4K	FCP	$63.0_{+10.8}$	52.2	61.3	<u>59.3</u>	63.3	
	Overall	77.0 + 8.2	68.8	70.0	<u>73.4</u>	65.0	
	FSP	86.5+7.7	78.8	78.8	82.3	60.8	
HRbench-8K	FCP	$57.5_{+5.7}$	51.8	59.8	<u>58.5</u>	58.5	
	Overall	$72.0_{+6.7}$	65.3	69.3	<u>70.4</u>	59.6	
	Perception	$67.1_{+6.5}$	60.6	63.5	<u>63.8</u>	64.9	
MME-Real	Reasoning	$48.4_{+9.8}$	38.6	<u>44.9</u>	40.4	47.3	
	Overall	$64.8_{+6.6}$	58.3	<u>61.3</u>	61.0	62.8	
	Perception	$70.5_{+2.5}$	<u>68.0</u>	65.5	<u>68.0</u>	63.6	
MME-Real-CN	Reasoning	$52.1_{+6.5}$	45.6	<u>50.0</u>	44.4	51.3	
	Overall	64.6 <sub>+3.8</sub>	<u>60.8</u>	60.5	60.5	59.7	
	Perception	$59.1_{+10.4}$	48.8	<u>51.0</u>	50.6	54.4	
MME-Real-Lite	Reasoning	$49.1_{+11.3}$	37.7	44.8	39.3	48.3	
	Overall	55.2+11.1	44.1	<u>48.6</u>	46.2	52.0	
	Attribute	83.5 + 5.3	<u>78.2</u>	67.8	77.4	72.2	
V*	Spatial	80.3 + 6.7	73.6	73.7	86.8	60.5	
	Overall	82.2+5.8	76.4	70.2	<u>81.2</u>	67.5	
RealWorld QA	Overall	$70.2_{+2.0}$	68.2	<u>70.0</u>	70.2	75.5	
			Reasoning				
MathVision	Mini	27.6 + 0.6	27.0	26.3	35.2	36.5	
MathVista	Mini	$70.0_{\pm 1.8}$	68.2	<u>70.4</u>	72.2	63.4	
MathVerse	Vision Only	$\frac{39.1}{100}$ +3.9	35.2	29.2	40.0	35.3	
LogicVista	Overall	$\frac{49.0}{20.2}$ + 9.2	39.8	45.6	54.4	53.2	
WeMath	Overall	$\frac{39.3}{22.4}$ +5.0	34.3	31.7	47.1	44.2	
VisuLogic	Overall	23.4+3.4	20.0	<u>24.9</u>	25.8	26.7	
		<b>5</b> 4.0	General	( <b>=</b> 0		(F.O.	
	aAcc	$\frac{71.0}{49.2}$ +5.4	65.6	65.9	71.2	65.2	
Hallucination	fAcc	48.3+9.4	38.8	41.3	50.6	44.8	
	qAcc Overall	$\frac{47.7}{55.6}$ +7.3	40.4 48.3	40.7 49.3	49.2 57.0	40.7 50.2	
						<u>!</u>	
MMStar	Overall	65.9 <sub>+1.2</sub>	64.7	<u>68.5</u>	69.1	65.7	
MMVet Hard	Overall	58.3 <sub>+5.5</sub>	52.9	<u>55.1</u>	48.4	58.3	
OCR Bench	Overall	86.3-2.1	88.4	<u>88.1</u>	85.5	809.0	
	Human	$80.0_{+7.5}$	72.5	<u>77.0</u>	76.9	79.5	
Chart QA	Augment	<u>92.2</u> -2.7	94.9	94.9	82.6	91.9	
	Overall	86.1+2.4	83.7	<u>85.9</u>	81.1	85.7	
BLINK	Val	56.1-0.3	<u>56.4</u>	55.5	63.6	63.3	

**Baselines:** We take Qwen-2.5-VL-7B [1] as the primary baseline. Additionally, we compare the performance of Thyme-7B with other MLLMs such as InternVL3-8B [68], as well as larger-scale models including Qwen-2.5-VL-32B and the closed-source model GPT-4o [28]. To ensure a fair comparison, we employ VLMEvalKit [7] as the evaluation pipeline.

#### C.3 Evaluation Results

**Main Results:** Table 4 presents a comprehensive comparison between Thyme and other leading multimodal models across a range of benchmarks covering *Perception, Reasoning,* and *General* tasks. In perception tasks, Thyme demonstrates clear advantages even over larger-scale models such as Qwen2.5-VL 32B, indicating that simply scaling model size does not effectively address perception challenges. Instead, Thyme's test-time scaling strategy proves

Table 5: **Performance Comparison on the MME-Realworld.** Thyme-7B demonstrates substantial improvements over the Qwen2.5-VL-7B baseline, particularly in more challenging perception and reasoning domains such as Monitoring and Autonomous Driving, where the baseline's performance is weaker.

Model Owen2.5-VL-7B	Monitoring 38.75	Perce Autonomous Driving 22.70	eption OCR 87.00	Diagram and Table 78.83	Remote Sensing 45.40	Overall 60.94
Thyme-VL-7B Improvement ↑	49.27 27.14%	37.46 64.99%	88.36 1.56%	80.86 2.57%	53.93 18.80%	67.10 10.10%
		Reas	oning			
Model	Monitoring	Autonomous Driving	OCR	O	Remote Sensing	Overall
Qwen2.5-VL-7B Thyme-VL-7B	26.10 47.39	24.25 32.29	64.80 70.60	63.40 70.40	-	38.59 48.38
Improvement ↑	81.57%	33.16%	8.95%	11.04%	-	25.37%

highly beneficial for perception tasks. Furthermore, by converting complex computations into executable code through training, Thyme achieves notable improvements in reasoning abilities. However, in this domain, the benefits of scaling model size are more pronounced, suggesting that reasoning and logical inference capabilities largely depend on the inherent knowledge within the model itself. Thyme mainly enhances visual recognition quality and helps avoid the model independently predicting overly complex computations. Finally, due to the improvements in both perception and reasoning, Thyme shows significant gains in many general tasks, particularly with a substantial reduction in hallucination.

**Delve deep into perception tasks:** Taking MME-Realworld as an example, it includes many high-resolution perception tasks in real-world scenarios. In Table 5, we show the performance of Thyme and the baseline on various tasks. It can be seen that on tasks where the baseline model already performs well, such as OCR, Diagram and Table, achieving accuracy of over 60% and even close to 90%, the improvement from Thyme is limited. However, for more difficult tasks where Qwen2.5-VL-7B's perception is relatively poor, such as monitoring and autonomous driving, Thyme shows an improvement of over 25% in both perception and reasoning tasks, with the improvement in reasoning tasks being more pronounced.

#### 713 C.4 Ablation and Analysis

#### 4 C.4.1 The Impact of Training Strategies on the SFT Process

In this subsection, we conduct detailed ablations on different strategies during the SFT phase.
The specific results appear in Table 6. Below we introduce and compare these strategies.

- ♦ Naive SFT: This approach directly uses all data for SFT without incorporating any of our training strategies. Direct SFT does not yield significant performance gains, and the model's output format is quite chaotic. During inference, it tends to predict the content of the sandbox on its own, and the code blocks and sandbox outputs are sometimes overwritten by the model's own predictions.
- ♦ **Mask Sandbox:** In the SFT stage, we mask sandbox labels and outputs. This requires the model only to learn how to write code and how to perform further reasoning based on the returned results, leading to a significant enhancement in performance.
- Only Last Round: This strategy masks information from previous rounds. For tasks involving multi-round code execution, the model only needs to learn the output of the final round. This effectively prevents the model from learning strange patterns, such as a tendency to produce a suboptimal piece of code in the first round and then correct it in subsequent rounds.
- Without Code Comment: We also investigate the impact of the presence of comments in the code on the model's performance. In this line of experiments, we remove all comments from the code in the SFT data for training, but we find the results are not satisfactory. We speculate the reason is that while comments do not play a role during code execution, the process of writing comments implies an understanding of the code, making the model more logical when it writes code.

Table 6: **Impact of Different SFT Strategies.** Directly mixing all SFT datasets for training does not yield optimal results. Instead, targeted strategies are necessary, such as masking sandbox content in the SFT data, training multi-turn interactive tasks using only the final turn, and employing annealing training on small batches of math calculation data to teach the model corresponding coding behaviors effectively.

	1 0							
Training Data	<b>Benchmark</b> Split	Hallucination Overall	MME-Rea Perception	lworld-Lite Reasoning	<b>V*</b> Overall	HRBench 8K Overall	MathVista mini	RealWorld QA Overall
-	Qwen 2.5 VL 7B	48.29	48.75	37.73	76.40	65.50	68.20	68.20
Ours								
All	Naive SFT + Mask Sandbox + Only Last Round + wo Code Comment	42.20 50.20 52.88 51.43	43.97 50.10 50.47 49.13	36.00 42.90 45.46 44.27	72.72 78.50 78.53 77.48	69.75 65.34 65.12 64.90	67.60 68.70 68.40 66.70	65.62 69.01 69.67 68.32
Math Data	Annealing	53.74	51.75	45.40	79.58	65.12	68.70	69.80

Table 7: Investigation of Different Reward Design Strategies. An ablation study is performed on various reward components, which are added to a baseline reward focused on outcome and format. The study examines the effects of incorporating a Consistency reward (evaluating alignment between the reasoning and the final answer), a Process reward (scoring the quality of the thinking process), and a Code reward (based on the successful execution of generated code). Observations show that adding a Consistency reward leads to consistent performance improvements. In contrast, the Process and Code rewards do not yield a positive gain, with the Process reward even having a negative impact on performance.

Training Data	<b>Benchmark</b> Split	Hallucination Overall	MME-Realworld-Lite Perception Reasoning		<b>V*</b> Overall	HRBench 8K Overall	MathVista mini	RealWorld QA Overall	Avg
			1	Baselines					
-	Qwen 2.5 VL 7B	48.29	48.75	37.73	76.40	65.50	68.20	68.20	59.01
Thyme-SFT Data	Thyme-SFT	53.74	51.75	45.40	79.58	65.12	68.70	69.80	62.01
			Rev	vard Design					
	Outcome+Format	58.20	53.70	45.60	80.10	70.75	67.40	69.41	63.59
Thyme-RL Data	+ Consistency	56.66	58.25	49.06	81.76	72.25	69.70	72.06	65.68
	+ Process Reward	55.63	52.95	44.60	80.10	72.25	67.50	67.32	62.91
	+ Code Reward	52.18	56.80	49.86	82.72	70.87	69.10	70.28	64.54

Math Data Annealing: Since our volume of code data for mathematical calculations is relatively small, when it is mixed with the full dataset for training, the model is rarely observed to write computation-related code during the inference phase. The primary goal of the SFT stage is to enable the model to learn this behavior. Therefore, although annealing this portion of the data does not show significant performance gains compared to the "Only Last Round" strategy, it more effectively introduces the behavior of using code to perform complex calculations.

#### C.4.2 The Influence of RL Reward Design on the RL Process

736

737

738

739

740

741 742

747

749

750

751

752

753

754

755

In this subsection, we explore a variety of reward design strategies, summarize the challenges encountered, and share insights with the aim of informing future work, as shown in Table 7.
Besides format rewards and outcome rewards, the main additional reward functions include:

- ♦ **Consistency reward:** We provide Qwen2.5-VL-72B with the last 500 characters of the thinking process (usually a summary) and the answer content, asking it to assess the consistency between the reasoning and the final answer.
- Code reward: This reward is the proportion of model-generated code that runs successfully, calculated by dividing the number of successfully executed codes by the total number of codes written. This reward encourages the model to write more code and ensure its correctness.
- Process reward: The entire thinking process is fed into Qwen2.5-VL-72B, which assigns a score based on the text quality and reasoning logic.

All additional rewards apply only when the model's answer is correct. This prevents the model from biasing toward generating code or maintaining consistency at the expense of




Figure 7: **Key Metrics During the RL Training Phase.** The plots illustrate the dynamic changes in average response length, accuracy reward, and consistency reward over the training steps.

rss solving the problem correctly and providing accurate answers. In other words,

Reward  $r = \text{Result Reward} \times (1 + 0.5 \times \text{Additional Reward}) + 0.5 \times \text{Formatting Reward}$ .

As we can see from Table 7, the consistency reward brings consistent performance improvements, which aligns with observations from existing work. Scoring the quality of the reasoning process increases the computational overhead for the reward but, conversely, has a negative impact on performance. This is largely because the process score is highly subjective and easy to "hack". Similarly, during training, we observe that the code reward does, to some extent, encourage the model to write more code to help answer the question. However, this code is not always essential for the problem—for instance, cropping an uncomplicated graph, performing a very simple addition with code, or even generating a code block that contains only comments. Consequently, it does not yield a positive gain in performance.

#### C.4.3 Analysis of the RL Learning Process

Figure 7 illustrates the dynamics of several critical metrics during the RL process, from which we derive the following observations and findings.

First, the average response length shows a rapid initial decrease before gradually converging. This phenomenon stems from the SFT phase, which introduces a large volume of synthetically generated image operation data to teach the model code generation for problem-solving. However, the images in this dataset are often not complex, rendering many of the coding operations non-essential. During the RL phase, the model quickly discerns that for a majority of tasks, a direct textual response is more efficient than a code-based analysis. Consequently, there is a swift reduction in the generation of unnecessary code. Second, the result reward exhibits a generally upward trend, which aligns with our expectations for a successful learning process. A more noteworthy observation pertains to the consistency reward. In the initial training stages, the average result reward is approximately 0.5, whereas the average consistency reward is only 0.15. This disparity indicates that a significant number of initially correct answers lack coherent reasoning, highlighting the critical role of the consistency reward. By incorporating this reward, the model is incentivized to align its reasoning with its final output. As training progresses, the result reward converges to approximately 0.7, while the consistency reward increases to nearly 0.35. This demonstrates that the inclusion of the consistency reward substantially mitigates the problem of contradictions between the model's reasoning and its answers.

#### C.5 Case studies

759

760

761

762

763

764

765

766

767

768

771

772

773

776

777

778

779

780

781

782

785

786

787

# 789 C.5.1 Cropping & Zooming

**Question:** What street is indicated by the sign on the pole near the center bottom of the image? Options: A. MACHIGAN B. MACHLGUN C. MICHIGUN D. MICHIGAN

Please select the correct answer from the options above.

#### Model Responses: <think>

The task involves identifying the street name indicated by the sign located near the center bottom of the image. The sign appears small and somewhat distant, making it challenging to read clearly without zooming in. Cropping and zooming in on this specific region will enhance the visibility of the text on the sign, allowing for accurate identification of the street name. The sign is positioned near the lower part of the image, slightly to the right of the center. By cropping this area, we can focus on the sign and improve its readability. The coordinates for cropping can be estimated based on the sign's position relative to the entire image. Here is the Python code to crop and zoom in on the relevant section:

```
N MICHIGAN AV
```

```
import os
import random
from PIL import Image
Load the image
image_path = "hr_bench_4k/179.jpg"
image = Image.open(image_path)
Define the cropping coordinates (x1, y1, x2, y2)
These coordinates are estimated based on the sign's
position in the image
x1, y1, x2, y2 = 1550, 2650, 1850, 2750
Crop the image
cropped_image = image.crop((x1, y1, x2, y2))
Apply a zoom factor (optional, depending on the
required level of detail)
zoom_factor = 2
zoomed_image = cropped_image.resize((cropped_image.width
* zoom_factor, cropped_image.height * zoom_factor))
Save the processed image with a random suffix
random_suffix = random.randint(1000, 9999)
processed_filename = f"179_{random_suffix}.jpg"
processed_path = "/mnt/data/temp_processed_images/" +
processed_filename
zoomed_image.save(processed_path)
Print the path of the saved cropped image
print(processed_path)
```

<sandbox\_output> <subimage\_sign> </sandbox\_output> Upon examining the cropped and zoomed-in image, the sign clearly reads N MICHIGAN AV 100 E: This confirms that the street indicated by the sign is Michigan Avenue. 
 <think><<answer> D. MICHIGAN </answer>

Figure 8: **Cropping & Zooming Case 1.** Thyme first evaluates the size and distance of the sign, determining that cropping and zooming in on the corresponding area would improve visibility. It then proceeds to write code to crop and enlarge the region containing the sign. Thyme accurately locates the sign's position, successfully crops and zooms in on the area, and correctly answers the question.

**Question:** What is the phone number listed on the building in the foreground? Options: A. 206 441 5000 B. 206 451 5000 C. 206 444 5000 D. 206 441 4000

Please select the correct answer from the options above.

#### Model Responses: <think>

import cv2


The task involves identifying the phone number listed on a building in the foreground of the image. The number appears to be written vertically on a sign attached to a tall building. To accurately read the digits, it is necessary to zoom in on this specific area of the image. The sign is located on the left side of the building, near the center of the lower part of the image. Cropping and zooming in on this region will enhance the clarity of the text, making it easier to discern the correct digits. The coordinates for cropping are estimated based on the position of the sign relative to the entire image. The cropped area should focus on the vertical text on the building, which is approximately in the middle-left section of the image. This targeted cropping will isolate the relevant part of the image, improving readability. Here is the Python code to crop and zoom into the specified area:

```
SES SECULLAR IN SOCIAL STATES AND SOCIAL STATES
```

```
import os
import random
Load the image
image_path = "hr_bench_4k/224.jpg"
image = cv2.imread(image_path)
Define the cropping coordinates (x1, y1, x2, y2)
x1, y1, x2, y2 = 1750, 1950, 1850, 2600
Crop the image
cropped_image = image[y1:y2, x1:x2]
Apply zoom (resize the cropped image to enhance
details)
zoom_factor = 2
zoomed_image = cv2.resize(cropped_image, None,
fx=zoom_factor, fy=zoom_factor,
interpolation=cv2.INTER_CUBIC)
Save the processed image with a random suffix
random_suffix = random.randint(1000, 9999)
processed_filename = f"224_{random_suffix}.jpg"
processed_path = "/mnt/data/temp_processed_images/" +
processed_filename
cv2.imwrite(processed_path, zoomed_image)
Print the path of the saved cropped image
print(processed_path)
```

<sandbox\_output> <subimage\_phone\_number> </sandbox\_output> Upon examining the cropped and zoomed-in image, the phone number listed on the building is clearly visible. The digits are arranged vertically, and they read 206 441 5000: This matches option A. The other options do not correspond to the digits shown on the building's sign.

Figure 9: **Cropping & Zooming Case 2.** Thyme accurately locates the phone number's position, successfully crops and zooms in on the area, and correctly answers the question.



**Question:** What is the number of awning-tricycles in the image? Options: A. 78 B. 72 C. 43 D. 63 E. The image does not feature the awning-tricycles Please select the correct answer from the options above.

#### Model Responses: <think>

To determine the number of awning-tricycles in the image, we need to carefully examine the entire scene. The awning-tricycles are likely small objects that might be difficult to spot due to their size relative to the overall image. Cropping and zooming in on specific regions where awning-tricycles might be present can help identify them more accurately. The awning-tricycles appear to be located near the lower part of the image, close to the road and possibly parked or moving along the street. By cropping and zooming in on this area, we can focus on the relevant details and count the awning-tricycles more precisely. Let me proceed with cropping and zooming in on the lower part of the image where awning-tricycles are likely to be found:

```
import os
import random
from PIL import Image
Load the image
image_path = "MME-RealWorld/10993.jpg"
image = Image.open(image_path)
Define the coordinates for cropping (based on the
inferred region)
x1, y1, x2, y2 = 0, 1000, 1000, 1500 # Adjust these
coordinates based on the image content
Crop the image
cropped_image = image.crop((x1, y1, x2, y2))
Apply zoom (resizing the cropped image for better
visibility)
zoom_factor = 2
zoomed_image = cropped_image.resize((cropped_image.width
* zoom_factor, cropped_image.height * zoom_factor))
Save the processed image with a random suffix
random_suffix = random.randint(1000, 9999)
processed_filename = f"10993_{random_suffix}.jpg"
processed_path = "/mnt/data/temp_processed_images/" +
processed_filename
zoomed_image.save(processed_path)
```


<sandbox\_output> <subimage\_tricycle> </sandbox\_output> Upon analyzing the cropped and zoomed-in image, it becomes clear that there are no awning-tricycles visible in the scene. The focus of the image is on a road with vehicles and buildings, and no such objects can be identified. Therefore, option E is correct as the image does not feature awning-tricycles.

# Print the path of the saved cropped image

print(processed\_path)

<answer> E. The image does not feature the awning-tricycles </answer>

Figure 10: **Cropping & Zooming Case 3.** Thyme first analyzes the size of the awning-tricycles and the image, concluding that enlarging the area most likely to contain awning-tricycles could help determine the answer to the question. It then crops and zooms in on the lower-left corner of the image for closer inspection, ultimately concluding that there are no awning-tricycles in the picture.



**Question:** Please write out the expression of the formula in the image using LaTeX format.

**Model Responses:** <think> The text in the image appears to be slanted and difficult to read in its current orientation. To improve clarity, rotating the image by a specific angle will help align the text properly and make it easier to interpret. Let me proceed with the rotation to enhance readability.

import cv2

import numpy as np

print(processed\_path)

```
import os
Load the image
image_path = "OCR_55251.png"
image = cv2.imread(image_path)
Define the rotation angle (in degrees)
angle = 172 # The angle is derived from the filename
suffix
Get the image dimensions
height, width = image.shape[:2]
Calculate the rotation matrix
rotation_matrix = cv2.getRotationMatrix2D((width / 2,
height / 2), angle, 1)
Perform the rotation
rotated_image = cv2.warpAffine(image, rotation_matrix,
(width, height))
Save the rotated image with a random suffix
random_suffix = np.random.randint(100000, 999999)
processed_path =
f"/mnt/data/temp_processed_images/OCR_55251_{random_suffix}.png
cv2.imwrite(processed_path, rotated_image)
Print the saved image path
```

<sandbox\_output> <subimage\_OCR> </sandbox\_output> After rotating the image, the text becomes more legible. The formula in the image is a decimal number with a bar over the last digit, which typically indicates a repeating decimal. The number is 0.642857, with the last digit, 7, being repeated indefinitely. This can be represented in LaTeX format as \0.\overline642857\. The bar over the digits 642857 signifies that these digits repeat continuously. This notation is commonly used to represent repeating decimals in mathematical expressions. </rr>

 $0.\overline{642857}$ 

</answer>

Figure 11: **Rotation Case.** Thyme realizes that the input image is not properly oriented, so it performs a rotation operation with Python code to adjust the angle of the input image. Then, it correctly identifies the expression in the image and represents the result with LaTeX code.

**Question:** What is written in the image? Please try to answer the question with short words or phrases if possible.

#### Model Responses: <think>

The image appears to have low contrast, which may lead to poor text extraction in OCR. The text communities somewhat faint and blends into the background, making it challenging for OCR systems to accurately recognize the characters. Enhancing the contrast will make the text stand out more clearly from the background, improving readability and OCR performance. To address this, we can use Python with the PIL library to enhance the contrast of the image. Here is the code to do so:

```
import os
import random
from PIL import Image, ImageEnhance
Load the image
image_path = "OCRBench/150.jpg"
img = Image.open(image_path)
Enhance the contrast
enhancer = ImageEnhance.Contrast(img)
enhanced_img = enhancer.enhance(2.0) # Increase
contrast by a factor of 2
Save the enhanced image with a random suffix
random_suffix = random.randint(1000, 9999)
filename, ext =
os.path.splitext(os.path.basename(image_path))
processed_filename = f"{filename}_{random_suffix}{ext}"
processed_path =
os.path.join("/mnt/data/temp_processed_images/",
processed_filename)
enhanced_img.save(processed_path)
Print the path of the saved enhanced image
print(processed_path)
```

<sandbox\_output> <subimage\_ocr> </sandbox\_output>
Upon examining the original image, the text communities faint and blends into the background. After applying the contrast enhancement, the text becomes significantly more legible. The enhanced image clearly shows the word communities, confirming that the enhancement process successfully improved the visibility of the text. 

<answer> communities </answer>

Figure 12: **Contrast Enhancement Case.** Thyme accurately locates the phone number's position, successfully crops and zooms in on the area, and correctly answers the question.

communities

# 791 C.5.3 Complex Calculations

**Question:** A chef aboard a luxury liner wants to cook a goose. The time t in hours to cook a goose at  $180^{\circ}$ C depends on the mass of the goose m in kilograms according to the formula

$$t = am^b$$

where a and b are constants. The table below gives the times observed to cook a goose at  $180^{\circ}$  C.

Mass, m (kg)	Time, t (h)
3.00	2.75
6.00	3.75

Using the data in the table, determine both a and b to two decimal places.

#### Model Responses: <think>

To find the constants a and b in the equation  $t = am^b$ , we need to use the given data points from the table. The data points are: 1.  $m_1 = 3.00 \,\text{kg}$ ,  $t_1 = 2.75 \,\text{h}$  2.  $m_2 = 6.00 \,\text{kg}$ ,  $t_2 = 3.75 \,\text{h}$ 

We can set up two equations based on these data points: 1.  $2.75 = a(3.00)^b$  2.  $3.75 = a(6.00)^b$ 

We can solve this system of equations for a and b. Let's denote x = a and y = b. Then the equations become: 1.  $2.75 = x(3.00)^y$  2.  $3.75 = x(6.00)^y$ 

Dividing the second equation by the first equation eliminates x:

$$\frac{3.75}{2.75} = \frac{x(6.00)^y}{x(3.00)^y} = \left(\frac{6.00}{3.00}\right)^y = 2^y$$

So,

$$2^y = \frac{3.75}{2.75} = \frac{15}{11}$$

Taking the logarithm base 2 of both sides:

$$y = \log_2\left(\frac{15}{11}\right)$$

Using Python to compute this value:

import math
# Calculate y = log2(15/11)
y\_val = math.log2(15/11)

print(y\_val)

<sandbox\_output> 0.44745897697122117 </sandbox\_output> So,  $y \approx 0.45$ . Now substitute y = 0.45 back into one of the original equations to find x. Using the first equation:

$$2.75 = x(3.00)^{0.45}; x = \frac{2.75}{3.00^{0.45}}$$

Using Python to compute this value:

import math
# Calculate x = 2.75 / (3.00\*\*0.45)
x\_val = 2.75 / (3.00\*\*0.45)
print(x\_val)

<sandbox\_output> 1.6773671336980667 </sandbox\_output> So,  $x \approx 1.68$ .

Therefore, the constants are  $a\approx 1.68$  and  $b\approx 0.45$ . </think> <answer> 1.68, 0.45 </answer>

Figure 13: **Complex Calculations Case.** After deducing the mathematical expressions for x and y, Thyme writes code to perform the calculations, obtaining the accurate results.

#### C.6.1 Complex Problems Without Coding




**Question:** Which machinery has the highest occupancy rate, according to the 'Occupancy Rate' diagram? Options: A. Exavators B. Graders C. Cranes D. Telehandlers E. The image does not feature the number. Please select the correct answer from the options above.

Model Responses: <think> The task is to identify which machinery has the highest occupancy rate based on the 'Occupancy Rate' diagram. The relevant section of the image is the bar chart labeled Machinery Rentals - Occupancy Rate. This chart displays the occupancy rates for different types of machinery, with percentages shown for each type. The bar chart clearly shows that Telehandlers have the highest occupancy rate at 72.2%, followed by Excavators at 78.8%, Bulldozers at 64.8%, Graders at 74.0%, and Cranes at 64.8%. Therefore, option D, Telehandlers, is the correct choice.

<answer> D. Telehandlers </answer>

Figure 14: Failure Case 1. In this case, the image resolution is high, but Thyme does not perform the necessary crop to focus on the most relevant area and instead answers directly.

# 94 C.6.2 Unuseful Coding



**Question:** Please directly answer the question and provide the final value, e.g., 1, 2.5, 300. Question: Solve for the unknown a. Please try to answer the question with short words or phrases if possible.

**Model Responses:** <think> To solve for the unknown side 'a' in the given right triangle, we can use trigonometric relationships. The triangle has a hypotenuse of length 9, one leg 'b' opposite the  $60^{\circ}$  angle, and the other leg 'a' adjacent to the  $60^{\circ}$  angle. We need to find the length of 'a'. Using the cosine function, which relates the adjacent side to the hypotenuse in a right triangle:  $\cos(60^{\circ}) = a$  / hypotenuse We know that  $\cos(60^{\circ}) = 0.5$ . So, substituting the known values: 0.5 = a / 9 To find 'a', we multiply both sides of the equation by 9: a = 0.5 \* 9 Now, let's calculate the value of 'a':

# Calculate the value of 'a'
a\_value = 0.5 \* 9
print(a\_value)

<sandbox\_output> 4.5 </sandbox\_output>
Therefore, the length of side 'a' is 4.5. </think>
<answer> 4.5 </answer>

Figure 15: **Failure Case 2.** The case requires only trivial calculations, yet Thyme opts to write code, adding unnecessary overhead. Furthermore, Thyme confuses variable a with variable b, mistaking the value of b for the value of a, which leads to an incorrect result.

# 95 C.6.3 Inaccurate Cropping



**Question:** What is the model number of the train shown in the image? Options: A. 4005 B. 1002 C. 3001 D. 2001 Please select the correct answer from the options above.

# Model Responses: <think>

The task is to identify the model number of the train shown in the image. The model number appears to be visible on the front of the train, near the bottom right corner of the train's front panel. The number is clearly visible as 2001. To ensure accuracy and confirm this observation, it would be beneficial to zoom in on this specific area of the image. Cropping the image around the train's front panel will help focus on the model number and eliminate any distractions from the surrounding environment. The coordinates for cropping can be estimated based on the position of the train in the image. The relevant area is located towards the lower right part of the train's front panel. By cropping this section, we can zoom in on the model number for a clearer view. Here is the Python code to crop and zoom in on the relevant area:

```
import os
import random
from PIL import Image
Load the image
image_path = "hr_bench_4k/243.jpg"
img = Image.open(image_path)
Define the cropping coordinates (x1, y1, x2, y2)
These coordinates are estimated based on the position
of the train's front panel
x1, y1, x2, y2 = 1600, 1900, 1900, 2200
Crop the image
cropped_img = img.crop((x1, y1, x2, y2))
Save the cropped image with a random suffix
random_suffix = random.randint(1000, 9999)
filename, ext =
os.path.splitext(os.path.basename(image_path))
processed_filename = f"{filename}_{random_suffix}{ext}"
processed_path =
os.path.join("/mnt/data/temp_processed_images/",
processed_filename)
cropped_img.save(processed_path)
Print the path of the saved cropped image
print(processed_path)
```

<sandbox\_output> <subimage\_phone\_number> </sandbox\_output>
The cropped image confirms that the model number of the train is indeed
2001: This matches option D from the given choices. 
</rr>

<answer> D. 2001 </answer>

Figure 16: **Failure Case 3.** In this case, although Thyme eventually arrives at the correct answer, the region it crops during thinking process is irrelevant to the problem.

# 96 D Annotation Requirements

This annotation document aims to ensure each image accurately describes the characteristics of target objects during the annotation process and provides clear annotation information to users. The detailed steps and requirements are as follows:

#### 800 D.1 Task Description

802

803

804

805

806

807

808

809

810

811

812

813

814

823

824

825

826

827

828

829

830

831

833

834

836

For each high-resolution image, annotators are required to complete the following tasks:

- Question Annotation: Design a specific question for each image. The target of the question should be small and difficult-to-recognize objects in the image, with the object occupying no more than 5% of the image resolution. Users need to zoom in on the image to clearly identify these small objects.
- **Answer Annotation**: Provide an accurate answer based on the question. The answer should be directly related to the question and derived from analyzing specific regions within the image.
- **Bounding Box**: Draw a bounding box for each annotated target object. The bounding box coordinates should be  $(x_1, y_1, x_2, y_2)$ , indicating the top-left and bottom-right corners of the object area. The bounding box should ensure that the cropped region clearly shows the target object.
- **Category**: Clearly specify the category of each question, selecting only from the five categories defined in the question design.

# 815 D.2 Annotation Requirements

Object Selection: Select small objects in the image as targets. The area of these small objects should not exceed 5% of the total image area. Users need to zoom in to clearly identify these objects.

Bounding Box Design: The accuracy of bounding box coordinates need not be pixel-level but must ensure that the cropped area clearly displays the object. Please roughly determine the bounding box position and size according to the object features in the image.

822 Question Design: Questions should cover multiple aspects, including but not limited to:

- OCR recognition: Identify the text content in a certain location of the image. For example, "What is written on the sign in the image?"
- Attribute recognition: Identify attributes of specific objects in the image, such as color or shape. For example, "What is the color of this object?"
- Location recognition: Determine the location of objects within the image. For example, "Where is this object located in the image?"
- Quantity recognition: Identify the number of objects of the same type in the image.
   For example, "How many apples are in the image?"
- Object recognition: Identify the type of object at a specific location in the image.
- Chart understanding: For chart-type images, identify specific data points' values, compute maximum or minimum values, or predict trends. For example, "What is the maximum value in the chart?"

#### 835 D.3 Annotation Steps

 Image Review: Open the high-resolution image and carefully examine all elements, especially small and hard-to-recognize objects.

- 2. **Object Localization**: Identify objects to be annotated, ensuring the object occupies no more than 5% of the image area. These are usually small objects or details in the background.
- 3. **Draw Bounding Box**: Use annotation tools to draw bounding boxes according to the shape and position of the target objects, ensuring the boxes fully contain the objects.
- 4. **Design Questions and Answers**: Based on specific image content, propose questions and provide appropriate answers. Questions should be concise and directly related to the target objects.
- Save Annotation Data: Record annotation information (questions, answers, bounding box coordinates) for each image, ensuring all annotations are independent and meaningful.

# 850 E Related Work

 Multimodal Large Language Models. Fueled by the advancements in LLMs the field of MLLMs has seen rapid development in recent years, with model capabilities evolving at a remarkable pace [11, 65, 54, 18]. Modern MLLMs, such as Qwen2.5-VL [2], GPT-4o [29], and LLaVA [17], have demonstrated impressive performance in processing high-resolution images and engaging in complex human-like dialogue. Research has diversified into numerous sub-domains, including extending context length [39], improving computational efficiency [61, 58], mitigating hallucinations [24, 63], enhancing conversational abilities [52], and achieving better alignment with human preferences [62]. Concurrently, more sophisticated architectures have emerged. Omni-MLLMs are capable of processing a mix of modalities like speech, video, and images simultaneously [20, 66, 9], while Unify-MLLMs can produce interleaved, mixed-modal outputs, such as generating an image with auxiliary lines to aid in solving a math problem [51, 41]. These works showcase a clear trajectory towards more integrated and versatile multimodal interaction.

Multimodal Reasoning. Enhancing the reasoning capabilities of MLLMs is a critical frontier. Recently, RL has become a prominent technique in the post-training of MLLMs, leading to significant gains in vision tasks [23, 36], multimodal reasoning [13, 31, 27], and even reward modeling itself [60]. Compared to traditional methods like SFT or Direct Preference Optimization (DPO) [33], RL-based approaches have shown superior generalization and an ability to induce more complex, long-term reasoning capabilities, as demonstrated by models like DeepSeek-R1 [6]. However, a significant limitation of many existing efforts is that they primarily focus on enhancing the textual reasoning chain. The visual input often serves as a static condition rather than an active component within the reasoning process. While some paradigms have emerged to "think with images", they are often limited to a single function like cropping [67] or generating an auxiliary image [5]. Our work, Thyme, directly addresses this gap by empowering the model to autonomously generate and execute code for a diverse range of image manipulations and computations. This allows the model to treat the image not just as input, but as a dynamic entity that can be actively interrogated and transformed as an integral part of its reasoning process.

# Table 8: Prompt template for training data generation.

You are an advanced AI assistant tasked with generating training data for a complex image processing and question-answering task. Your role is to generate an ideal response containing a detailed thought process and specific executable Python code based on the user's question and the assumed condition of the image.

User Input: <image>

User's Question: user question

User Image Path (just for code reference): user image path

#### **Core Instructions:**

Your primary task is to determine whether the image can be used directly to answer the user's question or if it requires processing.

#### 1. If the image can be used directly:

- Clearly state that the image is ready to be used without any processing.
- Do not generate any code in this case, just answer the question and include -1 in the <answer></answer> box.

#### 2. If the image needs processing:

- a). Provide a detailed description of the issues with the image that prevent answering the question, such as incorrect orientation, low contrast, lighting issues, etc.
- b). Choose the appropriate category of operation that addresses the identified issues:
  - 1. Direction Issues: If the image needs rotation or flipping.
- 2. Lighting and Contrast Issues: If the image's brightness, contrast, or lighting needs adjustment, or the contrast between the text and background in the image is low for OCR.
- **3. Scaling and Region of Interest** (**ROI**): If parts of the image need to be cropped or resized.
- **4. Combined Issues**: If more than one category applies, specify the primary issue category and reflect multi-step processing in the code.
- c). Generate specific, executable Python code to address the identified image issues.
  - For example:
    - For **Direction Issues**: Specific angles for rotation (e.g., angle = 90 or angle = -90).
    - For **Scaling/ROI**: Specific coordinates like (x1, y1, x2, y2) for cropping.
- Save the processed image in the temporary folder (/mnt/data/temp\_processed\_images/), with the same filename as the User Image Path, followed by a random suffix.
- Print the saved image path (processed\_path) in the last line to allow for further processing in a sandbox environment.
- d) The code snippet must be wrapped with: <code>

```
"python code snippet
```

</code>, and should be executable.

e). Output the Tool ID used, if applicable. If you used a tool, return the corresponding tool ID. For instance, if you used ROI-related code, return <answer>3</answer>.

#### Output Format (strictly follow):

<think>Your detailed comparative analysis and executable code goes here
10 if you use tool else -1</d>

# Table 9: Prompt template for visual QA with cropping based on bounding box.

You are an advanced AI assistant tasked with constructing reasoning and code for a visual QA task. You will receive the user's question, image, User Image Path, and Ground Truth Bounding Box Coordinates. The image path and Ground Truth Bounding Box coordinates should only be used in the code and must not be mentioned in your analysis.

```
User Input: <image>
User's Question: user question
User Image Path (just for code reference): user image path
Ground Truth Bounding Box Coordinates: (x1, y1, x2, y2)
```

Your primary task is to provide a reasonable explanation of why cropping the image is necessary to answer the user's question based on the provided bounding box coordinates.

**Important:** Do **not** mention the provided "Ground Truth Bounding Box" in your analysis. Treat the bounding box coordinates as something you have inferred based on the content of the image. You should only reference these coordinates in your **executable code**, and avoid explicitly stating them in your analysis or thought process.

- a). Provide a detailed description of why cropping is necessary. For example:
- "The task seems to be extracting text from a sign near a door under a balcony. I guess I'll need to zoom in and crop the region around the sign. The coordinates appear to be near the center of the lower part of the image above the door. I'll refine this area further for better readability. Let me get started on that!"
- b). Generate simple, executable Python code to crop the image based on the inferred bounding box coordinates.
- Save the processed image in the temporary folder (/mnt/data/temp\_processed\_images/), with the same filename as the User Image Path, followed by a random suffix.
- Print the saved image path (processed\_path) in the last line to allow for further processing in a sandbox environment.
- c) The code snippet must be wrapped with:

```
<code>
"'python
code snippet
'"
</code>, and should be executable.
```

#### Output Format (strictly follow):

**Core Instructions:** 

```
<think>Your detailed analysis of why cropping is necessary and the
executable code goes here.<think>
<answer>1</answer>
```

# Table 10: Prompt template for visual QA with image rotation.

You are an advanced AI assistant tasked with constructing reasoning and code for a visual QA task. You will receive the user's question, a rotated image, the rotation angle, and the user Image Path. The image path and rotation angle should only be used in the code and must not be mentioned in your analysis.

\_\_

User Input: <image>

User's Question: user question

User Image Path (just for code reference): user image path

GT Degree: How many degrees was the image rotated?: rotation angle

#### **Core Instructions:**

Your primary task is to provide a reasonable explanation of why rotating the image is necessary to answer the user's question based on the provided rotation angle.

- a). Provide a detailed description of why rotating the image is necessary. For example:
- "The text in the image appears to be slanted and difficult to read in its current orientation. I believe rotating the image by a specific angle will help align the text properly and make it easier to interpret. Let me proceed with the rotation to improve clarity."
- b). Generate simple, executable Python code to rotate the image by the inferred angle.
- Save the processed image in the temporary folder (/mnt/data/temp\_processed\_images/), with the same filename as the User Image Path, followed by a random suffix.
- Print the saved image path (processed\_path) in the last line to allow for further processing in a sandbox environment.
- c) The code snippet must be wrapped with:

```
<code>
"'python
code snippet
"'
```

</code>, and should be executable.

The sum of your rotation angle and the GT Degree must be either 0 or 360; it should never be 180 or -180. And you do not need to answer the question.

**Important:** Do **not** mention the provided "GT Degree" in your analysis. Treat the GT Degree as something you've inferred based on the content of the image. You should only reference this angle in your **executable code**, and avoid explicitly stating it in your analysis, thought process, and comments in the code.

\_

# Output Format (strictly follow):

<think>Your detailed analysis of why rotating the image is necessary and
the executable code goes here.<think>

<answer>1</answer>

# 79 NeurIPS Paper Checklist

#### 1. Claims

Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

Answer: [Yes]

Justification: Please refer to the abstract and Section 1, and the experimental results in Section 5.

#### Guidelines:

- The answer NA means that the abstract and introduction do not include the claims made in the paper.
- The abstract and/or introduction should clearly state the claims made, including
  the contributions made in the paper and important assumptions and limitations.
  A No or NA answer to this question will not be perceived well by the reviewers.
- The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
- It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

#### 2. Limitations

Question: Does the paper discuss the limitations of the work performed by the authors?

Answer: [Yes]

Justification: We discuss limitations of our method and future work in Section 6.

#### Guidelines:

- The answer NA means that the paper has no limitation while the answer No means that the paper has limitations, but those are not discussed in the paper.
- The authors are encouraged to create a separate "Limitations" section in their paper.
- The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
- The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
- The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
- The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
- If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
- While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

#### 3. Theory assumptions and proofs

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [NA]

931

932

933

934

935

936

938

939

941

942 943

945

946

947

948

952

953

954

955

956

960

961

962

963

964

965

966

967

968

969

970

971

972

973 974

976

977

980

Justification: The paper does not include theoretical results.

# Guidelines:

- The answer NA means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

#### 4. Experimental result reproducibility

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [Yes]

Justification: We describe the implementation details and experimental settings in appendix  $\mathbb{C}$ .

### Guidelines:

- The answer NA means that the paper does not include experiments.
- If the paper includes experiments, a No answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
- (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
- (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
- (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).

(d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

# 5. Open access to data and code

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: [Yes]

Justification: We open-source our code and will also open-source the data after the review process.

#### Guidelines:

- The answer NA means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (https://nips.cc/public/guides/CodeSubmissionPolicy) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so "No" is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (https://nips.cc/public/guides/CodeSubmissionPolicy) for more details.
- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

#### 6. Experimental setting/details

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer, etc.) necessary to understand the results?

Answer: Yes

Justification: We describe the implementation details and experimental settings in appendix C.

#### Guidelines:

- The answer NA means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
- The full details can be provided either with the code, in appendix, or as supplemental material.

# 7. Experiment statistical significance

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

1036	Answer: [No]
1037	Justification: The experiments are too computationally expensive.
1038	Guidelines:
1039	• The answer NA means that the paper does not include experir
1040	• The authors should answer "Yes" if the results are accompanie
1041	confidence intervals, or statistical significance tests, at least for t
1042	that support the main claims of the paper.

- nents.
- ed by error bars, the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g. negative error rates).
- If error bars are reported in tables or plots, The authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

#### 8. Experiments compute resources

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

Answer: Yes

1043

1046

1047

1048

1049

1050

1051

1052

1053

1054

1055

1056

1057

1058 1059

1060

1061

1062

1063

1064

1065

1066

1067

1068

1069

1070

1072

1073

1074

1075

1076

1077

1078

1079

1080

1081

1082

1083

1084

1085

1086

Justification: We detail the compute resources consumed, in appendix C.1.

#### Guidelines:

- The answer NA means that the paper does not include experiments.
- The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
- The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
- The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

# 9. Code of ethics

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics https://neurips.cc/public/EthicsGuidelines?

Answer: Yes

Justification: We have ensured that the paper complies with the guidelines.

# Guidelines:

- The answer NA means that the authors have not reviewed the NeurIPS Code of Ethics.
- If the authors answer No, they should explain the special circumstances that require a deviation from the Code of Ethics.
- The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

# 10. Broader impacts

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: [NA]

Justification: There is no societal impact of this work.

#### Guidelines:

- The answer NA means that there is no societal impact of the work performed.
- If the authors answer NA or No, they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

#### 11. Safeguards

Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pretrained language models, image generators, or scraped datasets)?

Answer: [NA]

Justification: This paper poses no such risk since we manually check and filter the data, and make necessary requirements on possible usage.

#### Guidelines:

- The answer NA means that the paper poses no such risks.
- Released models that have a high risk for misuse or dual-use should be released
  with necessary safeguards to allow for controlled use of the model, for example
  by requiring that users adhere to usage guidelines or restrictions to access the
  model or implementing safety filters.
- Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
- We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

#### 12. Licenses for existing assets

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

#### 1140 Answer: [Yes]

1141

1142

1143

1144

1146

1147

1148

1150

1151

1152

1153

1154

1155

1156

1157

1158

1160

1161

1162

1163

1164

1165

1166

1167

1168

1169 1170

1171

1173

1174

1175

1176 1177

1178

1179

1180

1181

1182

1183

1184

1185

1186

1187

1188

1189

1190

1191

Justification: All the assets we used are properly credited and sourced from open-source platforms like Github and HuggingFace, under the license of Apache-2.0.

#### Guidelines:

- The answer NA means that the paper does not use existing assets.
- The authors should cite the original paper that produced the code package or dataset.
- The authors should state which version of the asset is used and, if possible, include a URL.
- The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, paperswithcode.com/datasets has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

#### 13. New assets

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: [Yes]

Justification: We provide detailed documentation alongside the released assets.

#### Guidelines:

- The answer NA means that the paper does not release new assets.
- Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
- The paper should discuss whether and how consent was obtained from people whose asset is used.
- At submission time, remember to anonymize your assets (if applicable). You
  can either create an anonymized URL or include an anonymized zip file.

# 14. Crowdsourcing and research with human subjects

Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer: [NA]

Justification: Our paper does not involve crowdsourcing nor research with human subjects.

#### Guidelines:

- The answer NA means that the paper does not involve crowdsourcing nor research with human subjects.
- Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
- According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

# 15. Institutional review board (IRB) approvals or equivalent for research with human subjects

Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

Answer: [NA]

Justification: Our paper does not involve crowdsourcing nor research with human subjects.

#### Guidelines:

- The answer NA means that the paper does not involve crowdsourcing nor research with human subjects.
- Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
- We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
- For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

## 16. Declaration of LLM usage

Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does not impact the core methodology, scientific rigorousness, or originality of the research, declaration is not required.

Answer: [Yes]

Justification: We describe how we use multimodal-LLMs for data quality control in appendix B.

#### Guidelines:

- The answer NA means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
- Please refer to our LLM policy (https://neurips.cc/Conferences/2025/LLM) for what should or should not be described.