

# SKILL PREFERENCES: LEARNING TO EXTRACT AND EXECUTE ROBOTIC SKILLS FROM HUMAN FEEDBACK

**Anonymous authors**

Paper under double-blind review

## ABSTRACT

A promising approach to solving challenging long-horizon tasks has been to extract behavior priors (skills) by fitting generative models to large offline datasets of demonstrations. However, such generative models inherit the biases of the underlying data and result in poor and unusable skills when trained on imperfect demonstration data. To better align skill extraction with human intent we present Skill Preferences (SkiP), an algorithm that learns a model over human preferences and uses it to extract human-aligned skills from offline data. After extracting human-preferred skills, SkiP also utilizes human feedback to solve downstream tasks with RL. We show that SkiP enables a simulated kitchen robot to solve complex multi-step manipulation tasks and substantially outperforms prior leading RL algorithms with human preferences as well as leading skill extraction algorithms without human preferences.

## 1 INTRODUCTION

Deep reinforcement learning (RL) is a framework for solving temporally extended tasks that has resulted in a number of breakthroughs in autonomous control including mastery of the game of Go (Silver et al., 2018; 2017), learning to play video games Mnih et al. (2015); OpenAI (2018); Vinyals et al. (2019), and learning basic robotic control (Akkaya et al., 2019; Kalashnikov et al., 2018). However, today’s RL systems require substantial manual human effort to engineer rewards for each task which comes with two fundamental drawbacks. The human effort required to design rewards is impractical to scale across numerous and diverse task categories and the engineered rewards can often be exploited by the RL agent to produce unintended and potentially unsafe control policies (Hadfield-Menell et al., 2017; Amodei et al., 2016; Turner et al., 2020). Moreover, it becomes increasingly difficult to design reward functions for the kinds of complex tasks with compositional structure often encountered real-world settings. In this work, we are interested in the following research question - *how can we learn robotic control policies that are aligned with human intent and capable of solving complex real-world tasks?*

Human-in-the-loop RL Christiano et al. (2017); Ibarz et al. (2018); Lee et al. (2021) has emerged as a promising approach to better align RL with human intent that proposes an alternate approach to traditional RL algorithm design. Rather than manually engineering a reward function and then training the RL agent, human-in-the-loop RL proposes for humans to provide feedback interactively to the agent as it is training. This paradigm shift sidesteps reward exploitation by providing the RL algorithm immediate feedback to align it best with human intent and, if efficient in terms of human labels required, has the potential to scale RL training across a diverse variety of tasks more reliably than reward engineering.

So far human-in-the-loop RL systems have been used to play Atari games Ibarz et al. (2018), solve simulated locomotion and manipulation tasks Christiano et al. (2017); Lee et al. (2021), and better align the output of language models Ziegler et al. (2019). While these initial results have been promising, human-in-the-loop methods are still out of reach for the kinds of long-horizon compositional tasks that are desired for real-world robotics. The primary reason is that current methods do not scale efficiently with respect to human labels for more challenging tasks. As task complexity increases, the number of human feedback interactions required to attain a suitable policy becomes impractical.




Figure 1: Our method - Skill Preferences (SkiP) - consists of two phases. During the skill extractions phase, human feedback is used to learn skills. During the skill execution phase, human feedback is used to finetune the skills to solve various downstream tasks. First, skills are extracted from a noisy offline dataset with human feedback. Second, skills are executed with RL in the environment with task-specific human feedback.

To address the ability of RL algorithms to scale to more complex long-horizon tasks, a number of recent works Pertsch et al. (2020); Singh et al. (2021); Ajay et al. (2021) have proposed data-driven extraction of behavioral priors, which we refer to as *skills*. In these methods, a behavioral prior is fit to an offline dataset of demonstrations and is then used to guide the RL policy to solve downstream tasks by regularizing it to stay near the behavioral distribution. Such methods have been shown to successfully solve tasks such as diverse object manipulation Singh et al. (2021) and operating a kitchen with a robotic arm Pertsch et al. (2020). However, they still require engineered rewards for the downstream tasks and, more importantly, assume access to a clean offline dataset of expert demonstrations that are specifically relevant to the downstream tasks. In real-world scenarios, such clean datasets are highly unlikely to exist. We desire skill extraction methods that are robust to noisy datasets, collected by a range of policies, with highly multi-modal structure.

In this work, we introduce Skill Preferences (SkiP), an algorithm that integrates human-in-the-loop RL with data-driven skill extraction. Our main insight is that human feedback can be incorporated not only for downstream RL, as is done in prior work, but also for extracting human-aligned skills. SkiP learns a human preference function and uses it to weigh the likelihood of trajectories in the offline dataset based on their degree of alignment with human intent. By incorporating human feedback during skill extraction, SkiP is able to extract structured human-preferred skills from noisy offline data and addresses the core limitation of prior skill extraction approaches - the dependence on curated expert datasets. SkiP is both capable of efficiently extracting skills and solving different downstream tasks with respect to human labels. Similar to how prior work in human-in-the-loop RL suggested replacing manually engineered reward functions with human feedback, our work suggests to replace the manual effort needed to curate clean offline datasets with human feedback. We summarize our main contributions below:

1. We introduce Skill Preferences (SkiP), an algorithm that incorporates human feedback to extract skills from offline data and utilize those skills to solve downstream tasks.
2. We show that, unlike prior leading methods for data-driven skill extraction, SkiP is able to extract structured skills from noisy offline datasets.
3. We show that SkiP is able to solve complex multi-step manipulation tasks in robotic kitchen environment substantially more efficiently than prior leading human-in-the-loop and skill extraction baselines.

## 2 BACKGROUND

**Reinforcement Learning:** As is common with RL methods, we assume that the control process is a Markov Decision Process (MDP) with discounted returns. Such MDPs are defined by the tuple  $\mathcal{M} = (\mathcal{S}, \mathcal{A}, R, \rho_0, \gamma)$  consisting of states  $s \in \mathcal{S}$ , actions  $a \in \mathcal{A}$ , rewards  $R = R(s, a)$ , an initial state distribution  $s_0 \sim \rho_0(\cdot)$ , and a discount factor  $\gamma \in [0, 1)$ . A control policy maps states to

actions within the MDP and usually takes the form of a probability distribution  $a \sim \pi(\cdot|s)$ . The value function  $V^\pi(s)$  and action-value function  $Q^\pi(s, a)$  describe the value with respect to future expected returns with respect to an initial state or state-action pair.

$$V^\pi(s) := \mathbb{E}_{\mathcal{M}, \pi} \left[ \sum_{t=0}^{\infty} \gamma^t R(s_t, a_t) \mid s_0 = s \right], \quad Q^\pi(s, a) := R(s, a) + \gamma \mathbb{E}_{s' \sim T(\cdot|s, a)} [V^\pi(s')],$$

where the first expectation  $\mathbb{E}_{\mathcal{M}, \pi}$  denotes actions are sampled according to  $\pi$  and future states are sampled according to the MDP dynamics. The goal in RL is to learn the optimal policy:

$$\pi^* \in \arg \max_{\pi} J(\pi, \mathcal{M}) := \mathbb{E}_{s \sim \rho_0} [V^\pi(s)].$$

In addition to the standard MDP setting, our method will also learn skills  $z \in \mathcal{Z}$  which consist of an encoder that maps state-action sequences to a skill  $q^{(e)}(z|s_t, a_t, \dots, s_{t+H-1}, a_{t+H-1})$  and a decoder that maps state-skill pairs to atomic actions  $q^{(d)}(a_1, a_2, \dots, a_H|s, z)$ .

### 3 METHOD

The two primary contributions of SkiP are (i) introducing human feedback during the skill extraction process to learn structured skills from noisy data and (ii) utilizing human preferences over skills for downstream RL training. Our approach shown schematically in Fig. 1 and detailed in full in Algo. 1. Due to utilizing human feedback to learn the behavioral prior, unlike prior approaches of skill extraction from offline data Ajay et al. (2021); Singh et al. (2021); Pertsch et al. (2020), our method is robust to suboptimal or noisy data.

**The SkiP Algorithm:** We first summarize the algorithm and then proceed with its derivation. Shown in Algo. 1, SkiP consists of two phases - (i) *skill extraction* and (ii) *skill execution*. A human teacher provides feedback during *both* phases. During skill extraction, a human teacher labels whether a trajectory is preferred or not (for details see Sec. 4) to train a preference classifier. A behavioral prior is then fit to the offline data with a weighted human preference function. During skill execution, the learned skills are rolled out by an RL agent - a Soft Actor-Critic (SAC) Haarnoja et al. (2018) - that is trained with task-specific human preferences. As such, human feedback is used during both phases of the algorithm. We proceed to define notation and provide a derivation.

**Preliminaries and Notation:** Our method is composed of two phases - (i) the skill extraction phase and (ii) the skill execution phase. During the skill extraction phase, we are given an offline dataset  $\mathcal{D}$  which consists of task-agnostic, multi-modal, and potentially noisy demonstrations. We denote trajectory sequences as  $\tau_t = (s_t, a_t, \dots, s_{t+H-1}, a_{t+H-1})$ , action sequences as  $\mathbf{a}_t = (a_t, \dots, a_{t+H-1})$ , and skills which decode into action sequences as  $z \in \mathcal{Z}$ .

**Learning Behavioral Priors with Human Feedback (Skill Extraction):** Our main insight is to use human preferences in order to fit a weighted behavioral prior over an offline dataset of (potentially noisy) demonstrations. Our method builds on prior work for behavioral extraction from offline data via expected maximum likelihood latent variable models Ajay et al. (2021); Singh et al. (2021); Pertsch et al. (2020).

Specifically, prior work Ajay et al. (2021); Singh et al. (2021); Pertsch et al. (2020) considers a parameterized generative model  $p_\alpha(\mathbf{a}_t|s_t)$  over action sequences where  $\mathbf{a}_t = (a_t, \dots, a_{t+H-1})$  that represents a behavioral prior and is trained to replicate the transition statistics in the offline dataset:

$$p_\alpha \in \arg \max_{\alpha} \mathbb{E}_{\tau \sim \mathcal{D}} \left[ \sum_{t=0} \log \left( p_\alpha(\mathbf{a}_t|s_t) \right) \right]. \quad (1)$$

In our approach, we consider an adaptive behavioral prior that is biased towards trajectories that achieve higher rewards according to the human preference function. This can be particularly useful in diverse datasets collected with suboptimal or noisy policies or multiple policies of varying expertise. For example, one could imagine multiple humans collecting demonstrations or multiple robots exploring their environment. Similar to Siegel et al. (2020), we seek a behavioral prior that is biased towards the high reward trajectories in the dataset while also staying close to the average statistics in the dataset. However, unlike prior work on weighted behavioral priors Siegel et al. (2020); Peng

**Algorithm 1** SkiP: Skill Preferences

---

```

==== Skill Extraction Phase ====
INPUT: offline dataset  $\tilde{\mathcal{B}}$ 
Initialize prior  $p$ , skill encoder  $q_{\phi_2}$  and skill decoder  $p_{\phi_1}$ . Initialize learned preference classifier  $P_\psi$ 
A human provides labels  $(y_1, y_2, \dots)$  for 10% of the trajectories in  $\tilde{\mathcal{B}}$  and stores them in a new buffer  $\tilde{\mathcal{D}}$ 
for each iteration do
  Update  $\psi$  by maximizing  $\mathbb{E}_{(y,\tau)\sim\tilde{\mathcal{D}}}[y \cdot \log P_\psi(\tau) + (1-y) \cdot \log(1 - P_\psi(\tau))]$ 
for each iteration do
  Update  $p, q_{\phi_2}, p_{\phi_1}$  by optimizing  $\mathcal{L}^{prior}$  (3)           {Update preference weighted behavioral prior}
==== Skill Execution Phase ====
Initialize parameters of actor  $\pi_{\theta_1}$ , critics  $Q_{\theta_2}$  and  $Q_{\bar{\theta}_2}$  and reward model  $\hat{R}_\eta$ 
Initialize a dataset of preference  $\mathcal{D} \leftarrow \emptyset$  and a dataset of transitions  $\mathcal{B} \leftarrow \emptyset$ 
for Each iteration do
  for Each environment step do
     $z_t \sim \pi(z_t|s_t), s_{t+H} \sim p(s_{t+H}|s_t, z_t), \mathcal{B} \leftarrow \mathcal{B} \cup (s_t, z_t, \hat{R}_\eta(s_t, z_t), s_{t+H})$ 
  if iteration %  $K == 0$  then
    for step  $t = 1 \dots M$  do
       $(\tau_0^{(z)}, \tau_1^{(z)}) \sim \mathcal{B}$ , query human for label  $y, \mathcal{D} \leftarrow \mathcal{D} \cup (\tau_0^{(z)}, \tau_1^{(z)}, y)$            {Get preference labels}
    for each gradient step of  $\hat{R}_\eta$  do
      Sample  $(\tau_0^{(z)}, \tau_1^{(z)}, y) \sim \mathcal{D}$ , update  $\hat{R}_\eta$  with  $\min \mathcal{L}^{reward}$  (7)           {Update preferences}
      Relabel entire replay buffer  $\mathcal{B}$  with  $\hat{R}_\eta$ 
    for each gradient step of agent do
      Sample  $(s, a, s', R) \sim \mathcal{B}$ , update  $\pi_{\theta_1}$  by optimizing  $\mathcal{L}_{actor}^{SAC}$  (Appendix B.1)           {Update agent}
      Update  $Q_{\theta_2}$  and  $Q_{\bar{\theta}_2}$  by optimizing  $\mathcal{L}_{critic}^{SAC}$  (Appendix B.1)

```

---

et al. (2019); Wu et al. (2019) the weight is determined through the human preference function and we aim to maximize action-sequence likelihood as opposed to single-timestep actions.

We formulate this as:

$$p_\alpha \in \arg \max_{\alpha} \mathbb{E}_{\tau \sim \mathcal{D}} \left[ \sum_{t=0}^{|\tau|} \omega(\tau_t) \cdot p_\alpha(\mathbf{a}_t | s_t) \right] \text{ such that } \mathbb{E}_{\tau \sim \mathcal{D}} [D_{KL}(p_\alpha || \bar{p})] \leq \delta, \quad (2)$$

where  $\bar{p}$  denotes the empirical behavioral policy and  $\omega(s_t, a_t)$  is the weighting function. The non-parametric solution to the above optimization is given by:

$$p_\alpha(\mathbf{a}_t | s_t) \propto \bar{p}(\mathbf{a}_t | s_t) \cdot \exp(\omega(\tau_t)/\eta),$$

where we have used  $\propto$  to avoid specification of the normalization factor, and  $\eta$  represents a temperature parameter that is related to the constraint level  $\delta$ . The above non-parametric policy can be projected into the space of parametric neural network policies as Peng et al. (2019); Siegel et al. (2020):

$$p_\alpha \in \arg \max_{\alpha} \mathbb{E}_{\tau \sim \mathcal{D}} \left[ \sum_{t=0}^{|\tau|} \exp(\omega(\tau_t)/T) \cdot \log(p_\alpha(\mathbf{a}_t | s_t)) \right]. \quad (3)$$

For the choice of the weighting function, we use the learned preference classifier  $P_\psi(y|\tau)$  which inputs a trajectory and outputs the likelihood of this trajectory being human-preferred with  $y \in [0, 1]$ .  $P_\psi(y|\tau)$  is learned by sampling a small subset of the offline dataset and soliciting human feedback to label preferred versus not preferred trajectory:  $\omega(\tau_t) := \log P_\psi(\tau_t)$ .

In this process, we treat the temperature  $\eta$  as the hyper-parameter choice. This implicitly defines the constraint threshold  $\delta$ , and makes the problem specification and optimization more straightforward. For our practical implementation, we fit a variational autoencoder similar to Ajay et al. (2021); Pertsch et al. (2020) but softly weighted to maximize the likelihood of human-preferred transitions. We introduce a latent variable  $z$  with a Gaussian prior such that the ELBO loss is given by:

$$\log p(\mathbf{a}_t | s_t) \geq \mathbb{E}_{\tau \sim \mathcal{D}, z \sim q_{\phi_2}(z|\tau)} \left[ \underbrace{\log p_{\phi_1}(\mathbf{a}_t | s_t, z)}_{\mathcal{L}_{rec}} + \beta \underbrace{(\log p(z) - \log q_{\phi_2}(z|\tau))}_{\mathcal{L}_{reg}} \right]. \quad (4)$$

This is the standard  $\beta$ -VAE loss applied to action sequence modeling where  $\beta$  is a scalar controlling the regularization strength and  $\phi_1, \phi_2$  are neural network parameters that are optimized during training. Note that  $q_{\phi_2}$  encodes trajectories into a latent vector and  $p_{\phi_1}$  decodes latent vectors and the starting state back into action sequences. Our training objective weighs this loss with the preference function. Thus, our overall skill extraction objective is to maximize:

$$\mathcal{L} = \arg \max_{\phi_1, \phi_2} E_{\tau \sim \mathcal{D}, z \sim q_{\phi_2}(z|\tau)} [P_{\psi}(\tau)(\mathcal{L}_{\text{rec}} + \mathcal{L}_{\text{reg}})]. \quad (5)$$

**Reward learning and human preferences over skills (Skill Execution):** Unlike traditional RL where the hand-engineered rewards are available, we consider the preference-based RL framework (Christiano et al., 2017; Ibarz et al., 2018; Lee et al., 2021; Leike et al., 2018): a (human) teacher provides preferences between the agent’s behaviors and the agent uses this feedback to perform the task. In order to incorporate human preferences into deep RL, Christiano et al. (2017) proposed a framework that learns a reward function  $\widehat{R}_\eta$  from preferences. In this work, we modify the preference framework to operate not over atomic state-action transitions but rather state-skill transitions that have substantially longer time spans.

Formally, we assume access to an offline dataset (the agent’s replay buffer)  $\mathcal{B}$  of state-action transitions and sample state-skill sequence pairs  $\tau_1^{(z)}, \tau_2^{(z)}$  for which a human provides a binary label  $y \in \{0, 1\}$ , where  $\tau^{(z)} = (s_t, z_t, s_{t+H}, z_{t+H}, \dots, s_{(t+M)H}, z_{(t+M)H})$  where  $H$  is the length of actions the skill decodes to and  $M$  is the total number of state-skill transitions. Note how such trajectories are  $H$  times longer than if we were to sample state-action trajectories of length  $M$ .

The reward function  $\widehat{R}$  therefore fits a Bernoulli distribution across sequences. In this work, we learn a parameterized reward function  $\widehat{R}_\eta$  as in (Lee et al., 2021) utilizing a Bradley-Terry model Bradley & Terry (1952) in the following manner:

$$P_\eta[\tau_1^{(z)} \succ \tau_0^{(z)}] = \frac{\exp \sum_t \widehat{R}_\eta(s_t^1, z_t^1)}{\sum_{i \in \{0,1\}} \exp \sum_t \widehat{R}_\eta(s_t^i, z_t^i)}. \quad (6)$$

Here, the operator  $A \succ B$  means that  $A$  is preferred to  $B$ .  $\widehat{R}_\eta$  can therefore be interpreted as a binary preference classifier where labels are provided through human feedback. The parameters  $\eta$  of the neural network are updated by optimizing a binary cross-entropy loss:

$$\mathcal{L}^{\text{Reward}} = -\mathbb{E}_{(\tau^0, \tau^1, y) \sim \mathcal{D}} [y(0) \log P_\eta[\tau_0^{(z)} \succ \tau_1^{(z)}] + y(1) \log P_\eta[\tau_1^{(z)} \succ \tau_0^{(z)}]]. \quad (7)$$

## 4 EXPERIMENTAL SETUP

**Environments:** For our experiments, we use the robot kitchen environment and offline dataset from the D4RL suite Fu et al. (2020). This environment requires a 7-DOF (6-DOF arm and 1-DOF gripper) robotic arm to solve complex multi-step tasks in a kitchen. Due to the 7-DOF control and compositional long-horizon nature of the tasks, this environment cannot be solved by standard methods such as SAC or behavior cloning Pertsch et al. (2020).

**Offline dataset:** We desire our method to work on suboptimal offline data and, unlike prior skill extraction approaches Pertsch et al. (2020); Singh et al. (2021); Ajay et al. (2021) do not assume that the offline dataset consists solely of expert demonstrations. We simulate a noisy offline dataset by combining 601 expert trajectories and 601 noisy trajectories generated by random policy. The expert trajectories involve various structured kitchen interactions such as opening the microwave and operating the stove. We solicit human feedback on 10% of the total trajectories or equivalently 120 human labels .

**Downstream tasks:** We use 6 different downstream tasks shown in Fig. 2 that vary in difficulty to evaluate our approach. The task suite consists of tasks that require one, two, or three subtasks to be completed in a row in order to achieve the overall goal. We note that even the tasks with one subtask is challenging for RL methods that operate over atomic actions and do not leverage skills, as is shown in the experimental results.

**Simulated human:** Similar to prior work (Christiano et al., 2017; Lee et al., 2021), we obtain feedback from simulated human teachers instead of real humans. During skill extraction, human

provides labels whether a trajectory is noisy or structured.<sup>1</sup> During skill execution, the simulated human assigns positive labels to trajectory segments that have made more progress toward completing the desired task. Progress is calculated by computing  $\|s_{M-H} - \bar{s}\|_2 - \|s_1 - \bar{s}\|_2$ , where  $\bar{s}$  is the state when the target task is completed.




Figure 2: We evaluate in the robot kitchen environment from D4RL Fu et al. (2020), which requires a 7-DOF robotic arm to operate a kitchen. Within this environment, we consider a variety of manipulation tasks of varying difficulty. The simplest tasks involve one subtask - opening a microwave or moving the kettle - while more challenging tasks require the agent to compose multiple subtasks. Overall, we consider 6 evaluation tasks that require chaining one, two, or three subtasks.




Figure 3: An illustration of the skill extraction procedure within the robot kitchen environment. Starting with a noisy offline dataset, which consists of both expert and random actions, our method fits a behavioral prior to the offline data using human feedback to identify human-preferred motions which results in a set of diverse skills that can then be finetuned to downstream tasks.

**Baselines:** In addition to our method, we compare to *Atomic Preferences* which we based on PEBBLE Lee et al. (2021): a state-of-the-art human preference RL method. it pretrains the SAC agent with behavior cloning over the optimal offline dataset and trains the online SAC agent with human preferences over atomic transitions instead of high-level skill transitions. We also compare to *Flat Prior* which learns a single-step action prior on the atomic action space over the optimal dataset and trains an online SAC agent regularized with the action prior over ground-truth reward. The Oracle we compare to is *SPiRL*, a leading skill extraction with access to the ground truth (expert demonstrations and ground truth reward) in Fig. 4.

## 5 EXPERIMENTAL RESULTS

For the experimental evaluation of our approach, we investigate the following questions: (a) Can SkiP solve challenging long-horizon tasks and how does our method compare to prior leading approaches? (b) How do SkiP compare to an oracle baseline that extracts skills from perfect expert demonstrations and has access to the ground truth reward? (c) Is it necessary to provide human feedback during skill extraction or is it sufficient to fit an unweighted behavioral prior over the offline data? (d) How should we incorporate human feedback during the skill execution phase?

**Main Results:** We evaluate SkiP and related baselines on the 6 tasks shown in Fig. 2 and display the learning curves in Fig. 4. We observe that SkiP is the only method (except for the Oracle) that is

<sup>1</sup>Here, we remark that limited number of human labels (10% of the total trajectories) is utilized in our experiments for skill extraction.




Figure 4: SkiP and baselines (Sec. 4) evaluated over six tasks in the robot kitchen environment shown in Fig. 2. SkiP outperforms both baselines across the majority of the tasks and is the only method that is capable of matching the Oracle on most tasks. We also compare SkiP to SkiP with 3x more human labels and find comparable performance between the two versions. SkiP solves most tasks given 300-1000 human labels depending on the complexity of the task.

capable of solving the majority of tasks in the robot kitchen task suite and outperforms the baselines on all environments. On 5 out of 6 tasks, SkiP is able to match the oracle baseline asymptotically which means that it arrives at the optimal solution.

SkiP is also human-label efficient. During skill extraction, only 120 labels are required to train the preference classifier. During skill execution, 300-1K labels are required to solve most tasks depending on the task’s complexity. We hypothesize that human label efficiency is better during the skill extraction phase because classifying structured and noisy skills from a static offline dataset is easier than classifying task-specific preferences from an evolving replay buffer. Further human label efficiency improvements pose interesting research directions for future work.

**Ablation Studies:** To further understand the properties of the SkiP algorithm, we investigate whether human feedback is necessary during skill extraction as well as how the human preference reward function compares to alternate approaches to human feedback during skill execution.

*Is it necessary to provide human feedback during skill extraction or is it sufficient to fit an unweighted behavioral prior over the offline data?* The offline dataset used throughout this paper consists of suboptimal data that is a mixture of expert and random actions. We compare fitting a human-feedback weighted behavioral prior as opposed to an unweighted behavioral prior that maximizes the likelihood of all action sequences equally. For the skill execution phase, both methods have access to the same human preference reward function. The results shown in Fig. 5 indicate that the method, which extracts skills without human feedback, is unable to solve any of the tasks suggesting that human feedback is essential for skill extraction from suboptimal offline data.

*How should we incorporate human feedback during the skill execution phase?* Instead of preferences, a simpler approach to learning from human feedback is to provide binary feedback if a task (or subtask) has been solved and learning a reward classifier to guide the RL agent. We implement this by providing a positive reward of 1 for a high-level transition  $(s_t, z, s_{t+H})$  when a subtask has been completed and 0 otherwise. Using the same number of human queries for both approaches, we compare learning with preferences as opposed to learning from sparse rewards. For both approaches, we use human feedback for skill extraction. As shown in Fig. 6, RL with a reward classifier for sub-task completion is able to solve some tasks but generally performs much worse than RL with human preferences.

## 6 RELATED WORK

**Human-in-the-loop Reinforcement Learning:** Several works have successfully utilized feedback from real humans to train RL agents (Arumugam et al., 2019; Christiano et al., 2017; Ibarz et al., 2018; Knox & Stone, 2009; Lee et al., 2021; MacGlashan et al., 2017; Warnell et al., 2018). One of






Figure 5: SkiP with human feedback vs SkiP without human feedback during skill extraction. Learning curve with shaded region representing standard error across three seeds. Both algorithms learn prior from the suboptimal dataset and were evaluated with online RL. SkiP with human feedback outperforms SkiP without human feedback on all 6 environments




Figure 6: SkiP with preferences vs SkiP with learned sparse reward. Learning curve with shaded region representing standard error across three seeds. Both algorithms use the same prior. SkiP with preferences outperforms SkiP with learned sparse reward on 5 out of 6 environments.

major directions is directly utilizing the human feedback as a learning signal (Pilarski et al., 2011; MacGlashan et al., 2017; Arumugam et al., 2019) but assumed unlimited access to human labels which limited their practicality for more challenging tasks. To address this limitation, a number of works proposed learning reward model from human feedback (Knox & Stone, 2009; Warnell et al., 2018; Pinto & Gupta, 2016; Levine et al., 2018; Fu et al., 2018; Xie et al., 2018). Recently, several works have successfully combined human preferences with deep RL algorithms to learn basic locomotion skills as well as playing video games from pixels using human (Christiano et al. (2017); Ibarz et al. (2018); Cao et al. (2020); Lee et al. (2021)). However, these methods are limited to short-horizon or cyclic tasks and do not scale to more challenging compositional multi-step tasks. In this work, we investigate how to scale human preferences to such challenging tasks by specifying preferences over skills.

**Data-driven Extraction of Behavioral Priors:** Behavioral prior or skill extraction refers to fitting a distribution over an offline dataset of demonstrations and biasing the agent’s policy towards the most likely actions from that distribution. Commonly used for offline RL Wu et al. (2019); Siegel et al. (2020); Peng et al. (2019), behavioral priors learned through maximum likelihood latent variable models can also be used as skills for structured exploration in RL Singh et al. (2021), to solve complex long-horizon tasks from sparse rewards Pertsch et al. (2020); Ajay et al. (2021), and regularize offline RL policies Wu et al. (2019); Peng et al. (2019); Nair et al. (2020). A limita-



tion of these skill extraction methods is that the quality of the behavioral prior is highly dependent on the demonstrations in the offline dataset. Since a behavioral prior models maximum likelihood transitions in the offline dataset, suboptimal, noisy, or irrelevant transitions can degrade downstream policy learning. In this work, we introduce human feedback into the skill extractions phase to learn a human preferred behavioral prior which enables skill extraction methods to be robust to suboptimal offline data.

## 7 CONCLUSION

We presented Skill Preferences (SkiP) an algorithm that uses human feedback for both skill extraction as well as execution, and showed that SkiP enables robotic agents to solve long-horizon compositional manipulation tasks. We hope that this work excites other researchers about the potential of learning with skills and human feedback.

## ACKNOWLEDGMENTS

We would like to thank Berkeley DeepDrive, Tencent, ONR Pecase N000141612723, and NSF NRI 2024675 for supporting this research.

## REFERENCES

- Anurag Ajay, Aviral Kumar, Pulkit Agrawal, Sergey Levine, and Ofir Nachum. {OPAL}: Offline primitive discovery for accelerating offline reinforcement learning. In *International Conference on Learning Representations*, 2021. URL <https://openreview.net/forum?id=V69LGwJ01IN>.
- Ilge Akkaya, Marcin Andrychowicz, Maciek Chociej, Mateusz Litwin, Bob McGrew, Arthur Petron, Alex Paino, Matthias Plappert, Glenn Powell, Raphael Ribas, et al. Solving rubik’s cube with a robot hand. *arXiv preprint arXiv:1910.07113*, 2019.
- Dario Amodei, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. Concrete problems in ai safety. *arXiv preprint arXiv:1606.06565*, 2016.
- Dilip Arumugam, Jun Ki Lee, Sophie Saskin, and Michael L Littman. Deep reinforcement learning from policy-dependent human feedback. *arXiv preprint arXiv:1902.04257*, 2019.
- Ralph Allan Bradley and Milton E Terry. Rank analysis of incomplete block designs: I. the method of paired comparisons. *Biometrika*, 39(3/4):324–345, 1952.
- Zehong Cao, KaiChiu Wong, and Chin-Teng Lin. Human preference scaling with demonstrations for deep reinforcement learning. *arXiv preprint arXiv:2007.12904*, 2020.
- Paul F Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences. In *Advances in neural information processing systems*, 2017.
- Justin Fu, Avi Singh, Dibya Ghosh, Larry Yang, and Sergey Levine. Variational inverse control with events: A general framework for data-driven reward definition. In *Advances in Neural Information Processing Systems*, 2018.
- Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4rl: Datasets for deep data-driven reinforcement learning. *arXiv preprint arXiv:2004.07219*, 2020.
- Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International Conference on Machine Learning*, 2018.
- Dylan Hadfield-Menell, Smitha Milli, Pieter Abbeel, Stuart Russell, and Anca Dragan. Inverse reward design. In *Advances in Neural Information Processing Systems*, 2017.
- Borja Ibarz, Jan Leike, Tobias Pohlen, Geoffrey Irving, Shane Legg, and Dario Amodei. Reward learning from human preferences and demonstrations in atari. *Advances in neural information processing systems*, 2018.

- Dmitry Kalashnikov, Alex Irpan, Peter Pastor, Julian Ibarz, Alexander Herzog, Eric Jang, Deirdre Quillen, Ethan Holly, Mrinal Kalakrishnan, Vincent Vanhoucke, et al. Qt-opt: Scalable deep reinforcement learning for vision-based robotic manipulation. In *Conference on Robot Learning*, 2018.
- W Bradley Knox and Peter Stone. Interactively shaping agents via human reinforcement: The tamer framework. In *International Conference on Knowledge Capture*, 2009.
- Kimin Lee, Laura Smith, and Pieter Abbeel. Pebble: Feedback-efficient interactive reinforcement learning via relabeling experience and unsupervised pre-training. *arXiv preprint arXiv:2106.05091*, 2021.
- Jan Leike, David Krueger, Tom Everitt, Miljan Martic, Vishal Maini, and Shane Legg. Scalable agent alignment via reward modeling: a research direction. *arXiv preprint arXiv:1811.07871*, 2018.
- Sergey Levine, Peter Pastor, Alex Krizhevsky, Julian Ibarz, and Deirdre Quillen. Learning hand-eye coordination for robotic grasping with deep learning and large-scale data collection. *The International Journal of Robotics Research*, 37(4-5):421–436, 2018.
- James MacGlashan, Mark K Ho, Robert Loftin, Bei Peng, David Roberts, Matthew E Taylor, and Michael L Littman. Interactive learning from policy-dependent human feedback. In *International Conference on Machine Learning*, 2017.
- Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Belle-mare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.
- Ashvin Nair, Abhishek Gupta, Murtaza Dalal, and Sergey Levine. Awac: Accelerating online reinforcement learning with offline datasets, 2020.
- OpenAI. Openai five. <https://blog.openai.com/openai-five/>, 2018.
- Xue Bin Peng, Aviral Kumar, Grace Zhang, and Sergey Levine. Advantage-weighted regression: Simple and scalable off-policy reinforcement learning. *CoRR*, abs/1910.00177, 2019. URL <http://arxiv.org/abs/1910.00177>.
- Karl Pertsch, Youngwoon Lee, and Joseph J. Lim. Accelerating reinforcement learning with learned skill priors. In *Conference on Robot Learning (CoRL)*, 2020.
- Patrick M Pilarski, Michael R Dawson, Thomas Degris, Farbod Fahimi, Jason P Carey, and Richard S Sutton. Online human training of a myoelectric prosthesis controller via actor-critic reinforcement learning. In *International Conference on Rehabilitation Robotics*, 2011.
- Lerrel Pinto and Abhinav Gupta. Supersizing self-supervision: Learning to grasp from 50k tries and 700 robot hours. In *International Conference on Robotics and Automation*, 2016.
- Noah Siegel, Jost Tobias Springenberg, Felix Berkenkamp, Abbas Abdolmaleki, Michael Neunert, Thomas Lampe, Roland Hafner, and Martin A. Riedmiller. Keep doing what worked: Behavioral modelling priors for offline reinforcement learning. *ArXiv*, abs/2002.08396, 2020.
- David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *Nature*, 550(7676):354–359, 2017.
- David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Artfhur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, et al. A general reinforcement learning algorithm that masters chess, shogi, and go through self-play. *Science*, 362(6419):1140–1144, 2018.
- Avi Singh, Huihan Liu, Gaoyue Zhou, Albert Yu, Nicholas Rhinehart, and Sergey Levine. Parrot: Data-driven behavioral priors for reinforcement learning. In *International Conference on Learning Representations*, 2021. URL <https://openreview.net/forum?id=Ysuv-WOFeKR>.

- Alexander Matt Turner, Neale Ratzlaff, and Prasad Tadepalli. Avoiding side effects in complex environments. *arXiv preprint arXiv:2006.06547*, 2020.
- Oriol Vinyals, Igor Babuschkin, Wojciech M Czarnecki, Michael Mathieu, Andrew Dudzik, Junyoung Chung, David H Choi, Richard Powell, Timo Ewalds, Petko Georgiev, et al. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, 575(7782):350–354, 2019.
- Garrett Warnell, Nicholas Waytowich, Vernon Lawhern, and Peter Stone. Deep tamer: Interactive agent shaping in high-dimensional state spaces. In *Conference on Artificial Intelligence*, 2018.
- Yifan Wu, George Tucker, and Ofir Nachum. Behavior regularized offline reinforcement learning. *CoRR*, abs/1911.11361, 2019. URL <http://arxiv.org/abs/1911.11361>.
- Annie Xie, Avi Singh, Sergey Levine, and Chelsea Finn. Few-shot goal inference for visuomotor learning and planning. In *Conference on Robot Learning*, 2018.
- Daniel M. Ziegler, Nisan Stiennon, Jeffrey Wu, Tom B. Brown, Alec Radford, Dario Amodei, Paul F. Christiano, and Geoffrey Irving. Fine-tuning language models from human preferences. *CoRR*, abs/1909.08593, 2019. URL <http://arxiv.org/abs/1909.08593>.